



Spray Adhesive (High – quality)

Technical Data Sheet

Model : TD03

Description

TODA Spray Adhesive is a multi-purpose ecological adhesive with strong bonding ability, it is made with up-to-date technology and equipment, it has super viscosity and long service life.

Features

1. Fast bonding speed, excellent and long lasting bonding power.
2. Compared with conventional adhesives, the difference is obvious (excellent) when contact shoes, anti-firing plate, aluminum-plastic plate and PVC board.
3. Good protective properties after hardening: anti petro, anti acid and alkali, impact resistant. Effectively prolong the service life of contacted objects.
4. Extra heat and cold resistant after hardening: Endurable when temperature is between -50°C and 100°C .

Technical Index

Appearance	:	Viscous liquid
Viscosity	:	230 ± 20 Mpas/ 25°C
Solids Content	:	18 - 20%
Specific Gravity	:	0.88 - 0.98 kg/L
Drying times	:	5 - 10 minutes
Shear Strength	:	30 minutes : ≥ 0.7 mpa 48 hours : ≥ 1.70 mpa
Application Tools	:	Spray gun
Shelf Life	:	12 months in sealed cans

Health and Safety

The product subject to legislation regulating their storage and use.

Storage and shelf life

Store in well sealed containers. Keep satisfactorily for at least 12 months. High temperature storage should be avoided and recommend to store within the temperature 5 to 35°c .