



## Contact Adhesive (High - quality)

## Technical Data Sheet

Model : TD04

### Description

TODA Contact Adhesive is a multi-purpose ecological adhesive with strong bonding ability, it is made with up-to-date technology and equipment, it has super viscosity and long service life.

### Features

1. Fast bonding speed, excellent and long lasting bonding power.
2. Compared with conventional adhesives, the difference is obvious (excellent) when contact shoes, anti-firing plate, aluminum-plastic plate and PVC board.
3. Good protective properties after hardening: anti petro, anti acid and alkali, impact resistant. Effectively prolong the service life of contacted objects.
4. Extra heat and cold resistant after hardening: Endurable when temperature is between  $-50^{\circ}\text{C}$  and  $100^{\circ}\text{C}$ .

### Technical Index

Appearance	:	Viscous liquid
Viscosity	:	$3000 \pm 500$ Mpas/ $25^{\circ}\text{C}$
Solids Content	:	20 - 22%
Specific Gravity	:	$1 \pm 0.5$ kg/L
Drying times	:	15 minutes
Shear Strength	:	30 minutes : $\geq 0.7$ mpa 48 hours : $\geq 1.70$ mpa
Application Tools	:	Brusher, Scroller, Shaver, Trowel, etc.
Shelf Life	:	12 months in sealed cans

### Health and Safety

The product subject to legislation regulating their storage and use.

### Storage and shelf life

Store in well sealed containers. Keep satisfactorily for at least 12 months. High temperature storage should be avoided and recommend to store within the temperature 5 to  $35^{\circ}\text{C}$ .