

Cable Fittings: Cable Gland for Non-Armoured Cable, DNA Series

Flameproof/ Increased Safety and Dust protection by enclosure

Zone 1 & 2 – 21 & 22



Application

The DNA cable glands are suitable for use in Zone 1, Zone 2, and Zone 21, Zone 22 hazardous areas, allowing direct insertion of normal non-armoured cables into Ex d equipment or enclosures.


Specification

Body, gland nut : Brass
(optional nickel-plated brass)
Thread seal : Nylon (PA6)
(for metric threads only)

Catalogue Number Logic

DNA /				
Series	Body	Threads	Option	
S	Small	N NPT	NI Nickel-plated	
M	Medium	M Metric		
L	Large			

Ordering Requirements



Technical Data

Hazardous Area	Gas	Dust
Zones	1 & 2	21 & 22
Equipment Group/Category	II 2G	II 2D
Symbol of Protection	Ex db eb IIC Gb	Ex tb IIC Db
Certificate	TÜV CY 18 ATEX 0206101X	
T Rating	Temperature class of enclosure to which will be connected.	
Conformity to Standards	EN IEC 60079-0, EN 60079-1, EN IEC 60079-7, EN IEC 60079-31	
Ambeint Temperature	-20°C to +75°C	
Index of Protection	IP66	

Note: Cables for fixed installations shall have flame propagation characteristics that enable them to withstand the tests according to IEC 60332-1-2 or IEC 60332-3-22.



Brass



Nickel-plated brass

Cat. No.	Entry threads (Male)		Cable dia. outer 'd'	Dimensions in mm				Approx. weight (kg)	Shroud Ref.
	Metric	NPT		l	a	Across corners	Across flats		
DNA/S -M0 -□	M16x1.5	-	3.0-8.6	25.0	15.0	26.5	24.0	0.06	SPV-24
DNA/S -M1 -□	M20x1.5	-		25.0	19.8	26.5	24.0	0.07	
DNA/S -N1 -□	-	1/2"		25.0	19.8	26.5	24.0	0.07	
DNA/M -M1 -□	M20x1.5	-	6.1-11.9	25.0	15.0	26.5	24.0	0.07	SPV-24
DNA/M -N1 -□	-	1/2"		25.0	19.8	26.5	24.0	0.07	
DNA/L -M1 -□	M20x1.5	-		26.0	15.0	35.0	31.75	0.09	
DNA/S -M2 -□	M25x1.5	-	6.5-14.3	26.0	19.8	35.0	31.75	0.11	SPV-31
DNA/L -N1 -□	-	1/2"		26.0	19.8	35.0	31.75	0.08	
DNA/S -N2 -□	-	3/4"		26.0	20.1	35.0	31.75	0.12	
DNA/M -M2 -□	M25x1.5	-	11.1-20.2	33.0	15.0	42.0	38.1	0.14	SPV-38
DNA/S -M3 -□	M32x1.5	-		33.0	20.1	42.0	38.1	0.18	
DNA/M -N2 -□	-	3/4"		33.0	25.0	42.0	38.1	0.21	
DNA/S -N3 -□	-	1"	17.0-26.5	34.0	15.0	49.0	44.4	0.19	SPV-44
DNA/M -M3 -□	M32x1.5	-		34.0	25.0	49.0	44.4	0.25	
DNA/S -M4 -□	M40x1.5	-		34.0	25.6	49.0	44.4	0.31	
DNA/M -N3 -□	-	1"	22.0-32.5	38.0	15.0	56.0	50.8	0.26	SPV-50
DNA/S -N4 -□	-	1-1/4"		38.0	25.6	56.0	50.8	0.38	
DNA/M -M4 -□	M40x1.5	-		38.0	26.0	56.0	50.8	0.30	
DNA/S -M5 -□	M50x1.5	-	29.5-38.1	38.0	15.0	63.0	57.1	0.41	SPV-57
DNA/M -N4 -□	-	1-1/4"		38.0	26.0	63.0	57.1	0.36	
DNA/S -N5 -□	-	1-1/2"		38.0	26.0	63.0	57.1	0.37	
DNA/M -M5 -□	M50x1.5	-	35.6-44.0	40.0	15.0	70.0	63.5	0.44	SPV-63
DNA/S -M6 -□	M63x1.5	-		40.0	26.0	70.0	63.5	0.65	
DNA/L -N5 -□	-	1-1/2"		40.0	26.9	70.0	63.5	0.47	
DNA/S -N6 -□	-	2"	39.0-44.0	40.0	15.0	84.0	76.2	0.67	SPV-76
DNA/M -M6S -□	M63x1.5	-		40.0	26.9	84.0	76.2	0.49	
DNA/S -M7S -□	M75x1.5	-		40.0	39.9	84.0	76.2	0.76	
DNA/M -N6S -□	-	2"	44.1-54.0	40.0	15.0	84.0	76.2	0.52	SPV-76
DNA/S -N7S -□	-	2-1/2"		40.0	26.9	84.0	76.2	0.95	
DNA/M -M6L -□	M63x1.5	-		40.0	26.9	84.0	76.2	0.49	
DNA/S -M7L -□	M75x1.5	-		40.0	39.9	84.0	76.2	0.76	
DNA/M -N6L -□	-	2"		40.0	26.9	84.0	76.2	0.52	
DNA/S -N7L -□	-	2-1/2"		40.0	39.9	84.0	76.2	0.95	

Thread seal



Body (Entry threads)



Neoprene inner sealing ring

Sealing washer



Gland nut