

Application

The EAH fixture hangers are designed for suspension or pipe pendant mounting of lighting fixtures. They are suitable for use in Zone 1, Zone 2, and Zone 22 hazardous (explosive) atmospheres.

Specification

Body material : Marine grade copper-free aluminium alloy with polyester powder coated, RAL 7032 (Grey)



Technical Data

Hazardous Area	Gas	Dust
Zones	1 & 2	22
Equipment Group/Category	II 2G	II 3D
Symbol of Protection	Ex d IIB Gb	Ex tc IIB Dc
Conformity to Standards	EN IEC 60079-0, EN 60079-1, EN IEC 60079-31	
Ambient Temperature	-20°C to +75°C	
Index of Protection	IP54	


Catalogue Number Logic

EAH			
Series	Entry arrangement	Entry threads	Fixture stem
C	2 hub straight	1 1/2" NPT	1 1/2" NPT
T	3 hub	2 3/4" NPT	2 3/4" NPT

Ordering Requirements

Cat. No.	Entry diagram	Entry threads	Fixture stem size	Volume (cm³)	Approx. weight (kg)
2 Hub straight					
EAHC 11		1/2" NPT	1/2" NPT	100	0.708
EAHC 12			3/4" NPT	110	
EAHC 21		3/4" NPT	1/2" NPT	110	0.698
EAHC 22			3/4" NPT	120	
3 Hub					
EAHT 11		1/2" NPT	1/2" NPT	110	0.786
EAHT 12			3/4" NPT	120	
EAHT 21		3/4" NPT	1/2" NPT	130	0.778
EAHT 22			3/4" NPT	130	

Dimensions (in mm)



Note: When conduit is used for entry, a sealing fitting and compound (flame-arresting element) shall be installed at the point of entry to the lighting fixture.