

ชัด3ล้าน PoE มีไมค์ในตัว



3 ล้านพิกเซล



LED แบบแสง 2 สี



ภาพสี 24 ชั่วโมง



ตรวจจับการเคลื่อนไหว



รองรับ PoE



มีไมค์ในตัว



IPC PoE Mic Built-in

Features

- * Image Sensor 1/2.7" CMOS Sensor
- * 3.0 Mega pixel IP Camera
- * 3.6mm / F1.3 Real time H.265
- * Dual light, MIC, PoE, IP66
- * Motion detection
- * Good image, Low price
- * Infrared LED 3PCS Smart Dual Light LED
- * Frame Rate 3MP / 2MP&25Fps
- * ONVIF 2.4 , RTSP, API, SDK
- * RTSP Code Main-stream RTSP://IP:Port/live/0/MAIN
Sub-stream RTSP://IP:Port/live/0/SUB



IP CAMERA 3.0MP

PoE Mic Bulit-in

SPECIFICATION

Image Sensor	1/2.7" CMOS Sensor
Pixels	3.0 Mega Pixel
Effective Pixels	2304 x 1296
Min. Illumination	Color: 0.01Lux
Shutter Speed	Auto: PAL 1/1-1/10000s; NTSC 1/1-1/10000s
Day/Night	Auto (ICR) / full Color B&W
Wide Dynamic Range	Digital WDR
S/N Ratio	≥52dB
White Balance	Auto
Gain Control	Auto
Backlight Compensation	Off / WDR / BLC / FLK (FlickerControl)
TV System	PAL / NTSC
Lens	
Focus Length	3.6mm
Aperture	F1.3
Focus Control	Fixed
Lens Type	Fixed
Fill Light	
Infrared LED	3PCS Smart Dual Light LED
Infrared Distance	30M
IR Status	Under 10 Lux
IR Power On	Lens Auto Contro
Video	
Compression	H.264, H.265, H.265+
Image Resolution	Main stream 3MP(2304x1296), 2MP(1920x1080) Sub-stream D1(704x576), 448P(800x448, 360P(640x360), CIF(352x288)
Frame Rate	3MP / 2MP & 25Fps
Bitrate Control	VBR/CBR
Dual-stream	Supported
Digital Noise Reduction	3D noise reduction

Model

HP-30B302PEL-M

Image Control	Saturation, Brightness, Contrasts, Sharpness, Mirror, Defogging
Privacy Masking	3 Rectangular Zone
OSD	Supported
Audio	
Audio Compression	G.711U/A
Audio input	Mic built-in, Sensitive adjustable
Network	
Network Protocols	ONVIF, CGI, HTTP, TCP/IP, IPv4, RTSP, UDP, NTP, DST, DHCP, DNS
Security	IP Filter, Users management
Cloud	P2P
User Interface	Web, App (iOS, Android)
Max. User	3
Aplication Programing	ONVIF2.4, RTSP, API, SDK
Video Delay	0.3S (Within the Lan)
Intelligent Functions	
Normal Events	Motion detection
External Interfaces	
Network	10/100M, RJ-45 interface (PoE)
Audio input	Mic built-in
Operation Environment	
Operating Temperature	-30° C ~ +60° C
Operating Humidity	RH95% MAX
Protection Level	IP66
Electrical	
Power	DC12V±10%, 1000mA
Power Consumption	IR Off: 90MA. IR ON: 500MA
POE	Supported
Mechanical	
Weight	0.6kg
Dimension	175x68x66mm
Housing	Metal+Plastic