



IP CAMERA

HP-30D30PEL-M

Onvif

ชัด 3 ล้าน PoE มีไมค์ในตัว



3 ล้านพิกเซล



LED แบบแสง 2 สี



ภาพสี 24 ชั่วโมง



ตรวจจับการเคลื่อนไหว



รองรับ PoE



มีไมค์ในตัว



PoE
Mic Built-in

Features

- * Image Sensor 1/3" CMOS Sensor
- * 3.0 Mega pixel IP Camera
- * Lens 3.6mm / F1.3
- * IR Distance 25-30 meters
- * Compression H.264 / H.265 / H.265+
- * DC12V / PoE, IP66
- * Motion detection
- * Built-in Microphone
- * Light Function Infrared LED + White Light
- * ONVIF, RTSP, HTTP, P2P (QR Code via Hiplus app)



IP CAMERA 3.0MP

PoE Mic Bulit-in

SPECIFICATION

Type	3.0MP Dome IP Camera
Image Sensor	1/3" High-resolution CMOS
Resolution	3MP (2304 × 1296)
Effective Pixels	2304 × 1296
Compression	H.264 / H.265 / H.265+
TV System	PAL / NTSC
Electronic Shutter	Auto: PAL 1/25–1/10000s; NTSC 1/25–1/10000s
S/N Ratio	≥ 52dB
Scanning System	Progressive
Video Output	RJ45
Lens Type	Fixed
Lens	3.6mm / F1.3
Field of View	~78°
Night Vision (Light Function)	Infrared LED + White Light
IR Distance	25–30 meters
Light Modes	Full Color 24/7 (Default) B/W (IR only) Smart Mode (B/W at night, White Light turns on when motion is detected ⇨ Color)

Model

HP-30D30PEL-M

Audio	Built-in Microphone
Network	ONVIF, RTSP, HTTP, P2P (QR Code via Hiplus app)
Remote Functions	Live View, Playback, Motion Detection, Video Tampering, Alarm Trigger, Smart Light Control, Remote Configuration, Firmware Upgrade
User Management	Add/Delete/Edit users, Access rights
Maintenance	Reboot, Export/Import Config, System Log
Power Supply	DC12V / PoE (IEEE 802.3af)
Power Consumption	< 5W
Ingress Protection	IP66 (Waterproof & Dustproof)
Housing Material	Metal (Weather-resistant)
Operating Temperature	-20°C ~ +55°C