



5M PIXEL
Video Recorder



FACE DETECTION



HA-75504-AI

DVR 5IN1 SYSTEM

AHD / TVI / CVI / CVBS / IPC SYSTEM SUPPORT





5M PIXEL

Video Recorder



FACE DETECTION



Specification

Model		HA-75504-AI
Inputs	8Mbps ~24Mbps Decrease one Analog channel can increase 4Mbps Analog channel and digital channel can be converted	
out	48Mbps	
Analog video-input	4CH inputs	
Live		
IP Video Input	2ch,(only IP up to 6ch)	
Composite Video Input	up to 6 ch (Analog video + IP video)	
Recording and Playback		
Compression	Audio: G.711a, Video: H.264 / H.265	
Display resolution	Analog: 5MP-Lite: 20fps 4MP-Lite: 30 fps 1080P / 720P / 960H: 30fps IP: 5MP / 4MP / 1080P / 720P	
Speed	Main-stream Analog: 5MP-Lite: 20fps (each ch) 4MP-Lite: 30fps (each ch) 1080P / 720P: PAL: 25fps (each ch) NTSC: 30fps (each ch) IP: PAL: 25fps (each ch) NTSC: 30fps (each ch) Sub-stream Max PAL: 704*576: 10fps (each ch) NTSC: 704*480: 10fps (each ch)	
Event	MD (Sensitivity Level 1-8) Videlo loss Beep, Email, Push notification to Mobile APP	
Playback function	Fast forward / backward (2x, 4x, 8x,16x) Slow forward (1/2x, 1/4x, 1/8x, 1/16x)	
Playback	5MP-lite: 80fps (Max 4CH playback) 4MP-lite: 120fps (Max 4CH playback) 1080P: 120fps (Max 4CH playback) 720P: 120fps (Max 4CH playback)	
UI/Monitoring		
Local	UI5.0	
WEB	IE10/11, Safari V12.1 above, Firefox V.52 above Google chrome V.57 above, Edge V.79 above	

Feature

- * Analog video-input 4CH inputs
- * IP Video Input 2ch,(only IP up to 6ch)
- * Composite Video Input up to 6 ch (Analog video + IP video)
- * Compression Audio: G.711a
Video: H.264 / H.265
- * Playback5MP-lite:80fps (Max 4CH playback)
4MP-lite: 120fps (Max 4CH playback)
1080P: 120fps (Max 4CH playback)
720P:120fps (Max 4CH playback)
- * Ethernet 1 RJ45 10/100Base-T
- * USB2.0*1(front) / USB2.0*1+(rear)
- * Audio 4 in / 1 out
- * HDD 1 SATA Up to 10 TB capacity
- * RS485x1
- * Input Voltage/Current DC12V/2A

DVR 5IN1 SYSTEM

AHD / TVI / CVI / CVBS / IPC SYSTEM SUPPORT



5M PIXEL
Video Recorder



FACE DETECTION



Specification

Model		HA-75504-AI
Inputs	8Mbps ~24Mbps Decrease one Analog channel can increase 4Mbps Analog channel and digital channel can be converted	
out	48Mbps	
Analog video-input	4CH inputs	
Live		
IP Video Input	2ch,(only IP up to 6ch)	
Composite Video Input	up to 6 ch (Analog video + IP video)	
Recording and Playback		
Compression	Audio: G.711a, Video: H.264 / H.265	
Display resolution	Analog: 5MP-Lite: 20fps 4MP-Lite: 30 fps 1080P / 720P / 960H: 30fps IP: 5MP / 4MP / 1080P / 720P	
Speed	Main-stream Analog: 5MP-Lite: 20fps (each ch) 4MP-Lite: 30fps (each ch) 1080P / 720P: PAL: 25fps (each ch) NTSC: 30fps (each ch) IP: PAL: 25fps (each ch) NTSC: 30fps (each ch) Sub-stream Max PAL: 704*576: 10fps (each ch) NTSC: 704*480: 10fps (each ch)	
Event	MD (Sensitivity Level 1-8) Videlo loss Beep, Email, Push notification to Mobile APP	
Playback function	Fast forward / backward (2x, 4x, 8x,16x) Slow forward (1/2x, 1/4x, 1/8x, 1/16x)	
Playback	5MP-lite: 80fps (Max 4CH playback) 4MP-lite: 120fps (Max 4CH playback) 1080P: 120fps (Max 4CH playback) 720P: 120fps (Max 4CH playback)	
UI/Monitoring		
Local	UI5.0	
WEB	IE10/11, Safari V12.1 above, Firefox V.52 above Google chrome V.57 above, Edge V.79 above	

Feature

- * Analog video-input 4CH inputs
- * IP Video Input 2ch,(only IP up to 6ch)
- * Composite Video Input up to 6 ch (Analog video + IP video)
- * Compression Audio: G.711a
Video: H.264 / H.265
- * Playback5MP-lite:80fps (Max 4CH playback)
4MP-lite: 120fps (Max 4CH playback)
1080P: 120fps (Max 4CH playback)
720P:120fps (Max 4CH playback)
- * Ethernet 1 RJ45 10/100Base-T
- * USB2.0*1(front) / USB2.0*1+(rear)
- * Audio 4 in / 1 out
- * HDD 1 SATA Up to 10 TB capacity
- * RS485x1
- * Input Voltage/Current DC12V/2A

DVR 5IN1 SYSTEM

AHD / TVI / CVI / CVBS / IPC SYSTEM SUPPORT