



4M Megapixel
Network Camera Series



HP-78B40PEL-PAS

CAMERA 7800 SERIES

4Megapixel Network Camera





4M Megapixel
Network Camera Series



Specification



Feature

- * 1/3" Progressive CMOS, H.265/H.264
- * Pixels 4MP 1920(H) x 1080(V)
- * Focal Length (Zoom Ratio) 3.6 mm
- * Min. Object Distance 1m
- * IR LED 1 / WarmLight 2
- * Red Blue Light 2 (1 Red&1 Blue)
- * IR Viewable Length Up to 25m
- * WarmLight Viewable LengthUp to 20m
- * White Balance Auto / Manual
- * Storage Micro SD slot, up to 256GB
- * Audio Built-in microphone&Speaker
- * RJ45 (10/100BASE-T)
- * ONVIF(Profile S/G/T)
- * IP66
- * D12V / POE (IEEE802.3af)

CAMERA 7800 SERIES
4Megapixel Network Camera

Model		HP-78B40PEL-PAS
Imaging Device	1/3"	
Effective Pixels	4MP 1920(H) x 1080(V)	
Scanning System	Progressive CMOS	
Min. Illumination	Color 0.002lux @ F1.0 (AGC ON) B/W 0 lux @ IR ON	
Lens Type		
Focal Length (Zoom Ratio)	3.6 mm	
Max. Aperture Ratio	F No. 1.0	
Angular Field of View	Horizontal: 77° Vertical: 42° Diagonal: 90°	
Min. Object Distance	1m	
Lens Type	Fixed (M12)	
Network		
Ethernet	RJ45 (10/100BASE-T)	
Video Compression Format	H.265/H.264	
Resolution	Mainstream @ 25fps, 2MP (1920x1080) Substream @ 25fps, VGA (640x480)	
Video Quality Ajustment	512Kbps ~ 4Mbps	
Bitrate control method	CBR/VBR	
IP	IPv4	
Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, HTTPS	
Security	IP address filter; complicated password; Authenticated username and password	
Application Programming Interface	ONVIF (Profile S/G/T)	
Web Viewer	IE10/11	
Environmental		
Operating Conditions	-35~+60CC less than ≤ 95% RH	
Ingress Protection	IP66	
Electrical		
Input Voltage / Current	D12V / POE (IEEE802.3af)	
Power Consumption	1.2-6.8W	
Mechanical		
Material	Metal & Plastics	
Dimensions (HxWxD)	152.3*70.1mm	
Weight	282g	