

Specification



PoE Watchdog



Bt port support 60W



Hybrid PoE



Industrial grade chip



6KV Lightning protection



8KV ESD protection



Multiple installation



Temperature

Model	HS-SW10 2P8 GBT-AI
Ports	8x10/100/1000Mbps PoE Ports (RJ45) 2x10/100/1000Mbps Uplink Port (RJ45)
Transmission Rate	2000Mbps Full Duplex; 10 or 100 or 1000Mbps Half Duplex
Transmission Distance	130m
Performance	Bandwidth: 20Gbps Network Latency (10 to 1000Mbps): <16μs (use the 64byte package size) MAC address table:8K The Frame Filter & Transmission Rate: 14800pps the most for 10M port, 148800pps the most for 100M port 1488000pps the most for 1000M port
Networking	IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3xFlowControl IEEE 802.3af/at/bt Power over Ethernet
Power Support	Power input: AC 180V~240V / Total≤120W
Power output	PoE1~6Port:1/2(+52V),3/6(GND)≤30W PoE7~8Port:1245(+53V),3678(GND) compatible1/2(+52V),3/6(GND)≤60W
Size(L*W*H)	187mm*139mm*43mm
Working	Operating Temperature: -30C ~60C Storage Temperature: -40C ~70C Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing