

## Specification



PoE Watchdog



Bt port support 60W



Hybrid PoE



Industrial grade chip



6KV Lightning protection



8KV ESD protection



Multiple installation



Temperature

Model	HS-SW28 2P24 S2 HBT-AI
Ports	24X10/100Mbps PoE Ports (RJ45) 2X10/100/1000Mbps Uplink Port (RJ45) 2X10/100/1000Mbps SFP Port
Transmission Rate	2000Mbps Full Duplex; 10 or 100 or 1000Mbps Half Duplex
Transmission Distance	100Mbps / 10Mbps Adaptive MAX 250m
Performance Specification	Bandwidth: 12.8Gbps Network Latency (10 to 1000Mbps) ≤16μs (use the 64byte package size) MAC address table: 8K The Frame Filter & Transmission Rate: 14800pps the most for 10M port 148800pps the most for 100M port 1488000pps the most for 1000M port
Networking Standard	IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3ab 1000BASE-T IEEE 802.3x Flow Control IEEE 802.3af/at/bt Power over Ethernet
Power Support	Power Input: AC 180~240V Total≤300W AI Watchdog: Port 1~24 Power Output: PoE1~22Port:1/2(+52V),3/6(GND)≤30W PoE 23~24 Port:1245(+53V),3678(GND) Compatible1/2(+52V),3/6(GND)≤60W
Protection Level	Lightning Protection: 6KV ESD Protection: 8KV
Physical Specifications	Size(L*W*H): 440mm*180mm*45mm
Working Environment	Operating Temperature: -30C~60C Storage Temperature: -40C~70C
Operating Humidity	10%~90% Non-condensing
Storage Humidity	5%~90% Non-condensing