

Specification



PoE Watchdog



Bt port support 60W



Hybrid PoE



Industrial grade chip



6KV Lightning protection



8KV ESD protection



Multiple installation



Temperature

Model	HS-SW6 2P4 BT-AI
Ports	<p>PoE Ports: PoE1~4 100Mbps</p> <p>60W PoE Ports: PoE4 100Mbps</p> <p>Uplink Ports: LAN1-2 100Mbps</p>
Transmission Rate	<p>200Mbps Full Duplex;</p> <p>10 or 100Mbps Half Duplex</p>
Transmission Distance	250m
Performance	<p>Bandwidth: 1.2Gbps</p> <p>Network Latency (10 to 100Mbps):</p> <p><16μs (use the 64byte package size)</p> <p>MAC address table: 2K</p> <p>The Frame Filter & Transmission Rate:</p> <p>14800pps the most for 10M port,</p> <p>148800pps the most for 100M port</p>
Networking	<p>IEEE 802.3i 10BASE-T</p> <p>IEEE 802.3u 100BASE-TX</p> <p>IEEE 802.3xFlowControl</p> <p>IEEE 802.3af/at/bt Power over Ethernet</p>
Power Support	<p>Power input: AC 180V~240V</p> <p>Total≤60W</p>
Power output	<p>PoE1~3Port: 1/2(+52V), 3/6(GND)≤30W</p> <p>PoE 4 Port: 1245(+53V), 3678(GND)</p> <p>Compatible1/2(+52V), 3/6(GND)≤60W</p>
Size(L*W*H)	187mm*139mm*43mm
Working	<p>Operating Temperature: -30 ~60</p> <p>Storage Temperature: -40 ~70</p> <p>Operating Humidity: 10%~90%</p> <p>non-condensing</p> <p>Storage Humidity: 5%~90%</p> <p>non-condensing</p>