hi-view®
High Resolution High Technology

3MP NVR KIT
WIRELESS SURVEILLANCE SYSTEM

HW-3308KIT304M-H3

3MP

hiviewwifi

Download on the App Store

GET IT ON Google Play

ULTRA Compression Code

3Mpixel

WIRELESS Network

HDMI HIGH-DEFINITION MULTIMEDIA INTERFACE

CLOUD

P2P

3MP NVR KIT
WIRELESS SURVEILLANCE SYSTEM

hi-view
High Resolution High Technology

3Mpixel | WIRELESS Network | HDMI HIGH-DEFINITION MULTIMEDIA INTERFACE | CLOUD | P2P

Features

* 3MP/1080P/960P/720P Wireless Network Video Recorder
* Built-in WIFI module with high-performance and high stability
* Automatically Connection between NVR and IPC
* Support video preview / recording / playback backup
* Support the mixed use of wireless and wire, support different scene
* Support Android/IOS/PC remote

ULTRA
Compression Code

Specification

Model	HW-3308M-H3
Video input	8ch 720P/960P/1080P/3MP
HDMI Output	1 ch, resolution: 1024x768, 1280x1024, 1366x768, 1440x900, 1920x1080, 2K, support audio output
VGA Output	1 ch, resolution: 1024x768, 1280x1024, 1366x768, 1440x900, 1920x1080p
Resolution	720P/960P/1080P/3MP/5MP
Playback	4ch
Recording	Manual,time,motion dection,alarm
Storage	1 SATA
Storage capacity	6TB for each HDD
Network interface	1 RJ45 10M/100M, 2 WIFI connector
USB interface	2 USB2.0
Audio interface	3.5 mm headphone jack
Power consumption	≤5W
Power	DC12V
working temperature	-10°C--+55°C
Dimension (mm)	258*210*42mm
Working humidity	10%--90%RH

hi-view®
High Resolution High Technology

3MP NVR KIT
WIRELESS SURVEILLANCE SYSTEM

3MP NVR KIT WIRELESS SURVEILLANCE SYSTEM

3Mpixel | WIRELESS Network | HDMI HIGH-DEFINITION MULTIMEDIA INTERFACE | CLOUD | P2P

Features

* 3MP/1080P/960P/720P Wireless Network Video Recorder
* Built-in WIFI module with high-performance and high stability
* Automatically Connection between NVR and IPC
* Support video preview / recording / playback backup
* Support the mixed use of wireless and wire, support different scene
* Support Android/IOS/PC remote

Specification

Model	HW-33B304M-H3
Sensor	1/3" Progressive Scan Sensor
Signal System	PAL/NTSC
Resolution	2304x1296 16:9High Defination
Minimum illumination	Color: 0.01 Lux; B/W: 0.001 Lux
Shutter	1/25s to 1/25,000s
Lens	4mm
OSD	Date Time & Title
White Balance	Auto
Day&Night	Auto / Color / BW
3D-DNR	Auto
Mirror/Flip	On / Off
smart stream	Dual-stream: 2304x1296@15fps
	640x360@15fps
S/N	> 39.1 Db
Interface	RJ45 / WIFI 802.11b/g/n
Anti-thunder Level	Standard IEC61000-4-5
Working Temperature / Humidity	-10°C to +50°C / 30% to 80% RH
Working Temperature / Humidity	-20°C to +60°C / 20% to 90% RH
Power Input	DC12V-1A
Power consumption	$\leq$ 6W
Size	66*180mm
Weight	500g
Level of Protection	IP66

ULTRA
Compression Code