

AIR RIT AIR TOOLS

เครื่องมือลม

AIR BELT SANDER



ABS-10330



ABS-20520



ABS-20760



ABS-RMB2

Model No.	Belt Size (mm)	Free Speed (RPM)	Net Weight (g)	Air Inlet	Air Pressure (kg/cm ²)	Air Consumption (CFM)	Sound Level (dBA)
ABS-10330	10 x 330	16,000	886	1/4"	6.3	4	80
ABS-20520	20 x 520	16,000	1,295	1/4"	6.3	4	80
ABS-20760	20x760/40x760	4,500	3,400	1/4"	6.3	4	80
ABS-20760	60 x 260	700	1,100	1/4"	6.3	4	80



ABS10330RG



ABS6330RG-SA



ABS20520RG-SA



ABS20520RGT-SA

Model No.	Sanding Belt Size (mm)	Free Speed (RPM)	Overall Length	Air Inlet	Air Hose (I.D.)	Air Consumption
ABS10330RG	13 x 330	16,000	320 mm.	1/4"	3/8"	4 Cfm
ABS6330RG-SA	6 x 330	18,000	470 mm.	1/4"	3/8"	4 Cfm (170 L Min)
ABS20520RG-SA	20 x 520	18,000	470 mm.	1/4"	3/8"	4 Cfm (170 L Min)
ABS20520RGT-SA	20 x 520	18,000	470 mm.	1/4"	3/8"	4 Cfm (170 L Min)

AIR SANDER & AIR POLISHER



KAR550NV



KAR550CV



KAR550SV



ASYBB550SV



ASBGB550NV

Model No.	BackUp Pad Size	Orbit Diameter (mm.)	Free Speed (RPM)	Net Weight (g)	Vacuum Style	Air Consumption (L/min)	Sound Level (dBA)	Air Pressure (kg/cm ²)
KAR550NV	5inch (125mm)	5	13,000	700	Non Vacuum	340	70	6
KAR550CV	5inch (125mm)	5	12,000	755	Central Vacuum	340	70	6
KAR550SV	Sanding Pad Size 125 mm.(5")	5	12,000	790	Self-Generated Vacuum	340	80	6
ASYBB550SV	Sanding Pad Size 125 mm.(6")	5	12,000	940	Self-Generated Vacuum	340	80	6
ASBGB550NV	Sanding Pad Size 125 mm.(5")	5	12,000	930	Central Vacuum	340	80	6



KAR343NV



KAR343CV



KAR343SV

Model No.	BackUp Pad Size	Orbit Diameter (mm.)	Free Speed (RPM)	Net Weight (g)	Vacuum Style	Air Consumption (L/min)	Sound Level (dBA)	Air Pressure (kg/cm ²)
KAR343NV	3x4inch (75x100mm)	3	10,000	641	Non Vacuum	340	70	6
KAR343CV	3x4inch (75x100mm)	3	10,000	691	Central Vacuum	340	70	6
KAR343SV	3x4inch (75x100mm)	3	10,000	699	Self-Generated Vacuum	340	70	6



Model No. : AP415PL-B
 Pad inch : 3"(75mm)
 No-Load Speed : 5,500 RPM
 Air Pressure : 90psi 6.3kg/cm³
 Air Consumption : 4.0cfm
 Air Inlet : 4.0cfm
 Length : 172 mm
 Weight : 0.65 kg



Model No. : AASB30015-B
 Sanding Pad Size (mm) :
 2 inch (50mm) or 3 inch (75mm)
 Orbit Diameter (mm) : 0
 Free Speed (RPM) : 15,000
 Net Weight (g) : 750
 Vacuum Style : Non Vacuum
 Remark / Type : Concentric Rotation



Model No. : AASR843
 Sanding Pad Type : Triangle Pad
 Orbit Diameter (mm) : 3
 Free Speed (RPM) : 15,000
 Net Weight (g) : 5/16"
 Gross Weight : 854
 Vacuum Style : Non Vacuum



Model No. : AASB30015-RB
 Sanding Pad Size (mm) :
 2 inch (50mm) or 3 inch (75mm)
 Orbit Diameter (mm) : 0
 Free Speed (RPM) : 15,000
 Remark / Type : Concentric Rotation



Model No. : AP450PL-A
 No load speed : 5,000 RPM
 Orbit : 0mm (Concentric Rotation)
 Air Consumption : 350L/Min
 Spindle Thread : 5/16"
 Gross Weight : 4.0cfm
 Air Inlet : 1.0kg
 Sound Level : 80dBa



Model No. : AASRH3125
 Pad inch : 1.2"(30mm)
 No-Load Speed : 15,000 RPM
 Air Pressure : 90psi 6.3kg/cm²
 Air Consumption : 4.0cfm
 Air Inlet : 1/4"
 Length : 155 mm
 Weight : 0.51 kg



Model No. : K3125
 Best Equivaelnt to 3M 3125
 Color : Red
 Free Speed : 7500rpm
 Sanding Pad Size : 30mm
 with 3 pads (red, yellow, blue)



Model No. : AP715A2
 Backup Pad Size : 5inch (125mm)
 Free Speed (RPM) : 3,000 RPM
 Noise : 75dBa
 Net Weight : 1,130 g.
 Air Pressure : 6.0kg/cm²
 Orbit : No Oribt
 Air Consumption : 3.65CFM
 Vacuum Type : Non Vacuum
 Air Inlet : 1/4"



Model No. : AAG-494-C
 Max Motor Speed : 11,000 RPM
 Free Speed (RPM) : 11,000 RPM
 Net Weight : 1.9 kg.
 Air Inlet : 1/4"pt
 Chunk size : M10*1.5
 Disc size : 4"
 Air hose : 3/8"
 Length : 242 mm.



Model No. : ASDGRH3622
 Chuck Size : 1/4" (6mm)
 1/8" (3mm)
 No-Load Speed : 22000 rpm
 Air Pressure : 90psi 6.3kg/cm²
 Air Consumption : 4.0cfm
 Air Inlet : 1/4"
 Length : 165 mm.
 Weight : 0.58 kg.



Model No. : AB110120
 Size of Brushing Wheel : 110x120mm.
 Free Speed (RPM) : 2,500 RPM
 Length : 360 mm.
 Net Weight : 2,500 g.



CALL NOW :
+66(0)9 2519 7999



infokb@kingsbrite.com



www.kingsbrite.co.th



@supragrit.machine



HEAD OFFICE & FACTORY

129/33 M.3 T Wangchula AWangnoi
 Ayutthaya 13170 Thailand

Tel. : +66(0)3 572 1458-9 Fax : +66(0)3 572 1460