



SIMATIC S7-1200 G2: SM 1223 digital I/O, 8 DI/8 RLY; inputs: 8x DI 24 V DC sink/source; outputs: 8x DO relay 2 A

Figure similar

| General information   |                                     |
|---|-------------------------------------|
| Product type designation  | SM 1223, DI 8x 24 V DC, DQ 8x relay |
| Supply voltage  |                                     |
| Rated value (DC)  | 24 V                                |
| permissible range, lower limit (DC)                             | 20.4 V                              |
| permissible range, upper limit (DC)                             | 28.8 V                              |
| Input current   |                                     |
| from backplane bus 5 V DC, max.                                 | 105 mA                              |
| Digital inputs  |                                     |
| • from load voltage L+ (without load), max.                     | 4.1 mA; per channel                 |
| Digital outputs   |                                     |
| • from load voltage L+, max.                                    | 9 mA; per relay coil                |
| Power loss  |                                     |
| Power loss, typ.  | 4.8 W                               |
| Digital inputs  |                                     |
| Number of digital inputs  | 8                                   |
| • in groups of  | 4                                   |
| Input characteristic curve in accordance with IEC 61131, type 1 | Yes                                 |
| Number of simultaneously controllable inputs                    |                                     |
| all mounting positions  |                                     |
| — up to 40 °C, max.   | 8                                   |
| horizontal installation   |                                     |
| — up to 40 °C, max.   | 8                                   |
| — up to 50 °C, max.   | 8                                   |
| vertical installation   |                                     |
| — up to 40 °C, max.   | 8                                   |
| Input voltage   |                                     |
| • Type of input voltage   | DC                                  |
| • Rated value (DC)  | 24 V                                |
| • for signal "0"  | 5 V DC or 0.5 mA                    |
| • for signal "1"  | 15 V DC at 2.5 mA                   |
| Input current   |                                     |
| • for signal "0", max. (permissible quiescent current)          | 1 mA                                |
| • for signal "1", min.  | 2.5 mA                              |
| • for signal "1", typ.  | 4 mA                                |
| Input delay (for rated value of input voltage)                  |                                     |

|  |   |
|--|---|
| for standard inputs                              |   |
| — parameterizable                                | Yes; 0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in groups of four |
| for interrupt inputs                             |   |
| — parameterizable                                | No  |
| Cable length                                     |   |
| • shielded, max.                                 | 500 m   |
| • unshielded, max.                               | 300 m   |
| <b>Digital outputs</b>                           |   |
| Number of digital outputs                        | 8   |
| • in groups of                                   | 8   |
| Short-circuit protection                         | No; to be provided externally   |
| Switching capacity of the outputs                |   |
| • with resistive load, max.                      | 2 A   |
| • on lamp load, max.                             | 30 W with DC, 200 W with AC   |
| Output voltage                                   |   |
| • Rated value (DC)                               | 5 V DC to 30 V DC   |
| • Rated value (AC)                               | 5 V AC to 250 V AC  |
| Output current                                   |   |
| • for signal "1" rated value                     | 2 A   |
| Output delay with resistive load                 |   |
| • "0" to "1", max.                               | 10 ms   |
| • "1" to "0", max.                               | 10 ms   |
| Total current of the outputs (per group)         |   |
| horizontal installation                          |   |
| — up to 50 °C, max.                              | 16 A; Current per mass  |
| Relay outputs                                    |   |
| • Number of relay outputs                        | 8   |
| • Rated supply voltage of relay coil L+ (DC)     | 24 V  |
| • Number of operating cycles, max.               | mechanically 10 million, at rated load voltage 100 000  |
| Switching capacity of contacts                   |   |
| — with inductive load, max.                      | 2 A   |
| — on lamp load, max.                             | 30 W with DC, 200 W with AC   |
| — with resistive load, max.                      | 2 A   |
| Cable length                                     |   |
| • shielded, max.                                 | 500 m   |
| • unshielded, max.                               | 150 m   |
| <b>Interrupts/diagnostics/status information</b> |   |
| Diagnostics function                             | Yes   |
| Alarms   |   |
| • Diagnostic alarm                               | Yes   |
| Diagnoses  |   |
| • Monitoring the supply voltage                  | Yes   |
| Diagnostics indication LED                       |   |
| • for status of the inputs                       | Yes   |
| • for status of the outputs                      | Yes   |
| • for maintenance                                | Yes   |
| <b>Potential separation</b>                      |   |
| Potential separation digital inputs              |   |
| • between the channels, in groups of             | 4   |
| • between the channels and backplane bus         | Yes; 707 V DC (type test)   |
| Potential separation digital outputs             |   |
| • between the channels                           | Relays  |
| • between the channels, in groups of             | 8   |
| • between the channels and backplane bus         | Yes; 4 200 V DC (type test)   |
| <b>Isolation</b>                                 |   |
| Isolation tested with                            | 1500 V AC (type test)   |
| <b>Degree and class of protection</b>            |   |
| IP degree of protection                          | IP20  |
| <b>Standards, approvals, certificates</b>        |   |
| Siemens Eco Profile (SEP)                        | Siemens EcoTech   |

|  |   |
|--|---|
| CE mark  | Yes   |
| CSA approval   | No  |
| UL approval  | Yes   |
| cULus  | Yes   |
| FM approval  | No  |
| RCM (formerly C-TICK)  | Yes   |
| KC approval  | No  |
| Marine approval  | No  |
| <b>Ecological footprint</b>                                    |   |
| • environmental product declaration                            | Yes; type 2 acc. to ISO 14021   |
| <b>Global warming potential</b>                                |   |
| — global warming potential, (total) [CO2 eq]                   | 40.3 kg   |
| — global warming potential, (during production) [CO2 eq]       | 7.8 kg  |
| — global warming potential, (during operation) [CO2 eq]        | 32.5 kg   |
| — global warming potential, (after end of life cycle) [CO2 eq] | -0.09 kg  |
| <b>Ambient conditions</b>                                      |   |
| <b>Free fall</b>   |   |
| • Fall height, max.  | 0.3 m; five times, in product package   |
| <b>Ambient temperature during operation</b>                    |   |
| • min.   | -20 °C; No condensation   |
| • max.   | 40 °C; at max. voltages and max. specifications   |
| • horizontal installation, min.                                | -20 °C; No condensation   |
| • horizontal installation, max.                                | 60 °C; at rated voltages, 50 % of max. specification and alternate IO active              |
| • vertical installation, min.                                  | -20 °C; No condensation   |
| • vertical installation, max.                                  | 50 °C; at rated voltages, 50 % of max. specification and alternate IO active              |
| • permissible temperature change                               | 5°C to 55°C, 3°C / minute   |
| <b>Ambient temperature during storage/transportation</b>       |   |
| • min.   | -40 °C  |
| • max.   | 70 °C   |
| <b>Air pressure acc. to IEC 60068-2-13</b>                     |   |
| • Operation, min.  | 540 hPa   |
| • Operation, max.  | 1 140 hPa   |
| • Storage/transport, min.                                      | 540 hPa   |
| • Storage/transport, max.                                      | 1 140 hPa   |
| <b>Altitude during operation relating to sea level</b>         |   |
| • Installation altitude, min.                                  | -1 000 m  |
| • Installation altitude, max.                                  | 5 000 m; Restrictions for installation altitudes > 2 000 m, see manual                    |
| <b>Relative humidity</b>                                       |   |
| • Operation at 25 °C without condensation, max.                | 95 %  |
| <b>Vibrations</b>  |   |
| • Vibration resistance during operation acc. to IEC 60068-2-6  | 3.5 mm from 5 - 8.4 Hz, 1g from 8.4 - 150 Hz  |
| • Operation, tested according to IEC 60068-2-6                 | Yes   |
| <b>Shock testing</b>   |   |
| • tested according to IEC 60068-2-27                           | Yes; IEC 68, Part 2-27 half-sine: strength of the shock 15 g (peak value), duration 11 ms |
| <b>Pollutant concentrations</b>                                |   |
| • SO2 at RH < 60% without condensation                         | SO2: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60% condensation-free                                |
| <b>connection method</b>                                       |   |
| required front connector                                       | No  |
| <b>Mechanics/material</b>                                      |   |
| Enclosure material (front)                                     |   |
| • Plastic  | Yes   |
| <b>Dimensions</b>  |   |
| Width  | 30 mm   |
| Height   | 125 mm  |
| Depth  | 100 mm  |
| <b>Weights</b>   |   |
| Weight, approx.  | 194 g   |

Classifications

|        | Version | Classification |
|--------|---------|----------------|
| eClass | 14      | 27-24-22-04    |
| eClass | 12      | 27-24-22-04    |
| eClass | 9.1     | 27-24-22-04    |
| eClass | 9       | 27-24-22-04    |
| eClass | 8       | 27-24-22-04    |
| eClass | 7.1     | 27-24-22-04    |
| eClass | 6       | 27-24-22-04    |
| ETIM   | 9       | EC001419       |
| ETIM   | 8       | EC001419       |
| ETIM   | 7       | EC001419       |

Approvals / Certificates

|                          |     |                                |
|--------------------------|-----|--------------------------------|
| General Product Approval | EMV | For use in hazardous locations |
|--------------------------|-----|--------------------------------|



[KC](#)



[KC](#)



|                                |             |
|--------------------------------|-------------|
| For use in hazardous locations | Environment |
|--------------------------------|-------------|



[CCC-Ex](#)



last modified:

3/23/2025