

### product type designation



### S615

SCALANCE S615 LAN router; for protection of devices/networks in automation technology and for protection of industrial communication by means of VPN and firewall; Further functions: address conversion (NAT/NAPT), connection to SINEMA RC, 5-port switch, 1x dig. input, 1x digital output.

Technical Product Detail Page

<https://l.siemens.com/1P6GK5615-0AA00-2AA2>

### transfer rate

transfer rate	10, 100 Mbit/s
---------------	----------------

### interfaces

number of electrical/optical connections / for network components or terminal equipment / maximum	5
number of electrical connections	
• for power supply	1
• for redundant voltage supply	1
type of electrical connection	
• for power supply	5-pole terminal block
design of the removable storage / C-PLUG	Yes

### signal inputs/outputs

number of electrical connections	
• for digital input signals	1
• for digital output signals	1
type of electrical connection	
• for digital input signals	2-pole terminal block
• for digital output signals	2-pole terminal block

### supply voltage, current consumption, power loss

type of voltage / 1 / of the supply voltage	DC
supply voltage / 1 / rated value	24 V
power loss [W] / 1 / rated value	4 W
supply voltage / 1 / rated value	10.8 ... 28.8 V
consumed current	
• at DC / at 24 V / typical	0.2 A
product component / 1 / fusing at power supply input	Yes
fuse protection type / 1 / at input for supply voltage	Non-replaceable melting fuse (F 2 A5 / 32 V)

### ambient conditions

ambient temperature	
• during operation	-40 ... +70 °C
• during storage	-40 ... +80 °C
• during transport	-40 ... +80 °C
relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20

### design, dimensions and weights

design	compact
--------	---------

width	35 mm
height	147 mm
depth	127 mm
net weight	0.4 kg
fastening method	
• 35 mm DIN-rail mounting	Yes
• S7-300 rail mounting	Yes
• S7-1500 rail mounting	Yes
<b>product functions / management, configuration, engineering</b>	
product function	
• CLI	Yes
• web-based management	Yes
• MIB support	Yes
protocol / is supported	
• HTTP	Yes
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
type of configuration	Web Based Management, CLI, SNMP, SCT (Configuration support for certificate generation)
<b>product functions / diagnostics</b>	
product function	
• SysLog	Yes
• packet filter log	Yes
• audit log	Yes
• system log	Yes
<b>product functions / DHCP</b>	
product function	
• DHCP client	Yes
• DHCP server - internal network	Yes
<b>product functions / routing</b>	
product function / static IP routing	Yes
<b>product functions / security</b>	
firewall version	stateful inspection
product function / with VPN connection	IPsec, OpenVPN (as client for SINEMA RC)
type of encryption algorithms / with VPN connection	AES-256, AES-192, AES-128, 3DES-168, DES-56
type of authentication procedure / with VPN connection	Preshared key (PSK), X.509v3 certificates
type of hashing algorithms / with VPN connection	MD5, SHA-1, SHA-256, SHA-384, SHA-512
number of possible connections / with VPN connection	20
product function	
• password protection	Yes
• bandwidth limitation	No
• NAT/NAPT	Yes
<b>product functions / time</b>	
protocol / is supported	
• NTP	Yes
product component / hardware real time clock	Yes
product feature / hardware real time clock w. battery backup	No
<b>standards, specifications, approvals</b>	
standard	
• for safety / from CSA and UL	UL 60950 E115352
• for emitted interference	EN 61000-6-4
• for interference immunity	EN 61000-6-2
certificate of suitability	ATEX, EMC, RoHS
• CE marking	Yes
product function / is supported / identification link	Yes; acc. to IEC 61406-1:2022
<b>standards, specifications, approvals / marine classification</b>	
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	Yes

• French marine classification society (BV)	Yes
• DNV GL	Yes
• Lloyds Register of Shipping (LRS)	Yes
• Nippon Kaiji Kyokai (NK)	Yes
• Royal Institution of Naval Architects (RINA)	Yes

#### standards, specifications, approvals / hazardous environments

standard / for hazardous zone	EN 60079-15, EN 60079-0, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X
certificate of suitability / CCC / for hazardous zone according to GB standard	Yes; GB3836.1, GB3836.8
certificate of suitability / CCC / for hazardous zone according to GB standard / as marking	Ex nA IIC T4 Gc

#### standards, specifications, approvals / Environmental Product Declaration

Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
• total	141.056 kg
• during manufacturing	15.6 kg
• during operation	125 kg
• after end of life	0.42 kg

#### accessories

product extension / optional	
• C-PLUG	No
• KEY-PLUG	Yes
accessories	optional KEY-PLUG

#### further information / internet links

internet link	
• to website: Selection guide for cables and connectors	<a href="https://support.industry.siemens.com/cs/ww/en/view/109766358">https://support.industry.siemens.com/cs/ww/en/view/109766358</a>
• to web page: selection aid TIA Selection Tool	<a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a>
• to website: Industrial communication	<a href="https://www.siemens.com/simatic-net">https://www.siemens.com/simatic-net</a>
• to web page: SiePortal	<a href="https://sieportal.siemens.com/">https://sieportal.siemens.com/</a>
• to website: Image database	<a href="https://www.automation.siemens.com/bilddb">https://www.automation.siemens.com/bilddb</a>
• to website: CAx-Download-Manager	<a href="https://www.siemens.com/cax">https://www.siemens.com/cax</a>
• to website: Industry Online Support	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>

#### security information

security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit <a href="http://www.siemens.com/cybersecurity-industry">www.siemens.com/cybersecurity-industry</a> . Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <a href="https://www.siemens.com/cert.">https://www.siemens.com/cert.</a> (V4.7)
----------------------	--

#### Approvals / Certificates

##### General Product Approval



[Declaration of Conformity](#)



[China RoHS](#)



##### General Product Approval

##### For use in hazardous locations



[China RoHS](#)



For use in hazardous locations

Maritime application

[CCC-Ex](#)



[NK / Nippon Kaiji Kyokai](#)

Maritime application

Railway

Environment

Industrial Communication



[Confirmation](#)



[PROFINET](#)

last modified:

3/10/2026