Datasheet

Instruction

DNAKE wireless doorbell operates in 2.4GHz communication. With a long-range transmission, door camera can make the video call with indoor monitor, and open the door from indoor monitor. It's easy to install and no need any other configurations.

Key Features

- Plug and Play
- Long-range transmission (400m in open area)
- One door camera supports 2 indoor monitors
- Multi-languages

Physical

• Panel: Plastic

Color: Silver

Flash: 64 MB

Button: Mechanical

• Dimension: 160 x 86 x 55 mm

• Installation: Surface Mounting

• Power: DC 12V/0.5A or 2*Battery (C size)

• IP Rating: IP65

LED: 6 pcs

Camera: 0.3 MP

• Video Resolution: 640 x 480

Viewing Angle: 105°

Audio Codec: G.711a

Video Codec: H.264

Transmit Frequency Range: 2.4GHz-2.4835GHz

Data Rate: 2.0 Mbps

DNAKE DC200



- Modulation Type: GFSK
- Transmit Distance (in open area): 400 m

Working Temperature: -10°C to +55°C

Storage Temperature: -10°C to +70°C

Working Humidity: 10% to 90% (non-condensing)

Package Features

- Package Content:
 - DNAKE DC200
 (Power adapter not included)
 - Bracket
 - Screwing Kit
 - Quick Start Guide
- Qty/CTN: 14 pcs
- N.W/PCS: 0.32 kg
- G.W/CTN: 7.49 kg
- Giftbox Size: 167 x 200 x 62 mm
- Carton Size: 375 x 440 x 200 mm