

Datasheet

DNAKE DM30

Instruction

DNAKE wireless doorbell operates in 2.4GHz communication. With a long-range transmission, door camera can make the video call with indoor monitor, and open the door from indoor monitor. It's easy to install and no need any other configurations.



Key Features

- Plug and Play
- Long-range transmission (400m in open area)
- One indoor monitor supports 2 door cameras
- Multi-languages (English, Nederlands, Polski, Deutsch, Français, Italiano, Español, Português, Русский, Türk)

Physical

- Panel: Plastic
- Color: White
- Flash: 64 MB
- Button: 9 mechanical Buttons
- Handset Dimension: 172 x 51 x 19.5 mm
- Charger Base Dimension: 123.5 x 119 x 37.5 mm
- Screen: 2.4-inch TFT LCD
- Resolution: 320 x 240
- Installation: Desktop
- Power: Rechargeable Lithium Battery (1100mAh)
- Snapshot: 100 pcs
- Audio Codec: G.711a
- Video Codec: H.264
- Multi-languages: 10
- Transmit Frequency Range: 2.4GHz-2.4835GHz
- Data Rate: 2.0 Mbps
- Modulation Type: GFSK
- Transmit Distance (in open area): 400 m
- Working Temperature: -10°C to +55°C
- Storage Temperature: -10°C to +70°C
- Working Humidity: 10% to 90% (non-condensing)

Package Features

- Package Content:
 - DNAKE DM30 (Power adapter included)
- Qty/CTN: 16 pcs
- N.W/PCS: 0.26 kg
- G.W/CTN: 10.99 kg
- Giftbox Size: 167 x 200 x 85 mm
- Carton Size: 420 x 360 x 359 mm