

Datasheet

DNAKE DM50

Instruction

DNAKE wireless doorbell operates in 2.4GHz communication. With a long-range transmission, door camera can make the video call with indoor monitor, and open the door from indoor monitor. It's easy to install and no need any other configurations.

Key Features

- Plug and Play
- Long-range transmission (400m in open area)
- One indoor monitor supports 2 door cameras
- Multi-languages (English, Nederlands, Polski, Deutsch, Français, Italiano, Español, Português, Русский, Türk)

Physical

- Panel: Plastic
- Color: Silver/Black
- Flash: 64 MB
- Button: 9 Touch Buttons
- Dimension: 214.85 x 149.85 x 21 mm
- Screen: 7-inch TFT LCD
- Resolution: 800 x 480
- Installation: Surface Mounting or Desktop
- Power: Rechargeable Lithium Battery (2500mAh)
- Snapshot: 75 pcs
- Video Recording: Yes
- TF Card : 32G
- Audio Codec: G.711a
- Video Codec: H.264
- Multi-languages: 10
- Transmit Frequency Range: 2.4GHz-2.4835GHz
- Data Rate: 2.0 Mbps



- Modulation Type: GFSK
- Transmit Distance (in open area): 400 m
- Working Temperature: -10°C to +55°C
- Storage Temperature: -10°C to +70°C
- Working Humidity: 10% to 90% (non-condensing)

Package Features

- Package Content:
 - DNAKE DM50 (Power adapter included)
 - Bracket
 - Screwing Kit
- Qty/CTN: 20 pcs
- N.W/PCS: 0.49 kg
- G.W/CTN: 16.08 kg
- Giftbox Size: 310 x 216 x 68 mm
- Carton Size: 370 x 650 x 475 mm