



TC-H363N Spec:I5W/WIFI/4mm/VJO4.0

6MP WIFI PT Camera



Wi-Fi Series

KEY FEATURES

- Plastic housing
- Up to 2304x1296 resolution
- S+265/H.265/H.264
- Smart IR, IR range 30m
- Built-in speaker
- Operating conditions -30°~60°, 0~95% RH
- Red and blue indicator lights
- IP66



Tiandy Technologies Co.,Ltd.

Email: sales@tiandy.com
Website: en.tiandy.com

Tel: +86-22-58596065
Fax: +86-22-58596048

SPECIFICATIONS

Camera	
Image Sensor	1/3"CMOS
Min. Illumination	Color:0.02Lux@(F1.6,AGC ON),B/W:0Lux with IR
Shutter Time	1s~1/100000s
Day&Night	IR-cut filter with auto switch (ICR)
WDR	DWDR
S/N	>40dB
Angle Adjustment	(P)Fixde Lens: -60°~60°, Pan & Tilt Lens: 0~345°; (T)Fixde Lens: 5°-15°, Pan & Tilt Lens: -15~90°; (R)Fixde Lens: 0°, Pan & Tilt Lens: 0°
Lens	
Lens Type	Fixed
Focal Length	4mm/4mm
Lens Mount	M12/M12
Aperture Range	F1.6/F1.6, fixed focal lens
Field of View	(H)Fixde Lens:81.3°; Pan & Tilt Lens:81.3° (V)Fixde Lens:44.4°; Pan & Tilt Lens:44.4° (D)Fixde Lens:94.4°; Pan & Tilt Lens:94.4°
DORI Distance	Fixde Lens:Detect: 59.26m; Observe:23.52m; Recognize:11.85m; Identify:5.93m Pan & Tilt Lens:Detect: 59.26m; Observe:23.52m; Recognize:11.85m; Identify:5.93m
Illuminator	
IR LEDs	4+4
IR Distance	50m
Wavelength	850nm
White LEDs	4+4
Whitelight Distance	15m
Compression Standard	
Video Compression	S+265/H.265/H.264B/H.264M/H.264H
Video Bit Rate	Fixde Lens:32k~4Mbps Pan & Tilt Lens:32k~4Mbps
Audio Compression	G.711A/G.711U
Audio Sampling Rate	8kHz/16kHz
Image	
Max. Resolution	2304x1296@15fps
Main Stream	Fixde Lens PAL:15fps(2304x1296,1920x1080,1280x720,640x480,704x576) NTSC:15fps(2304x1296,1920x1080,1280x720,640x480,704x480) Pan & Tilt Lens: PAL:15fps(2304x1296,1920x1080,1280x720,640x480,704x576) NTSC:15fps(2304x1296,1920x1080,1280x720,640x480,704x480)
Sub Stream	Fixde Lens: PAL:15fps(704x576,704x288,640x360,352x288) NTSC:15fps(704x480,704x240,640x360,352x240) Pan & Tilt Lens: PAL:15fps(704x576,704x288,640x360,352x288) NTSC:15fps(704x480,704x240,640x360,352x240)
Third Stream	N/A

Tiandy

BLC	Yes
HLC	Yes
AGC	Yes
3D DNR	Yes
White Balance	Auto/Semi-Auto/Manual/Sunshine/Nature Light/Warmlight Lamp/Daylight Lamp/Filament Lamp/Lock White Balance
ROI	N/A
Corridor mode	N/A
EIS	N/A
OSD	Overlay of additional characters in one area, 1 line, up to 48 characters or 16 Chinese characters;16*16/32*32/48*48
Picture Overlay	N/A
Privacy Mask	4 black static areas
Defog	Yes
Feature	
Alarm Trigger	Voltage Alarm;Disk Full;Disk R/W Error;IP Address Conflict
Video Analytics	N/A
Rules of behavior analyse in 1 scene	N/A
Early Warning(EW)	N/A
Auto-Tracking	Auto-Tracking
Face Mode	N/A
Face Detection	N/A
Performance	
Linkage Method	trigger sound;trigger recording;trigger capture;notify surveillance center
Network	
ANR	Yes
Protocols	HTTP;TCP/IP;UDP;ICMP;DHCP;DNS;NTP;IPv4;SSH;Unicast;FTP
System Compatibility	P2P;CGI
Remote Connection	≤2
Client	Easy7 Smart Client
Moblie Client	EasyLive Lite
Web	IE10+;Firefox52+;Edge89+;Safari11+;Chrome57+
Interface	
Communication Interface	1*RJ-45,10/100 Mbps self-adaptive Ethernet port
Audio I/O	N/A
Alarm I/O	N/A
Built-In Speaker	Yes
Reset Button	Yes
On-board storage	Support microSD/microSDHC/microSDXC card, up to 512 GB
Additional interfaces	N/A

General

Web Client Language	3languages Simple Chinese/English/Vietnamese
Operating Temperature	-30°C~60°C
Operating Humidity	Humidity 95% or less (no condensation)
Storage Temperature	-30°C~60°C
Storage Humidity	Humidity 95% or less (no condensation)
Power Supply	DC12V±25%
Protection	Surge2000V;ESD6000V;IP66
Boundary Dimensions	133(L)102(W)209(H)mm
Package Dimensions	160(L)160(W)205(H)mm
GrossWeight	0.83kg
NetWeight	0.6kg

DIMENSIONS (Unit: mm)

