



RAPTOR

HIGH-PERFORMANCE ACTIVE SPEAKERS

RAPTOR Series

High-performance active speakers with powered loudspeakers and subwoofer. Professional PA sound quality, *crystal clear sound*, and a compact lightweight cabinet characterize ideal for a variety of installed live sound floor-monitoring, portable, fixed music, speech, and even rigged applications the raptor series control via APP allows full system control.

- RAPTOR Series Crystal Clear Sound
- Lightweight, efficient Class D amplification
- 2.4inch Color LCD screen provides access to comprehensive DSP feature
- Easily connect to the "Raptor" app on iOS for full wireless control – adjust volume, EQ, DSP mode, and more...
- Birch PLY with polyurea painted finish Anti-corrosion, wear-resistant, waterproof, Good weather resistance



2.4inch Color LCD screen provides access to comprehensive DSP feature
Adjustable crossover and savable/recallable scenes for common applications

"Raptor Series" app on iOS or full wireless control



SPECIFICATIONS



Model	RT-12	RT-15	RT-18S
Speaker Type	2-way Active Speaker	2-way Active Speaker	Active Subwoofer
Transducer	12" woofer 2.5" voice coil / 1.35"compress driver	15" woofer 2.5" voice coil / 1.35"compress driver	18" Subwoofer / 4" voice coil
Frequency Response	50Hz-20kHz (-10dB)	45Hz-20kHz(-10dB)	30Hz-110Hz (-10dB)
Power output (RMS)	1000W+1000W TOTAL 2000W	1000W+1000W TOTAL 2000W	1000W TOTAL 1000W
Power output (MAX)	4000W (MAX)	4000W (MAX)	2000W (MAX)
Amplifier	CLASS D	CLASS D	CLASS D
Sensitivity	129dB 1m/1W	130dB 1m/1W	134dB 1m/1W
Maximum SPL	130dB (Peak)	131dB (Peak)	134dB (Peak)
Nominal Impedance	2Ω + 4Ω	2Ω + 4Ω	8Ω
Dispersion Angle (H x V)	90° x 70°	90° x 70°	-
LCD	2.4inch Color LCD screen	2.4inch Color LCD screen	2.4inch Color LCD screen
DSP Processor	Connect APP allows full system	Connect APP allows full system	Connect APP allows full system
Media player	TWS 5.1	TWS 5.1	
Connection			
Line Input	2 x Combo XLR or 1/4" Jack (Female)	2 x Combo XLR or 1/4" Jack (Female)	2 x Combo XLR or 1/4" Jack (Female)
Line Output	1 x XLR (Male)	1 x XLR (Male)	2 x XLR (Male)
General			
Cabinet	PP,Painted,Black	PP,Painted,Black	birch PLY with polyurea painted finish
Grille	Mesh Hexagonal	Mesh Hexagonal	1.5mm steel
Heat sink	Aluminum, stain removal, aluminum natural color	Aluminum, stain removal, aluminum natural color	Aluminum, Stain Release
Pole	35mm stand pole	35mm stand pole	35mm stand pole
Operating voltage	220-240V ~ 50/60Hz 800W MAX 100-120V ~ 50/60Hz 800W MAX	220-240V ~ 50/60Hz 800W MAX 100-120V ~ 50/60Hz 800W MAX	220-240V ~ 50/60Hz 800W MAX 100-120V ~ 50/60Hz 800W MAX
Dimensions (H x W x D)	628 x 360 x 353 mm	713 x 430 x 403 mm	715 x 600 x 650 mm
Net Weight	16.9 Kgs	20.7 Kgs	55 Kgs

Suspension/mounting:
35mm pole socket, Three M10 suspension points

Certifications : CE



INSTALLATION EXAMPLE



Raptor Series Ideal for live sound concert, event, shopping mall, meeting room – training, fitness, restaurant, hotel banquet room.

SOUND VISION CO., LTD.

99/189 Moo.4, Sala Klang, Bang Krui, Nonthaburi 11130 Thailand

Email : info@soundvision.co.th Support : 02-433-9988 LINE Official : @soundvision www.soundvisionpro.com

