

<b>Technical</b>	
Input Video Port	2 x HDMI In; 1 x LAN, 10/100/1000Mbps Ethernet; 1 x WLAN
Input Video Signal	<ul style="list-style-type: none"> <li>HDMI: HDMI 1.4, HDCP 1.4</li> <li>LAN/WLAN: H.264</li> </ul>
Input Resolutions	<p><b>HDMI:</b> 640x480<sup>8</sup>, 800x600<sup>8</sup>, 1024x768<sup>8</sup>, 1280x768<sup>8</sup>, 1280x800<sup>8</sup>, 1280x1024<sup>8</sup>, 1360x768<sup>8</sup>, 1366x768<sup>8</sup>, 1440x900<sup>8</sup>, 1400x1050<sup>8</sup>, 1600x1200<sup>8</sup>, 1680x1050<sup>8</sup>, 1920x1200<sup>8</sup>, 720x480<sup>8</sup> (480p), 720x576<sup>6</sup> (576p), 1280x720<sup>5</sup> (720p30), 1280x720<sup>6</sup> (720p50), 1280x720<sup>8</sup> (720p60), 1920x1080<sup>2</sup> (1080p24), 1920x1080<sup>3</sup> (1080p25), 1920x1080<sup>5</sup> (1080p30), 1920x1080<sup>6</sup> (1080p50), 1920x1080<sup>8</sup> (1080p60), 3840x2160<sup>2</sup>(2160p24), 3840x2160<sup>3</sup>(2160p25), 3840x2160<sup>5</sup>(2160p30)</p> <p><b>LAN/WLAN:</b> H.264 encoding stream, up to 3840x2160<sup>5</sup> (2160p30) Note: The input resolution support for LAN or WLAN may vary according to the specific BYOD protocols and devices.</p> <p>1 = at 23.98 Hz, 2 = at 24 Hz, 3 = at 25 Hz, 4 = at 29.97 Hz, 5 = at 30 Hz, 6 = at 50 Hz, 7 = at 59.94 Hz, 8 = 60 Hz</p>
Output Video Port	2 x HDMI
Output Video Signal	HDMI 1.4, HDCP 1.4
Output Resolutions	<p><b>HDMI OUT1:</b> 720x480<sup>8</sup> (480p60), 720x576<sup>6</sup> (576p60), 640x480<sup>8</sup>, 800x600<sup>8</sup>, 1024x768<sup>8</sup>, 1280x720<sup>6</sup>(720p50), 1280x720<sup>8</sup> (720p60), 1280x800<sup>8</sup>, 1280x1024<sup>8</sup>, 1366x768<sup>8</sup>, 1440x900<sup>8</sup>, 1600x1200<sup>8</sup>, 1680x1050<sup>8</sup>, 1920x1200<sup>8</sup>, 1920x1080<sup>2</sup> (1080p24), 1920x1080<sup>3</sup> (1080p25), 1920x1080<sup>5</sup> (1080p30), 1920x1080<sup>6</sup> (1080p50), 1920x1080<sup>8</sup> (1080p60), 3840x2160<sup>3</sup> (2160p25), 3840x2160<sup>5</sup> (2160p30)</p> <p><b>HDMI OUT2:</b> 720x480<sup>8</sup> (480p60), 720x576<sup>6</sup> (576p60), 640x480<sup>8</sup>, 800x600<sup>8</sup>, 1024x768<sup>8</sup>, 1280x720<sup>6</sup>(720p50), 1280x720<sup>8</sup> (720p60), 1280x800<sup>8</sup>, 1280x1024<sup>8</sup>, 1366x768<sup>8</sup>, 1440x900<sup>8</sup>, 1600x1200<sup>8</sup>, 1680x1050<sup>8</sup>, 1920x1200<sup>8</sup>,</p>

Technical	
	1920x1080 <sup>2</sup> (1080p24), 1920x1080 <sup>3</sup> (1080p25), 1920x1080 <sup>5</sup> (1080p30), 1920x1080 <sup>6</sup> (1080p50), 1920x1080 <sup>8</sup> (1080p60)
	1 = at 23.98 Hz, 2 = at 24 Hz, 3 = at 25 Hz, 4 = at 29.97 Hz, 5 = at 30 Hz, 6 = at 50 Hz, 7 = at 59.94 Hz, 8 = 60 Hz

Audio	
Input Audio Port	2 x HDMI; 1 x LAN; 1 x WLAN
Input Audio Signal	RAW PCM 2.0, 16 bit, 32/44.1/48KHz sps
Output Audio Port	1 x HDMI OUT (HDMI OUT 1), 1 x Analog Audio OUT
Output Audio Signal	RAW PCM 2.0, 16 bit, 48KHz sps

Wi-Fi	
Standard	IEEE 802.11 a/b/g/n/ac
Frequency	Dual bands, 2.4~2.4835GHz, 5.2GHz and 5.8GHz
Security	WEP, TKIP, AES, WPA, WPA2

Control	
Control Connector	1 x RJ45, 10/100/1000Mbps Ethernet
Control Method	LAN (Web UI)

General	
Operating Temperature	0°C to + 45°C (32 to + 113 °F)
Storage Temperature	-20 to +70°C (-4 to + 158 °F)
Humidity	10% to 90%, non-condensing
ESD Protection	Human-body Model: ±8kV (Air-gap discharge)/±4kV (Contact discharge)
Power Supply	12V 3A DC
Power Consumption	26.5W (Max)
Device Dimensions (W x H x D)	242.6mm x 29.1mm x 142mm / 9.55" x 1.14" x 5.59"
Product Weight	0.80kg/1.76lbs