


Stainless Steel Gate Valve, BSPT

Model : SGA-S04, SGA-S16



Specification Standards :

- Threaded end according to BSPT standard

Features :

- Investment casting body
- Hand - wheel operator
- Test and inspection EN1266, MSS SP-110
- Available upon special request

Materials :

No.	Parts	Material
1	Body	CF8M / CF8
2	Disc	CF8M / CF8
3	Stem	SS316 / 304
4	Body gasket	PTFE
5	Cap	CF8M / CF8
6	Stem seal	PTFE
7	Stop nut	CF8M / CF8
8	Wheel handle	Aluminium
9	Stem nut	SS201
10	Washer	SS201
11	Stop gasket	SS304
12	Gland	SS304

Test Requirements

Working Pressure	150 PSI (10 Bar)
Maximum Pressure	200 PSI (14 Bar)
Shell Test Pressure	300 PSI (21 Bar)
Applicable Temperature	≤ 150 °C

Application :

- For general and industrial services
- Applicable medium : water, oil, gas

Dimensions

mm

Size	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"
DN	15	20	25	32	40	50	65	80
H	93	105	115	130	145	170	200	218
L	55	60.5	64	70.5	78	88	106.5	116.5
ΦE	70	70	80	80	100	100	125	125