

Stainless Steel Globe Valve, BSPT

Model : SGL-S04, SGL-S16



Specification Standards :


- Threaded end according to BSPT standard

Features :

- Investment casting body
- Hand - wheel operator
- Test and inspection EN1266, MSS SP-110
- Available upon special request

Test Requirements

Working Pressure	150 PSI (10 Bar)
Maximum Pressure	200 PSI (14 Bar)
Shell Test Pressure	300 PSI (21 Bar)
Applicable Temperature	≤ 150 °C



Materials :

No.	Parts	Material
1	Body	CF8M / CF8
2	Disc	CF8M / CF8
3	Cap	CF8M / CF8
4	Body gasket	PTFE
5	O - ring packing	PTFE
6	Cap nut	CF8M
7	Gland	SS304
8	Stem	SS316/304
9	Washer	SS201
10	Stem nut	SS201
11	Wheel handle	Aluminium

Application :

- For general and industrial services
- Applicable medium : water, oil, gas

Dimensions

	1/4"	3/8"	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"
DN	6	10	15	90	97	115	125	139	180	198
H	80	80	82	90	97	115	125	139	180	198
L	60	60	62	72	81	102	116	136.5	164	189
E	70	70	70	70	70	90	90	90	115	115

mm