





APPLICATIONS

The Hose Kit provides an easy and efficient solution for diverse settings like flooded basements, shops, residential areas, construction sites, and more.

The Hose Kit is compatible with 2" pumps. Its angled LOT male thread/LOH outlet discharge prevent the hose from overbending for a smooth drainge.

The PRO KIT comes with simple, secure and quick connect Storz fittings. Ease of convenience for mobility and storage.



SH2A/B/C-10S PRO PF




SH2B-10 H

Extendable


PRODUCT NOMENCLATURE

| SH | 2 | В - | - 10 | S | PRO | PF |
|--------|-----------|------|-------------|----------|-------------|--------|
| Series | Discharge | Туре | Hose | Coupling | Accessories | Thread |
| | inch | | length(m) | Style | Kit | |

The hose is bent without the angled outlet.



Smooth draingae with the angled outlet.



* The operating water level for the side discharge pump should be above the upper cover.

COMPATIBLE MODEL



GD 0.5~1HP PCD 74mm



PCD 84mm



All 0.5~3HP PCD 96mm

SPECS.

Compatible with other pumps with similar PCD.

| Model | Discharge | PCD | Thickness | Thread | Working Pressure | | Hose length | Compatible Model | | |
|-----------------|-----------|-----|-----------|--------|--------------------|-----|-------------|------------------|--|--|
| Model | inch(mm) | mm | mm | | kg/cm ² | psi | m | | | |
| SH2A-10S PRO PF | 2"(50) | 74 | 1.0 | PF/NPT | 3 | 43 | 10 | GD 0.5~1HP | | |
| SH2B-10S PRO PF | 2"(50) | 84 | 1.0 | PF/NPT | 3 | 43 | 10 | All 0.5HP | | |
| SH2C-10S PRO PF | 2"(50) | 96 | 1.0 | PF/NPT | 3 | 43 | 10 | 2" All 0.5~3HP | | |
| SH2B-10 H | 2"(50) | 74 | 1.0 | PF/NPT | 3 | 43 | 10 | GD 0.5~1HP | | |

DSHEN0-2405 % 500 MOQ for NPT Thread