

## TAPS110

### Taps and splitters



1-output "top-down" horizontal tap with 10dB attenuation and F connector for TV and Satellite band (5-2400MHz).

### Technical Chars

- The elegant and compact design allows installation in any junction box.
- The **die-cast zinc** products in this series ensure high performance, with very low insertion losses even at SAT frequencies and high isolation between outputs.
- Prepared for earth connection and wall mounting.
- **DC is allowed to pass between the through output and input.**

TAPS110		
Code		287310
Taps		1
Insertion loss		
RC 5-40MHz	dB	2
TV 47-862MHz	dB	2
SAT 950-1750MHz	dB	2.5
SAT 1750-2150MHz	dB	3
SAT 2150-2400MHz	dB	3.5
Tap loss		
RC 5-40MHz	dB	10
TV 47-862MHz	dB	10
SAT 950-1750MHz	dB	10
SAT 1750-2150MHz	dB	10
SAT 2150-2400MHz	dB	10
Outputs Isolation		
RC 5-40MHz	dB	28
TV 47-862MHz	dB	24
SAT 950-1750MHz	dB	23
SAT 1750-2150MHz	dB	22
SAT 2150-2400MHz	dB	22

Specifications		
Tap loss	dB	10
Dimensions and packaging		
Pieces		1
EAN code		8016978094929
Packaging dimensions	mm	55 x 64 x 27
Product dimensions	mm	55 x 64 x 27
Packaging weight	kg	0.082