

TAPS212

Taps and splitters



2-output "top-down" horizontal tap with 12dB attenuation and F connector for TV and Satellite band (5-2400MHz).

Technical Chars

- The elegant and compact design allows installation in any junction box.
- The **die-cast zinc** products in this series ensure high performance, with very low insertion losses even at SAT frequencies and high isolation between outputs.
- Prepared for earth connection and wall mounting.
- **DC is allowed to pass between the through output and input.**

TAPS212		
Code		287313
Taps		2
Insertion loss		
RC 5-40MHz	dB	3
TV 47-862MHz	dB	3
SAT 950-1750MHz	dB	3.5
SAT 1750-2150MHz	dB	4
SAT 2150-2400MHz	dB	5
Tap loss		
RC 5-40MHz	dB	12
TV 47-862MHz	dB	12
SAT 950-1750MHz	dB	12
SAT 1750-2150MHz	dB	12
SAT 2150-2400MHz	dB	12
Outputs Isolation		
RC 5-40MHz	dB	25
TV 47-862MHz	dB	25
SAT 950-1750MHz	dB	25
SAT 1750-2150MHz	dB	22
SAT 2150-2400MHz	dB	21

Specifications		
Tap loss	dB	12
Dimensions and packaging		
Pieces		1
EAN code		8016978094950
Packaging dimensions	mm	55 x 64 x 27
Product dimensions	mm	55 x 64 x 27
Packaging weight	kg	0.085