




MAKE EVERY EXPERIMENT
MORE CONVENIENT

2024/07

Joan Lab Equipment (Zhejiang) Co.,Ltd.



JOANLAB[®]

HISTORY

2010

Set up Ningbo Joan Lab Equipment Co., Ltd.(Export lab items)

2013

Set up own brand "JOANLAB"

2015

Introduced German production technology, set up production factory in Huzhou

2019

Set up a R&D center in Hangzhou, developed multiple series of new products

2023

142 million in sales

2024

Expand production scale and construction new factory of 35,000 m²

CONTENTS



01 SHAKER&MIXER

Mini Vortex Mixer	04	Vortex Mixer With Multifunction	05
Vial Vortex Mixer	07	Roller Mixer	08
Roller Mixer	09	Roller Mixer	10
Long axis Rotating Mixer Shaker	11	Rotary Rotating Mixer Shaker	12
Microplate oscillator	13	Microplate oscillator	14
Multi Tube Vortex Mixer	15	Multi Tube Vortex Mixer	16
Orbital Shaker	17	Plate circumference/Rocker shaker	18
3D Oscillator Shaker	19		



02 LAB CENTRIFUGE

Mini Centrifuge	21	Mini Centrifuge	22
Digital Mini Centrifuge	23	High Speed Centrifuge	24
High Speed Centrifuge	25	Low Speed Centrifuge	26
CGF Centrifuge	27	Low Speed Centrifuge	28



03 MICROPLATE CENTRIFUGE

Microplate Centrifuge	30
-----------------------	----



04 LAB STIRRER

Mini Magnetic Stirrer	32	Digital Display Hotplate Stirrer	33
Digital Display Hotplate Stirrer	34	Digital Display Hotplate Stirrer	35
Large Capacity Magnetic Stirrer	36	Large Capacity Magnetic Stirrer	37
Multiple Magnetic Stirrer	38	Multiple Magnetic Stirrer with Heating	39
Overhead Stirrer	40	Overhead Stirrer	41
Overhead Stirrer	42		



05 DRY BATH

Mini Dry Bath	43	Dry Bath	45
PRP Gel Maker	47	Dry Bath - Two Modules	48
Dry Bath Shaking Incubator	50		



06 WATER BATH

Water Bath With Magnetic Stirrer	53	Water Bath	54
----------------------------------	----	------------	----



07 HEATING MANTLE

Heating Mantle	56
----------------	----



08 INFRARED STERILIZER

Infrared Sterilizer	58
---------------------	----



09 MICROPIPETTE

Electric Pipette	60	Liquid Vacuum Aspiration System	61
Bottle Top Dispenser	62	M Series Micropipette	63
P Series Micropipette	64	Multichannel Pipette	65



10 VACUUM PUMP

Oilless Diaphragm Vacuum Pump	67	Adjustable Speed Oil-free Diaphragm Vacuum Pump	68
Oilless Diaphragm Vacuum Pump - 30L	69	6L Mini Vacuum Pump	70
Vacuum Filtration Apparatus	71		





11 BALANCE SCALE

Electronic Balance	73	0.001g Balance	74
Analytical Balance - FA	75	Dual Range Analytical Balance - CEB	76
Moisture Analyzer	77		



Mini Vortex Mixer



Stepless speed regulation
Wide speed range



High quality and colorful
silicone



Press to start / Compact body



Brushless motor / Durable

TECHNICAL DATA

Model	VM-300	VM-300S	Shell Protection Level	IP42	
Control Mode	Constant speed	Knob	Power	12W	
Motor	Brushless motor		Voltage	100-240V, 50/60Hz	
Amplitude	4.5mm (Circular oscillation)		Product Size	93*93*72mm	100*93*72mm
Maximum Sample Processing Capacity	50ml		Allowable Ambient Temperature	5-40°C, 80%RH	
Speed Range	3000rpm	0-3000rpm	Gross / Net weight	0.55/0.36kg	0.56/0.37kg

Vortex Mixer With Multifunction



- Ultra-low body, stable operation
- Various fixtures, large handling capacity
- Brushless motor with strong power
- Touch / Run, easy to switch

TECHNICAL DATA

Model	VM-500S	VM-500Pro	Speed Range	Touch: 0-3000rpm	Touch: 0-3000rpm
Operating Mode	Touch / Run			Run: 200-3000rpm	Run: 100-3000rpm
Control Mode	Knob	Digital display & Button	Timing / Time	No	1min - 8h
Display	No	LCD	Shell Protection Level	IP21	
Motor	Brushless motor		Voltage	20W	
Amplitude	4.5mm (Circular oscillation)		Power	DC12V	

Multifunctional Mixer Adapted Module

Model	Picture	Image	Module application scope
VM501			Centrifuge tube / Test tube
VM502			Flask / Multi tube
VM503			Φ12mm Blood collection tube * 21
VM504			5ml/ 15ml Centrifuge tube * 12
VM505			50ml Centrifuge tube * 4 5ml/ 15ml Centrifuge tube * 5
VM506			0.2ml Centrifuge tube * 96 96 well plate
VM507			0.5ml Centrifuge tube * 20 1.5 / 2.0ml Centrifuge tube * 30
VM508			Cell culture plate

Vial Vortex Mixer



Various modules available



Brushless motor with strong power

TECHNICAL DATA

Model	VM-550X
Motor Type	Brushless motor
Speed	100 - 2000rpm
RPM Increment	100rpm
Module capacity	VM551 Vial $\phi 22 \times 60$ or $\phi 26 \times 65$ VM552 Vial $\phi 16 \times 3$ $\phi 18 \times 2$ VM553 Vial $\phi 22 \times 2$ $\phi 28 \times 2$
Module MaterialTiming	EVA modules
Allowed Ambient Humidity Temp.	1min - 8h
Voltage	5 ~ 40 C 80%RH
Power adapter	DC12V
Power (W)	20W
Dimension (mm)	155*150*90

Roller Mixer



Timing function



Anti - lock design, more convenient




Adjustable speed



Brushless motor with strong power

TECHNICAL DATA

Model	RM-6	RM-6Pro	RM-8Pro
Motor Type	Brush motor	Brushless motor	Brushless motor
Display	/	LCD	LCD
Speed	20 - 80rpm		
Number Of Rollers	6	6	8
Roller Length (mm)	280		
Roller Center Distance (mm)	34		
SPECS	φ 6 - 34mm		
Timing	/	1min - 23h59min	1min - 23h59min
Allowed Ambient Humidity Temp.	5 ~ 40 C 80%RH		
Voltage	AC 100 - 220V, 50/60Hz		
Power	25W		
Dimension (mm)	440*255*105	440*255*105	430*320*100



Roller Mixer



Timing function



Anti - lock design, more convenient



Adjustable speed



Brushless motor with strong power

TECHNICAL DATA

Model	RM-6H	RM-8H
Motor Type	Brushless motor	
Display	LCD	
Type	Horizontal rolling	
Speed	20 - 80rpm	
Number Of Rollers	6	8
Roller Length (mm)	280	
Roller Center Distance (mm)	34	
SPECS	φ 6 - 34mm	
Timing	1min - 23h59min	
Allowed Ambient Humidity Temp.	5 ~ 40 C 80%RH	
Voltage	AC 100 - 220V, 50/60Hz	
Power	25W	
Dimension (mm)	440*255*105	430*320*100

Roller Mixer



Timing function



Anti - lock design, more convenient



Adjustable speed



Brushless motor with strong power

TECHNICAL DATA

Model	RM-4max
Motor Type	Brushless motor
Type	Horizontal rolling
Speed	20 - 80rpm
Number Of Rollers	4
Roller Length (mm)	280
Roller Center Distance (mm)	68
SPECS	φ 45 - 100mm
Timing	1min - 23h59min
Allowed Ambient Humidity Temp.	5 ~ 40 C 80%RH
Voltage	AC 100 - 220V, 50/60Hz
Power	25W
Dimension (mm)	440*255*105

Long Axis Rotating Mixer Shaker



Timing function




Six different modules

TECHNICAL DATA

Model	RML - 80	RML - 80Pro
Motor	Brush motor	Brushless motor
Control Mode	Knob	Digital display & Button
Type	Non-stop run	Non-stop run / Timing
Speed	20 - 80rpm	
Timing	/ 1min - 23h59min	
Power	25W	
Dimension (mm)	425*100*125	

MODULES

	Composite module	Centrifuge tube : 50ml*4+15ml*10+2ml*8 Blood collection tube : 10ml*10+2/5ml*8
	RML-801	Centrifuge tube : 50ml*12
	RML-802	Centrifuge tube : 15ml*23 Blood collection tube : 10ml*23
	RML-803	Centrifuge tube : 1.5/2.0ml*28 Blood collection tube : 2.0/5.0ml*28
	RML-804	Centrifuge tube : 15ml*16 Blood collection tube : 10ml*16
	RML-805	Centrifuge tube : 50ml*12

Rotary Rotating Mixer Shaker



Timing function



Large handling capacity



Adjustable angle



Brushless motor with strong power

TECHNICAL DATA

Model	RMO - 80	RMO - 80Pro
Motor	Brush motor	Brushless motor
Control Mode	Knob	Digital display & Button
Type	Non-stop run	Non-stop run / Timing
Speed	20 - 80rpm	
Angle Range	40° - 80°	
SPECS	Centrifuge tube : 50ml*8 or 15ml*16 or 1.5ml/2ml*24 Blood collection tube : 10ml*16 or 2ml/5ml*24	
Timing	/	1min - 23h59min
Allowed Ambient Humidity Temp.	5 ~ 40 C 80%RH	
Voltage	AC 100 - 220V, 50/60Hz	
Power	20W	
Dimension (mm)	230*180*265mm	

Microplate oscillator



Timing function




Brushless motor with strong power

TECHNICAL DATA

Model	VM - 500 - 1P	VM - 500 - 2P
Motor Type	Brushless motor	
Horizontal Gyration Amplitude	4mm	
Speed	100-1200rpm	
RPM Increment	100rpm	
Timing	1min - 8h	
Handling range	ELISA Plate / Tissue Culture Plate / 96-well plate	
Allowed Ambient Humidity Temp.	5 ~ 40 C 80%RH	
Voltage	DC12V	
Power	20W	
Dimension (mm)	155*150*90	180*150*90

Microplate oscillator



Timing function




Brushless motor with strong power

TECHNICAL DATA

Model	VM - 600	VM - 600D
Motor Type	Brushless motor	
Horizontal Gyration Amplitude	3mm	
Speed	500 - 1200rpm	
RPM Increment	10rpm	
Timing	1min - 8h	
Handling Range	ELISA Plate/Tissue Culture Plate *4	ELISA Plate/Deep Tissue Culture Plate *4
Allowed Ambient Humidity Temp.	5 ~ 40℃ 80%RH	
Voltage	AC 110 - 220V	
Power	20W	
Dimension (mm)	355*260*95	355*260*105

Multi Tube Vortex Mixer



Timing function




Large handling capacity

TECHNICAL DATA

Model	VM - 600Max
Motor Type	Brushless motor
Horizontal Gyration Amplitude	4mm
Speed	1500 - 3000rpm
RPM Increment	10rpm
Timing	1min - 8h
Handling Range	Model1(VM601) Centrifuge tube : 50ml*25+15ml*16 Model2(VM602) Centrifuge tube : 15ml*49 / Blood tube :10ml*49 Model3(VM603) Blood tube : 2/5ml*49 Model4(VM604) Centrifuge tube : 1.5/2ml*81
Allowed Ambient Humidity Temp.	5 ~ 40 C 80%RH
Voltage	AC 100 - 220V, 50/60Hz
Power	30W
Dimension (mm)	355*260*145

Multi Tube Vortex Mixer



Smooth start, stable operation



Large handling capacity



Brushless motor with strong power



Touch / Run, easy to switch


TECHNICAL DATA

Model	VM800Pro
Operating Mode	Run
Speed Range	500 ~ 3000rpm
Amplitude	4mm Horizontal swing
Timing Range	1min ~ 24h
Maximum Load	4.5kg
Power	100W

ADAPTATION MODULE DETAILS

Model	VM801	VM802	VM803
Specification	(Centrifuge tube) 50ml*15	(Centrifuge tube) 15ml*50 (Blood tube) 10ml*50	(Centrifuge tube) (1.5/2ml)*72 (Blood tube) 2/5ml*72
Size(mm)	260*180*50	260*180*50	260*180*50
Aperture	27-31	14-17	9-11

Orbital Shaker



Adjustable speed



Timing function

TECHNICAL DATA

Model	OS-20Pro	OS-40Max	LS-40Max
Speed	40-200rpm		
Plate Size	250*250mm	320*320mm	320*320mm
Orbit Diameter	20mm	20mm	Linear and reciprocating 20mm
Timing Range	1min-23h59min		
Maximum Load	2kg	5kg	5kg
Voltage	AC100-240V 50/60Hz		
Dimensions	260*355*135mm	330*435*140mm	340*435*140mm

Fix Plate Shaker/Rocking Shaker



Brushless motor



Suitable for a variety of containers

TECHNICAL DATA

Model	OS - 20F	RS - 20Pro
Type	Circular orbital	Work Plate Rocking
Plate Size	250*250	250*250
Tit Angle	/	7°
Orbit Diameter	20	/
Speed	40-200rpm	10 - 80rpm
Timing	1min - 23h59min	1min - 24h
Max Load	2kg	2kg
Allowed Ambient Humidity Temp.	5 ~ 40 C 80%RH	5 ~ 40 C 80%RH
Voltage	AC 100 - 240V	AC 100 - 240V
Power	30W	25W
Dimension (mm)	355*260*100	355*260*135

Plate circumference/ Linear shaker



Brushless motor



Suitable for a variety of containers

TECHNICAL DATA

Model	OS - 40F	LS - 40F
Type	Circular orbital	Linear & reciprocating
Plate Size	320*320	320*320
Orbit Diameter	20	20
Speed	40-200rpm	40 - 200rpm
Timing	1min - 23h59min	1min - 23h59min
Max Load	3kg	3kg
Allowed Ambient Humidity Temp.	5 ~ 40 C 80%RH	5 ~ 40 C 80%RH
Voltage	AC 100 - 240V	AC 100 - 240V
Power	45W	45W
Dimension (mm)	435*330*140	435*330*140

3D Oscillator Shaker



Timing function



Suitable for a variety of containers



Adjustable speed



3D mixing

TECHNICAL DATA

Model	SK - 3D
Type	3D Oscillating
Display	LCD
Tilt Angle	10°
Max Load	0.8kg
Speed	10 - 80rpm
Timing	1min - 8h
Allowed Ambient Humidity Temp.	5 ~ 40 C 80%RH
Voltage	DC 12V
Power	10W
Dimension (mm)	184*184*130

CENTRIFUGE



Mini Centrifuge



Stop running after opening lid



Low noise

TECHNICAL DATA

Model	MC-4K	MC-7K	MC-10K	MC-12K
Max Speed	4000rpm	7000rpm	10000rpm	12000rpm
Max RCF	984xg	3013xg	6149xg	8855xg
Rotor Capacity	0.2ml*16 + 1.5 / 2.0ml*8		1.5 / 2.0ml*8	
Power	15W	20W	30W	40W
Dimensions (mm)	160*135*110	160*135*110	160*135*110	160*135*110
Weight (kg)	0.8	0.8	0.8	0.8

Mini Centrifuge



Multi-rotor, more working capacity



Low centre of gravity for stable operation



High frequency and wide voltage



Low noise

TECHNICAL DATA

Model	MC-7S	MC-4/7S
Control Mode	Constant speed	
Max Relative Centrifugal Force	3286xg	1080/3286xg
Max Rotation Speed	7000rpm±5%	4000/7000rpm±5%
Rotor Capacity	0.2/0.5/1.5/2ml*12 + 0.2ml*8*4 Centrifuge tube 0.5/1.0ml*12 Micro blood tube	
Power	25W	25W
Voltage	DC24V	

Digital Mini Centrifuge



LCD display



Multi-rotor,big working capacity



Run smoothly,precise separation



Speed adjustable and timing

TECHNICAL DATA

Model	MC-5Pro	MC-7Pro
Control Mode	Digital display & Button	
Display	LCD display	
Max Relative Centrifugal Force	1680xg	3286xg
Max Rotation Speed	5000rpm±5%	7000rpm±5%
Rotor Capacity	0.2/0.5/1.5/2ml*12 + 0.2ml*8*4 Centrifuge tube 0.5/1.0ml*12 Micro blood tube	
Timing	10sec-99min	
Power	25W	

High Speed Centrifuge



Memory program



Stable rotation



Temperature protection function



Multi-rotor, big working capacity

TECHNICAL DATA

Model	MC-10Pro	MC-12Pro
Control Mode	Digital display & Button	
Max Relative Centrifugal Force	6708xg	9660xg
Speed Range	1000-10000rpm±5%	1000-12000rpm±5%
Rotor Capacity	0.2/0.5/1.5/2ml*12 + 0.2ml*8*4 Centrifuge tube 0.5/1.0ml*12 Micro blood tube Hematocrit rotor: 40mm*12 Capillary tube	
Max Speed Acceleration / Reduction	≤12 s/ ≤15s	
Noise Under Max Rotation Speed	≤47db (A)	
Input Power	48W	
Shell Protection Level	AC100-240V / DC24V	
Allow Surrounding Temperature	5 - 40 C / 80%RH	

High Speed Centrifuge



Memory program



Stable rotation



Temperature protection function



Enclosed high-speed type rotor

TECHNICAL DATA

Model	MC-13Pro	MC-15Pro
Control Mode	Digital display & Button	
Max Relative Centrifugal Force	11337xg	14104xg
Speed Range	1000-13000rpm±5%	1000-14500rpm±5%
Rotor Capacity	0.2/0.5/1.5/2ml*12 Centrifuge tube 0.5/1.0ml*12 Micro blood tube	
Max Speed Acceleration / Reduction	≤12 s/ ≤15s	
Noise Under Max Rotation Speed	≤47db (A)	
Input Power	50W	55W
Shell Protection Level	AC100-240V / DC24V	
Allow Surrounding Temperature	5 - 40℃ / 80%RH	

Low Speed Centrifuge



Memory program



Multi rotors optional



Temperature protection &
overshock protection



Double electronic lock

TECHNICAL DATA

Model	LC500-8	LC500-12	LC500-6	LC500-18	LC500-24
Rotor Capacity	15ml*8 Centrifuge tube 2/5/10ml*8 Blood tube	15ml*12 Centrifuge tube 2/5/10ml*12 Blood tube	15/50ml*6 Centrifuge tube 2/5/10ml*6 Blood tube	2/5/10ml*18 Blood tube	2/5/10ml*24 Blood tube
Speed	500 - 4000rpm				
Max RCF	1967xg	2075xg	2146xg	2182xg	2164xg
Semidiameter Of Rotor	11cm	11.6cm	12cm	12.2cm	12.1cm
Timing Range	30s - 59min50s				
Protection Function	Lid opening protection, overtemperature protection, overshock protection				
Power	60W	60W	80W	80W	80W
Power Supply	AC 110V - 220V, 50/60Hz				

CGF Centrifuge



Four programs built in



Multi rotors optional

TECHNICAL DATA

Model	LC500-8P	LC500-12P
Rotor Capacity	15ml*8 Centrifuge tube 5/10ml*8 Blood tube	15ml*12 Centrifuge tube 5/10ml*12 Blood tube
Speed	500 - 4000rpm	
Max RCF	1967xg	2075xg
Timing Range	30s - 59min50s	
Control mode	Digital display + button	
Power	60W	60W
Power Supply	AC 110V - 220V, 50/60Hz	

Built-in 4 programs

CGF: Highly concentrated growth factor
fibrin centrifugal
PRP: Platelet-rich plasma centrifugal
APRF: Advanced plasma rich fibrin
IPRF: Injectable plasma rich fibrin
(Don't use the yellow 2ml adapters for CGF)

Low Speed Centrifuge



LCD display



Electronic lock



Emergency switches



Memory program

TECHNICAL DATA

Model	LC400	LC400Pro
Speed Range	500-4000rpm	500-5000rpm
Max Relative Centrifuge Force	1717xg	2683xg
Rotor Capacity	15ml*4 Centrifuge tube 2/5/10ml*8 Blood tube	
Increment	100rpm	
Timing Range	30s ~ 59min50s	
Noise	≤ 60dB(A)	
Voltage	AC100-240V	
Power	35W	45W
Dimensions (mm)	265*260*190	

MICROPLATE CENTRIFUGE



Microplate Centrifuge



LCD display



Rotor for microplate, big working capacity



Brushless motor with strong power



Speed adjustable and timing

TECHNICAL DATA

Model	LC500 - MP	
Max Capacity	96-well PCR microplate * 4	
Speed Range	500 - 2000 rpm	
Max RCF	500xg	
Semidiameter Of Rotor	10.2cm	
Protection Function	Lid opening protection, overtemperature protection, overshock protection	
Timing	30s - 59min50s	
Power	50W	
Power Supply	AC 110V - 220V 50/60Hz	

STIRRER



Mini Magnetic Stirrer



Strong magnetic field



Large mixing ability



Durable brushless motor



LCD display

TECHNICAL DATA

Model	MS3	MS5	MS5S
LCD Display	No	No	Yes
Control	Knob	Knob	Knob
Motor Type	Brushless motor		
Working Plate Size (mm)	125	135	135
Speed Range	350-1800rpm	350-1800rpm	200-2000pm
Max Stirring Volume	1L(H ₂ O)	2L(H ₂ O)	2L(H ₂ O)
Stir Bar Size (mm)	30	30	30
Power	5W	10W	10W
Shell Protection Level	IP21	IP42	IP42
Power adapter	DC12V 1A		

Heating Magnetic Stirrer



Strong magnetic field



Stainless steel ceramic
coated countertops

TECHNICAL DATA

Model	HS-5
Control Mode	Brushless motor
Max Stirring Volume	2L(H ₂ O)
RPM	200-1500rpm
Timing Range	/
Control Mode	Knob
Working Plate (mm)	Φ135
Plate Temp.	260°C
Allowable Ambient Temp	5~40°C 80%RH
Power	200W
Product Size (mm)	225*155*90

Digital Display Hotplate Stirrer



Strong magnetic field



Stainless steel ceramic coated countertops

TECHNICAL DATA

Model	HS-5C	HS-5Pro
Control Mode	Brushless motor	Brushless motor
Max Stirring Volume	2L(H2O)	2L(H2O)
RPM	200-1500rpm	50-1500rpm
Timing Range	/	1min-12h
Control Mode	Digital display & Knob	Digital display & Button
Working Plate (mm)	Φ135	Φ135
Plate Temp.	280°C	310°C
Liquid/Plate Temp Accuracy	±1°C/±3°C	±1°C/±3°C
Power	300W	400W
Product Size (mm)	225*155*90	225*155*90

Digital Display Hotplate Stirrer



Forward and reverse



Stainless steel ceramic
coated countertops

TECHNICAL DATA

Model	HS-8Pro
Control Mode	Brushless motor
Max Stirring Volume	5L(H ₂ O)
RPM	50-1500rpm
Timing Range	1min - 12h
Control Mode	Digital display & Knob & Button
Working Plate (mm)	Square Plate 160*160mm
Plate Temp.	310°C
Allowable Ambient Temp	5~40°C 80%RH
Power	500W
Product Size (mm)	285*180*90

Large Capacity Magnetic Stirrer



Timing function



Knob operation



Forward and reverse




Large capacity

TECHNICAL DATA

Model	MS-5L	MS-10L	MS-15L	MS-30L	MS-50L
Control Mode	Display & Knob				
Display Method	LCD display				
Power	10W	20W	20W	30W	50W
Working Plate (mm)	180*180	220*220	220*220	260*260	330*330
Max Stirring Volume	5L	10L	15L	30L	50L
Speed Range	50-1500rpm	50-1500rpm	50-1500rpm	50-1300rpm	50-1100rpm
Speed Regulation Accuracy	5rpm	5rpm	5rpm	5rpm	5rpm
Timing Range	1min-23h59min				
Stir Bar Size (mm)	40	50	60	80	100
Product Size (mm)	285*180*65	315*220*65	315*220*65	350*260*85	435*330*85

Large Capacity Magnetic Stirrer



Forward and reverse



Extra large stirring capacity



Timing function



Knob operation

TECHNICAL DATA

Model	MS-100L
Control Mode	Digital display & Knob
Display Method	LCD display
Power	120W
Working Plate	400*400mm
Max Stirring Volume	100L
Speed Range	100-600rpm
Speed Regulation Accuracy	5rpm
Timing Range	1min-24h
Stir Bar Size	160mm

Multiple Magnetic Stirrer



Can be set to run synchronously or asynchronously



Timing function



Stepless speed regulation, wide speed range



LCD display



Durable brushless motor

TECHNICAL DATA

Model	MMS4Pro	MMS6Pro	MMS9Pro
Control	Asynchronous control		
Number Of Stirring Points	4	6	9
Max Capacity	4*500ml	6*500ml	9*500ml
Working Plate Size	4-(110*110mm)	6-(110*110mm)	9-(110*110mm)
Motor	Brushless motor		
Speed	50-1500rpm		
Bar Size (mm)	Z30		
Timing	1min-19h59min		
Voltage	AC100-240V		

Multiple Magnetic Stirrer with Heating



Can be set to run synchronously
or asynchronously



LCD display



304 stainless steel plate,
corrosion resistant



Heat more uniformly



Durable brushless motor

TECHNICAL DATA

Model	MHS4Pro	MHS6Pro
Control	Asynchronous control	
Number Of Stirring Points	4	6
Max Capacity	4*500ml	6*500ml
Working Plate Size	4-(110*110mm)	6-(110*110mm)
RPM	50-1200 rpm	
Plate Material	304 Stainless steel	
Plate Temperature	120°C	
Timing	1min-19h59min	
Bar Size (mm)	Z30	Z30
Power	240W	360W
Voltage	AC 220V	

Overhead Stirrer



Smooth start



Adjustable speed



DC permanent magnet motor



Powerful

TECHNICAL DATA

Model	OS-5	OS-10	OS-15S	OS-30S
Motor	Brushed motor		Brushless motor	
Max Amount Of Stirring	5L	10L	10L	20L
Range Of Rotate Speed	200-1500rpm	100 - 1000rpm	100 - 1500rpm	50 - 1200rpm
Timing	/	/	1min-24h	1min-24h
Max Torque	10N.cm	20N.cm	15N.cm	30N.cm
Max Viscosity	5000mPas	10000mPas	8000mPas	16000mPas
Drill Chuck Diameter	1-10mm	1-10mm	1-10mm	1-10mm
Power	30W	36W	50W	60W
Voltage	DC24V/2.5A			

Overhead Stirrer



Smooth start



Adjustable speed



DC permanent magnet motor



Stirring paddles penetrate

TECHNICAL DATA

Model	OS-15Pro	OS-30Pro
Motor	Brushless motor	Brushless motor
Max Amount Of Stirring	10L	20L
Range Of Rotate Speed	100-1500rpm	50 - 1200rpm
Timing	0-24h	0-24h
Max Torque	15N.cm	30N.cm
Max Viscosity	8000mPas	16000mPas
Drill Chuck Diameter	1-10mm	1-10mm
Power	50W	60W
Voltage	DC24V/2.5A	

Overhead Stirrer



One-click lock



Adjustable speed



High mixing capacity



Powerful

TECHNICAL DATA

Model	OS-50pro	OS-100pro
Motor	Brushless motor	
Max Amount Of Stirring	50L	100L
Range Of Rotate Speed	100 - 2000rpm	50 - 1200rpm
Timing	0 - 24h	0 - 24h
Max Torque	50N.cm	100N.cm
Max Viscosity	35000mPas	70000mPas
Drill Chuck Diameter	1-10mm	1-10mm
Power	80W	100W
Power adapter	DC24V/4A	

DRY BATH



Mini Dry Bath



Small volume



Multi-point operation



LCD display



Overtemperature protection

TECHNICAL DATA

Model	MDB100C	MDB100
Temperature Range	Room temp - 15°C ~ 100°C	Room temp + 5°C ~ 100°C
Temperature Stability	±0.5°C	±0.5°C
Temperature Homogeneity	±0.5°C	±0.5°C
Display Accuracy	0.1°C	0.1°C
Heating Time	≤12min (25-100°C)	≤12min (25-100°C)
Cooling Time	20 - 25 min (20-0°C)	/
Multi-point Operation	Yes	No
Temperature Point Can Be Set	9	9
Time Setting Range	5s - 23h59min	5s - 23h59min
Power	60W	48W
Voltage	DC 24V	DC 24V
Size	160*115*96 mm	160*115*96 mm

Module Options

Numbers And Aperture Of Test Tube

MDB1	40 * 0.2ml Centrifuge tube
MDB2	24 * 0.5ml Centrifuge tube
MDB3	15 * 1.5ml Centrifuge tube
MDB4	15 * 2.0ml Centrifuge tube
OEM Of Modules	Modules can be customized according to customer needs

Dry Bath



LCD display



Multi-point operation



Overtemperature protection



Multi modules optional

TECHNICAL DATA

Model	DB100C	DB100
Temperature Range	Room temp - 15°C ~ 100°C	Room temp + 5°C ~ 100°C
Temperature Stability	±0.5°C	±0.5°C
Temperature Homogeneity	±0.5°C	±0.5°C
Display Accuracy	0.1°C	0.1°C
Heating Time	≤12min (25-100°C)	≤12min (25-100°C)
Cooling Time	20 - 25 min (20-0°C)	/
Multi-point Operation	Yes	No
Temperature Point Can Be Set	9	9
Time Setting Range	5s--23h59min	5s--23h59min
Power	96W	96W
Voltage	AC100-240V	AC100-240V
Size	170*160*102 mm	170*160*102 mm

Module Options	Numbers And Aperture Of Test Tube
DB1	96 * 0.2ml Centrifuge tube
DB2	48 * 0.5ml Centrifuge tube
DB3	35 * 1.5ml Centrifuge tube
DB4	35 * 2.0ml Centrifuge tube
DB5	24 * 5.0ml Blood tube
DB6	12 * 5 / 15ml Centrifuge tube
DB7	6 * 50ml Centrifuge tube
DB8	Flat bottom plate (ELISA plate/culture plate, etc.) (Non-replaceable modules)
DB9	Cuvettes dedicated module
DB10	Aluminum beads (Non-replaceable modules)

OEM Of Modules

Modules can be customized according to customer needs



PRP Gel Maker



Memory program



Cosmetic & Dental & Restorative

TECHNICAL DATA

Model	DB100CG	DB100G
Temperature Range	Room temp - 15°C ~ 100°C	Room temp + 5°C ~ 100°C
Temperature Stability	±0.5°C	±0.5°C
Display Accuracy	0.1°C	0.1°C
Heating Time	≤12min (25-100°C)	≤12min (25-100°C)
Cooling Time	20 - 25 min (20-0°C)	/
Multi-point Operation / Memory program	Yes / P1 - 9	No / P1 - 9
Time Setting Range	5s--23h59min	5s--23h59min
Power	96W	96W
Module Size	110*75*86mm	110*75*86mm
Size	170*160*178 mm	170*160*178 mm

Dry Bath - Two Modules



LCD display



Memory program ,
9 temperature points



Rapid warming



Two modules, freely combined

TECHNICAL DATA

Model	DB100-2P
Temperature Range	Room temp + 5°C ~ 100°C
Temperature Stability	±0.5°C
Temperature Homogeneity	±0.5°C
Display Accuracy	0.1°C
Heating Time	≤12min (25-100°C)
Cooling Time	(110*75*32 mm) * 2
Multi-point Operation	No
Temperature Point Can Be Set	9
Time Setting Range	5s--24h
Power	200W
Voltage	AC100-240V
Size	280*180*85 mm

Module Options	Numbers And Aperture Of Test Tube
DB1	96 * 0.2ml Centrifuge tube
DB2	48 * 0.5ml Centrifuge tube
DB3	35 * 1.5ml Centrifuge tube
DB4	35 * 2.0ml Centrifuge tube
DB5	24 * 5.0ml Blood tube
DB6	12 * 5 / 15ml Centrifuge tube
DB7	6 * 50ml Centrifuge tube
DB9	Cuvettes dedicated module
DB2-1	Aluminum beads(Integral module,stand-alone) (Non-replaceable modules)
OEM Of Modules	Modules can be customized according to customer needs

Dry Bath Shaking Incubator



Thermal cover design prevents condensation from forming on the tube wall or tube cover during the temperature control process



Hot cover heat preservation function



Multi-point operation



Heating & cooling



Multi modules optional

TECHNICAL DATA

Model	DBSC-100Pro	DBS-100Pro
Actual temp range	RT - 15 ~ 100℃	RT ~ 100℃
Settable temp	-5℃ ~100℃	0℃~100℃
Temperature Stability	±0.5℃	±0.5℃
Max heating rate	5.5℃/min	5.5℃/min
Max cooling rate	5℃/min(100℃-Room temp) 1℃/min(Below room temp)	/
Program memory	P1 - 9	P1 - 9
Gradient Run	Yes	No
Speed	0-1500 rpm(Low module) / 0-800 rpm(high module)	
Timing	5s-24h	
Power	150W	
Voltage	100-240V 50/60HZ	
Size	265*190*150mm	

Optional thermal lid	DBS-Lid
Applicable models	DBS-1 / DBS-2 / DBS-3 / DBS-4

Module Options	Module capacity
DBS - 1	0.2ml *96(Pointed bottom - Centrifuge tube / 96-hole PCR microplate / PCR strips 8x0.2ml)
DBS - 2	0.5ml *24 (Pointed bottom - Centrifuge tube)
DBS - 3	1.5ml *24 (Pointed bottom - Centrifuge tube)
DBS - 4	2ml *24 (Round bottom - Centrifuge tube)
DBS - 5	15ml *8 (Round bottom - Centrifuge tube)
DBS - 6	50ml *4 (Pointed bottom - Centrifuge tube)

OEM Of Modules Modules can be customized according to customer needs

WATER BATH



Water Bath With Magnetic Stirrer



PID temperature control



Brushless Motor



Stainless steel inner tank



Strong Stirring Power

TECHNICAL DATA

Model	WB-6S	WBS-6Pro
Speed / Increment	/	100-1200RPM / 50RPM
Temperature Range	Room Temp. +5°C-100°C	Room Temp. +5°C-100°C
Liner Size	200*200*130mm(depth)-2L flask or 3L beaker	
Product Size (mm)	260*265*325	260*265*325
Display Accuracy	0.1°C	0.1°C
Power	800W	800W
Timing Range	1min-23h59min	1min-23h59min

Water Bath



-  Digital display thermostatic
-  High precise temperature control
-  One-piece stainless steel tank
-  High corrosion resistance

TECHNICAL DATA

Model	WB100-1 WB100-1F	WB100-2 WB100-2F	WB100-4 WB100-4F	WB100-6 WB100-6F	WB100-8F
Temperature Range	Room temp- 99.9℃				
Power	300W	600W	800W	1200W	1500W
Accuracy	±0.1℃				
Working Chamber Size (mm)	160*160*130	300*150*140	300*300*140	450*300*130	620*300*120

* WB100-F series are anti-dry series

HEATING MANTLE



Heating Mantle



Intelligent temperature control



Heating evenly, heating up fast

TECHNICAL DATA

Model	HM		HMC		HMS			HMSC	
Capacity	100ml	250ml	500ml	1L	2L	3L	5L	10L	20L
Function	Heating		Heating		Heating/magnetic stirrer			Heating/magnetic stirrer	
Heating Power	100W	150W	250W	350W	450W	600W	800W	1200W	2400W
Temperature Control	/		Digital temperature control			/		Digital temperature control	
Max Temperature	Room temp - 380°C		Room temp - 300°C		Room temp - 380°C			Room temp - 300°C	

INFRARED STERILIZER



Infrared Sterilizer



Sterilization only takes 5-7 seconds



Can be used in an anaerobic environment



No open-flame, more safe



Easy to clean

TECHNICAL DATA

Model	DS-900	DS-900S
Power	150W	240W
Max. Temperature Inside The Heating Hole	825°C±50°C	
Heating Temperature	Two temperatures available 400°C/850°C	
Max. Diameter Of Sterilizer Goods (mm)	φ14	φ35
Length Of Heating Zone (mm)	150	100
Warm-up Time	10min	

PIPETTE



Electric Pipette



Dynamic drainage + Gravity drainage



Membrane protection



6 levels adjustable pipetting speed



LCD display

TECHNICAL DATA

Model	EP100Pro
Range	0.1-100ml
Suction Speed	25ml < 5s (6 speeds adjustable)
Drain Mode	Dynamic drainage + Gravity drainage
Battery Life	Could work intermittently for about 8 hours
Type Of Pipette	Plastic or glass pipette (0.1-100ml); Pasteur pipettes
Filter Membrane	0.45µm hydrophobic filter membrane
Weight	180g

Liquid Vacuum Aspiration System



Work for multi purpose



Digital display speed control knob



9-speed speed regulation



High temperature disinfection

TECHNICAL DATA

Model	VP-6Pro	Fluid Absorption Rate	1.6L / Min
Type	Negative pressure suction	Ultimate Vacuum	0.06Mpa
Control Type	Digital display knob · 9 speeds	Diameter Of Collection Bottle	93mm
Pumping Rate	6L / Min	Power	10W

Bottle Top Dispenser



Digital window



Gear adjustment



Acid and alkali resistant



Safety valve protection



Various models



TECHNICAL DATA

Model	Capacity Range	Increment	Test Capacity	Systemic Error	Random Error	Repeat Error
DA-2ML	0.4-2ml	0.05	1ml	10ul	10ul	2ul
DA-5ML	1-5ml	0.1	2.5ml	25ul	25ul	5ul
DA-10ML	2-10ml	0.25	5ml	50ul	50ul	10ul
DA-30ML	5-30ml	0.5	15ml	125ul	125ul	25ul
DA-60ML	10-60ml	1	30ml	250ul	250ul	50ul

M Series Micropipette



Wide range



Dispense accurately

TECHNICAL DATA

Model	Capacity Range	Test Capacity	Tip	Increment	Accuracy Error	Repeat Error
M2.5	0.1 - 2.5ul	1.25	10ul	0.05ul	±3.00%	±3.00%
M10	0.5 - 10ul	5	10ul	0.1ul	±1.50%	±0.80%
M20	2 - 20ul	10	200ul	0.5ul	±1.20%	±0.40%
M50	5 - 50ul	25	200ul	0.5ul	±0.90%	±0.30%
M100	10 - 100ul	50	200ul	1ul	±1.00%	±0.15%
M200	20 - 200ul	100	200ul	1ul	±0.70%	±0.15%
M1000	100 - 1000ul	500	1000ul	5ul	±0.80%	±0.20%
M5000	1000 - 5000ul	2500	5000ul	50ul	±0.60%	±0.15%
M10000	2 - 10ml	5ml	10ml	0.1ml	±1.20%	±0.20%

P Series Whole Autoclavable Micropipette



121°C sterilization



Wide range



Dispense accurately



TECHNICAL DATA

Model	Capacity Range	Test Capacity	Tip	Increment	Accuracy Error	Repeat Error
P10	0.5 - 10ul	5ul	10ul	0.1ul	±1.00%	±1.00%
P20	2 - 20ul	10ul	200ul	0.5ul	±1.00%	±1.00%
P50	5 - 50ul	25ul	200ul	0.5ul	±0.90%	±0.60%
P100	10 - 100ul	50ul	200ul	1ul	±1.00%	±0.40%
P200	20 - 200ul	100ul	200ul	1ul	±0.80%	±0.30%
P1000	100 - 1000ul	500ul	1000ul	5ul	±0.70%	±0.25%
P5000	1000 - 5000ul	2500ul	5000ul	50ul	±0.60%	±0.30%
P10000	2 - 10ml	5ml	10ml	0.1ml	±1.20%	±0.30%



Multichannel Pipette



Digital window



8/12 channels optional



Suitable for 96-well plates



The tip can rotate 360 degrees

TECHNICAL DATA

Model	Type	Capacity Range	Tip	Increment	Test Capacity	Allow Maximum Error	
M8 - 10	8 channels	0.5 - 10ul	10ul	0.1ul	5	2.50%	0.125
M8 - 50	8 channels	5 - 50ul	200ul	0.5ul	25	1.50%	0.375
M8 - 300	8 channels	50 - 300ul	300ul	5ul	150	1.00%	1.500
M12 - 10	12 channels	0.5 - 10ul	10ul	0.1ul	5	2.50%	0.125
M12 - 50	12 channels	5 - 50ul	200ul	0.5ul	25	1.50%	0.375
M12 - 300	12 channels	50 - 300ul	300ul	5ul	150	1.00%	1.500

VACUUM PUMP



Oilless Diaphragm Vacuum Pump



Oil-free and no pollution



Illuminated switch



Overload,overheat and short circuit protection



High precision vacuum gauge

TECHNICAL DATA

Model	VP-10L	VP-15L
Type	Negative pressure	
Suction Flow Rate	10L/min	15L/min
Limit Vacuum Degree	0.075Mpa	0.08Mpa
Noise	<40db	<45db
Enclosure Ratings	IP21	
Power Supply	20W	30W
Diaphragm	Rubber	
Protection Devices	Overload protection, over temperature protection, short circuit protection	
Gross/Net Weight	1.95/1.58 kg	

Adjustable Speed Oil-free Diaphragm Vacuum Pump



The suction speed is adjustable



Illuminated switch



Overload, overheat and short circuit protection




High precision vacuum gauge

TECHNICAL DATA

Model	VP-15S
Type	Negative pressure
Suction Flow Rate	0-15 L/min
Limit Vacuum Degree	0.08Mpa
Noise	< 45db
Enclosure Ratings	IP21
Power Supply	30W
Diaphragm	Rubber
Protection Devices	Overload protection, over temperature protection, short circuit protection
Gross/Net Weight	1.95/1.58 kg

Oilless Diaphragm Vacuum Pump - 30L



Positive and negative pressure



Illuminated switch



Overload, overheat and short circuit protection



High precision vacuum gauge

TECHNICAL DATA

Model	VP-30L
Type	Positive and negative pressure
Suction Flow Rate	30 L/min
Limit Vacuum Degree	0.085Mpa
Greatest Pressure	5.0bar
Noise	< 50db
Enclosure Ratings	IP21
Power Supply	50W
Diaphragm	Rubber
Protection Devices	Overload protection, over temperature protection, short circuit protection

6L Mini Vacuum Pump



9-speed speed regulation



Digital display speed control knob



Mini portable, strong power



Steady motion

TECHNICAL DATA

Model	VP-6L	Pumping Rate	6L / Min
Type	Negative pressure suction	Ultimate Vacuum	0.06Mpa
Control Type	Digital display knob · 9 speeds	Power	10W

Vacuum Filtration Apparatus

TECHNICAL DATA

Receiving Flask Sand Core Diameter Sand Core Aperture

250ml	20mm	10um
500ml	40mm	10um
1000ml	40mm	10um
2000ml	40mm	10um
5000ml	40mm	30-50um
10000ml	40mm	30-50um



Boro 3.3



Tight sealing



Suitable for bottles
with GL-45



Large diameter·Fast
suction



TECHNICAL DATA

Receiving Flask	Sand Core Diameter	Filter Membrane	Sand Core Aperture
2000ml	80mm	90-100mm	10um
5000ml	80mm	90-100mm	10um
10000ml	80mm	90-100mm	10um

BALANCE



Electronic Balance



 Counting

 Unit conversion

TECHNICAL DATA

Model	Max Capacity	Accuracy	Pan Size(mm)	Dimensions(mm)
JNB50001	5000g	0.1g	160*180	280*200*80
JNB100001	10000g	0.1g	160*180	280*200*80
JNB150001	15000g	0.1g	160*180	280*200*80
JNB200001	20000g	0.1g	175*160	280*200*80
JNB300001	30000g	0.1g	175*160	280*200*80
JNB2001	200g	0.1g	115	280*200*160
JNB5001	500g	0.1g	128	280*200*160
JNB10001	1000g	0.1g	128	280*200*160
JNB20001	2000g	0.1g	128	280*200*160
JNB30001	3000g	0.1g	128	280*200*160
JNB1002	100g	0.01g	115	280*200*160
JNB5002	500g	0.01g	128	280*200*160
JNB10002	1000g	0.01g	128	280*200*160
JNB20002	2000g	0.01g	128	280*200*160
JNB30002	3000g	0.01g	128	280*200*160
JNB1003	100g	0.001g	90	280*200*160
JNB2003	200g	0.001g	90	280*200*160

0.001g Balance



Dual screen display



Unit conversion



Multi-device printing
Standard RS232 interfac




Full electromagnetic
interference protection

TECHNICAL DATA

Model	FA2003S	FA3003S	FA5003S
Max Capacity	200g	300g	500g
Min Readout		20mg	
Accuracy		0.001g	
Repeatability		±0.002g	
Linearity Error		±0.002g	
Stability Time		≤ 3S	
Working Temp.		15°C ~ 35°C	
Pan Size		φ90mm	
Dimensions		300*200*295 mm	
Calibration Mode		External calibration	
Communication Interface		RS232(USB interface optional)	

Analytical Balance - FA



LED display



Unit conversion



Multi-device printing
Standard RS232 interface



Full electromagnetic
interference protection

TECHNICAL DATA

Model	FA1004 FA1004N	FA1204 FA1204N	FA2004 FA2004N	FA2204 FA2204N
Max Capacity	100g	120g	200g	220g
Min Readout	0.01g			
Accuracy	0.1mg			
Repeatability	±0.0002g			
Linearity Error	±0.0003g			
Stability Time	≤ 3S			
Working Temp.	15°C ~ 35°C			
Pan Size	Standard model φ80mm / Optional model φ90mm			
Dimensions	300*200*295 mm			
Calibration Mode	Internal calibration(FA****N) / External calibration(FA****)			
Communication Interface	RS232(USB interface optional)			

* FA-N series Internal calibration balance

Dual Range Analytical Balance - CEB



RS232 / USB



Unit conversion

TECHNICAL DATA

Model	CEB1035	CEB2055	CEB2055N
Max Capacity	120g / 31g	220g / 51g	220g / 51g
Min Readout		0.1mg / 0.01mg	
Accuracy		0.1mg / 0.01mg	
Repeatability		±0.1mg / ±0.03mg	
Linearity Error		±0.2mg / ±0.03mg	
Stability Time		about 2S / 3S	
Weighing unit		g/oz/ct/mg/custom	
Working Temp.		30 - 60min	
Pan Size		φ90mm	
Dimensions		273*210*310 mm	
Calibration Mode	Internal calibration(CEB****N) / External calibration(CEB****)		
Communication Interface	RS232 / USB		

* CEB-N series Internal calibration balance

Moisture Analyzer



Multiple protections, more secure



Two calibration modes



High-efficiency halogen heating lamp



Multi-device printing, standard RS232 interface

TECHNICAL DATA

Model	MBA1102	MBA1102a	MBA1103	MBA1103(HBM)
Max Capacity	110g			
Weighing Precision	0.01g	0.005g	0.001g	0.001g
Sensor	Load Cell	Load Cell	Load Cell	HBM
Temp.Sensor	PT-100-2			
Temp.Range	40°C-160°C			
Temp.Setting / Display Accuracy	1°C			
Pan Size	φ96mm			
Moisture / Testing Range	90.00%-10.00%	95.00%-5.00%	100.00%-0.00%	100.00%-0.00%
Moisture / DRY% Readability	0.1%	0.05%	0.01%	0.01%
Operate.Temp	5°C-35°C			
Language	CN/EN			



JOANLAB[®]

Joan Lab Equipment (Zhejiang) Co.,Ltd.

☎ 0086 - 13676857721

🌐 www.joanlab.com

✉ mary@joanlab.com

📍 Address: 181# Gangfeng Road, Kangshan Street, Wuxing District, Huzhou City,
Zhejiang Province, China.

2024/01