

NERO Pipette



Single Channel, Variable Volume

NRO-2	0.2-2.0 µl
NRO-10	0.5-10 µl
NRO-20	2-20 µl
NRO-50	5-50 µl
NRO-100	10-100 µl
NRO-200	20-200 µl
NRO-1000	100-1000 µl
NRO-5000	500-5000 µl
NRO-10000	1000-10000 µl

2,550.-



Single Channel, Fixed Volume

NRO-F-1	1 µl
NRO-F-2	2 µl
NRO-F-5	5 µl
NRO-F-10	10 µl
NRO-F-20	20 µl
NRO-F-25	25 µl
NRO-F-50	50 µl
NRO-F-100	100 µl
NRO-F-200	200 µl
NRO-F-250	250 µl
NRO-F-500	500 µl
NRO-F-1000	1000 µl
NRO-F-2000	2000 µl
NRO-F-5000	5000 µl
NRO-F-10000	10000 µl

2,090.-



NERO Carousel
Pipette Stand

FVO-NRO

2,550.-



8 Channel

NRO-E-10	0.5-10 µl
NRO-E-20	0.2-20 µl
NRO-E-50	0.5-50 µl
NRO-E-100	10-100 µl
NRO-E-200	20-200 µl
NRO-E-300	40-300 µl

7,750.-



12 Channel

NRO-T-10	0.5-10 µl
NRO-T-20	0.2-20 µl
NRO-T-50	0.5-50 µl
NRO-T-100	10-100 µl
NRO-T-200	20-200 µl
NRO-T-300	40-300 µl

8,650.-

AQUA Multi-functional Electronic



Single Channel Micropipette

AQS-10	0.2-10 µl
AQS-20	0.5-20 µl
AQS-100	2-100 µl
AQS-200	5-200 µl
AQS-300	10-300 µl
AQS-500	10-500 µl
AQS-1000	50-1000 µl
AQS-5000	0.1-5 ml
AQS-10000	1-10 ml

19,950.-



8 Channel

AQE-10	0.2-10 µl
AQE-100	5-100 µl
AQE-300	10-300 µl

104,050.-



12 Channel

AQT-10	0.2-10 µl
AQT-100	5-100 µl
AQT-300	10-300 µl

108,590.-

E-BURETTE

(With Motorised Piston and
One-Touch One-Drop Dispensing)

Model No.	Capacity (ml)	Increment (ml)
TI-10	10	0.005
TI-25	25	0.01
TI-50	50	0.01



49,790.-

EASYAID - Electronic Pipette Filler



Gray EA-G Red EA-R Violet EA-V Green EA-GR Blue EA-GB



Max Speed :

1 ml - 0.3 ml / sec
2 ml - 0.6 ml / sec
5 ml - 1.5 ml / sec
10 ml - 3 ml / sec
25 ml - 8 ml / sec
50 ml - 8 ml / sec
100 ml - 8 ml / sec

6,350.-

Vacuum Aspirator

Vacuum Range :
0 to -850 mbar (Adjustable)

Flow rate of liquid :
23 mL/sec - 40 mL/sec

Max flow rate in Air :
15 L/min

Noise at 1 meter
distance : < 62 dB

VA-2

2 Litre Capacity

38,050.-

VA-4

4 Litre Capacity

79,190.-



Bottle Top Dispenser



with
Recirculation Valve
and Springless Valve®
Technology



4 liquid handling modes

- Rinsing
- Dilution
- Refilling
- Purging

without dismounting
the dispenser.



"Safety in
Hydrofluoric Acid"

Microlit SCITUS Bottle Top Dispenser

SCI-2.5	0.25-2.5 ml	6,790.-
SCI-5	0.5-5 ml	6,790.-
SCI-10	1-10 ml	6,790.-
SCI-30	2.5-30 ml	7,990.-
SCI-60	5-60 ml	7,990.-
SCI-100	10-100 ml	9,050.-

Microlit BEATUS Bottle Top Dispenser

BEAT-2.5	0.25-2.5 ml	8,150.-
BEAT-5	0.5-5 ml	8,150.-
BEAT-10	1-10 ml	8,150.-
BEAT-30	2.5-30 ml	9,550.-
BEAT-60	5-60 ml	9,550.-
BEAT-100	10-100 ml	10,890.-

Microlit ULTIMUS Bottle Top Dispenser

ULT-2.5	0.25-2.5 ml	9,990.-
ULT-5	0.5-5 ml	9,990.-
ULT-10	1-10 ml	9,990.-
ULT-30	2.5-30 ml	11,790.-
ULT-60	5-60 ml	11,790.-

Microlit LENTUS® Bottle Top Dispenser

LNT-HF-2.5	0.25-2.5 ml	27,150.-
LNT-HF-5	0.5-5 ml	27,150.-
LNT-HF-10	1-10 ml	27,150.-
LNT-HF-30	2.5-30 ml	31,690.-
LNT-HF-60	5-60 ml	31,690.-

Peristaltic Pump



Speed Variable Peristaltic Pump (ABS Engineering Plastic Housing)

MP110B

Flow Rate : 0.00011-750 ml/min
Speed Rate : 0.1 ~ 150RPM
Driver Weight : 3.6kg
Power Consumption <30W

35,650.-

MP310B

Flow Rate : 0.005-1750 ml/min
Speed Rate : 0.1 ~ 350RPM
Driver Weight : 3.9kg
Power Consumption <40W

73,250.-

MP610B

Flow Rate : 0.005-3000 ml/min
Speed Rate : 0.1 ~ 600RPM
Driver Weight : 3.9kg
Power Consumption <50W

104,150.-



Speed Variable Peristaltic Pump (304 Stainless Steel Housing)

MP100B

Flow Rate : 0.00011-750 ml/min
Speed Rate : 0.1 ~ 150RPM
Driver Weight : 3.5kg
Power Consumption <40W

51,850.-

MP300B

Flow Rate : 0.005-1750 ml/min
Speed Rate : 0.1 ~ 350RPM
Driver Weight : 4.3kg
Power Consumption <50W

90,150.-

MP600B

Flow Rate : 0.005-3000 ml/min
Speed Rate : 0.1 ~ 600RPM
Driver Weight : 4.3kg
Power Consumption <60W

159,450.-



Clever Flow Peristaltic Pump (ABS Engineering Plastic Housing)

MP110C

Flow Rate : 0.00011-750 ml/min
Speed Rate : 0.1 ~ 150RPM
Driver Weight : 3.6kg
Power Consumption <30W

64,950.-

MP310C

Flow Rate : 0.005-1750 ml/min
Speed Rate : 0.1 ~ 350RPM
Driver Weight : 3.9kg
Power Consumption <40W

98,390.-

MP610C

Flow Rate : 0.005-3000 ml/min
Speed Rate : 0.1 ~ 600RPM
Driver Weight : 3.9kg
Power Consumption <50W

129,150.-



Clever Flow Peristaltic Pump (304 Stainless Steel Housing)

MP100C

Flow Rate : 0.00011-750 ml/min
Speed Rate : 0.1 ~ 150RPM
Driver Weight : 4.5kg
Power Consumption <40W

72,350.-

MP300C

Flow Rate : 0.005-1750 ml/min
Speed Rate : 0.1 ~ 350RPM
Driver Weight : 4.5kg
Power Consumption <50W

104,850.-

MP600C

Flow Rate : 0.005-3000 ml/min
Speed Rate : 0.1 ~ 600RPM
Driver Weight : 4.5kg
Power Consumption <60W

135,490.-



Intelligent Dispensing Peristaltic Pump (ABS Engineering Plastic Housing)

MP110I

Flow Rate : 0.00011-750 ml/min
Speed Rate : 0.1 ~ 150RPM
Driver Weight : 3.6kg
Power Consumption <30W

88,950.-

MP310I

Flow Rate : 0.005-1750 ml/min
Speed Rate : 0.1 ~ 350RPM
Driver Weight : 3.9kg
Power Consumption <40W

121,750.-

MP610I

Flow Rate : 0.005-3000 ml/min
Speed Rate : 0.1 ~ 600RPM
Driver Weight : 3.9kg
Power Consumption <50W

153,090.-



Intelligent Dispensing Peristaltic Pump (304 Stainless Steel Housing)

MP100I

Flow Rate : 0.00011-750 ml/min
Speed Rate : 0.1 ~ 150RPM
Driver Weight : 4.5kg
Power Consumption <40W

122,190.-

MP300I

Flow Rate : 0.005-1750 ml/min
Speed Rate : 0.1 ~ 350RPM
Driver Weight : 4.5kg
Power Consumption <50W

128,090.-

MP600I

Flow Rate : 0.005-3000 ml/min
Speed Rate : 0.1 ~ 600RPM
Driver Weight : 4.5kg
Power Consumption <60W

184,850.-