

TECHNICAL SPECIFICATION

F019

REINFORCED POLYESTER FILM ADHESIVE TAPE

Spec No.	IT/R/998 Rev. 0
Page No.	1 of 1
Issue Date	23/09/2024
Control Status	Controlled Copy

	Properties	Unit	Value
1	TEMPERATURE CLASS	Deg. C	130
2	TYPE OF ADHESIVE	--	Precured Acrylic
3	BACKING MATERIAL	--	Polyester Film Reinforced with Unidirectional Glass Filament
4	TOTAL THICKNESS	mm	0.130 +/- 10%
5	TENSILE STRENGTH - MACHINE DIRECTION	Kgs/Cm	23 Minimum
6	ELONGATION AT BREAK - MACHINE DIRECTION	%	10 Minimum
7	ADHESION TO STEEL	Gms/Cm	350 Minimum
8	BREAK DOWN VOLTAGE - IS 2584 METHOD	kV	3.5 Minimum

TEST METHOD

IS 7809 PART II

Features : Good Resistance to Solvents and Varnish.

Note:

All Statements, Technical Information and Recommendations are based on Test, we believe to be reliable and should not be taken to frame specifications.

Before using the Tape the user shall determine the suitability of the product for his intended use.



INTEK TAPES PVT. LTD.

Prepared By

Approved By

Verified By

Please Correspond to :
No. 13, 9th Main 3rd Block, Jayanagar, Bangalore - 560 011. INDIA.
Phone No. 91-80-26655691 / 92 / 94 Fax: 91-80-26656693 / 26648984
e-mail : sales@intektapes.com

F003

Warranty & Liability : If the product supplied by Intek Tapes Pvt Ltd., is found to be defective within the shelf life period, Intek's sole obligation will be to replace the product or refund the purchase price.

Limitation of Liability : Intek shall not be liable for damages or loss arising out of using Intek's products whether direct, Indirect, incidental or consequential.