

imageCLASS
MF756Cx II
MF752Cdw II

Canon

Delighting You Always



A class of **Excellence**

Bring Ideas to Life in Vivid Colours.

Empower Your Business with the imageCLASS MF750 II Series. Boost productivity with advanced features, an intuitive interface, and robust security—all designed to keep your workflow smooth and efficient. Seamlessly integrating into any workspace, the MF750 II Series delivers vibrant colour where it counts and powerful performance where it matters most.

UP TO
33 PPM
(A4)
FAST PRINT
SPEED

UP TO
100 IPM
(A4)
DUPLEX
SCAN

V² COLOUR


APPLICATION
LIBRARY

MONO
UP TO **7,600**
PAGES
HIGH-YIELD
CARTRIDGE

COLOUR
UP TO **5,500**
PAGES
HIGH-YIELD
CARTRIDGE



INCREASED PRODUCTIVITY

Boost productivity with quick first print out time and single pass duplex scan—perfect for handling documents efficiently without slowing down your workflow.



CLOUD SCANNING AND PRINTING

Skip blank pages* for cleaner files. Print from or scan to third party cloud storage for seamless collaboration.

*applicable for scanning only



CUSTOMISE YOUR WORKFLOW

Streamline routine tasks with personalised shortcuts using the Application Library feature. Easily rearrange them on the Home screen to suit your workflow.



SECURITY ASSURANCE

Enjoy peace of mind with enhanced security features that verify system integrity at startup and protect against sniffing, spoofing, and tampering.

Business Can Be Simple

SPECIFICATIONS/ImageCLASS		MF756Cx II	MF752Cdw II
Printing Method		Print, Scan, Copy, Fax	
Print Speed	A4*	Colour Laser Beam Printing	
	Letter*	33 ppm (mono) / 33 ppm (colour)	
	2-Sided, A4	35 ppm (mono) / 35 ppm (colour)	
Print Resolution		29 ipm (mono) / 29 ipm (colour)	
Print Quality with Image Refinement Technology		600 x 600 dpi	
Warm-Up Time (From Power On)		1,200 x 1,200 dpi (equivalent)	
First Print Out Time (FPOT) (Approx.) ²		14 sec or less	
PRINT	Print Language	UFR II, PCL 6, Adobe® PostScript® 3™	UFR II, PCL 6
	Auto Duplex Print	Yes	
	Print Margins	Top/Bottom/Left/Right margin: 5 mm Top/Bottom/Left/Right margin: 10 mm (Envelope)	
	Supported File Format for USB Direct Print	JPEG, TIFF, PDF	
	Copy Speed	A4	33 ppm (mono) / 33 ppm (colour)
	Copy Resolution	up to 600 x 600 dpi	
	First Copy Out Time (FCOT) (Approx.) Platen Glass	A4	8.3 sec (mono) / 9.4 sec (colour)
	First Copy Out Time (FCOT) (Approx.) ADF	A4	7.6 sec (mono) / 8.8 sec (colour)
	Reduce/Enlargement	25-400% in 1% increments	
	Copy Features	Collate 2 on 1, 4 on 1, ID Card Copy, Passport Copy, 2-sided originals	
COPY	Scan Resolution	Optical	Up to 600 x 600 dpi
		Driver Enhanced	Up to 9,600 x 9,600 dpi
	Scan Type	Colour Contact Image Sensor	
	Maximum Scan Size	Platen Glass	Up to 216 x 297 mm
		ADF	Up to 216 x 356 mm
	Scan Speed ³	Platen Glass	1.8 sec (mono) / 1.9 sec (colour)
		ADF	(A4) 1-Sided: 50 ipm (mono) / 40 ipm (colour) (A4) 2-Sided: 100 ipm (mono) / 80 ipm (colour)
	Colour Depth	24-bit	
	Pull Scan	Yes, USB and Network	
	Push Scan (Scan To PC) with MF Scan Utility	Yes, USB and Network	
Scan To Cloud	MF Scan Utility		
SEND Method	SMB, Email, FTP, iFAX Simple	SMB, Email, FTP	
Colour Mode	Full Colour, Greyscale, Monochrome		
Scan Resolution	300 x 600 dpi		
SCAN	File Format	JPEG (single page), TIFF, PDF, Compact PDF, PDF (OCR)	
	Modem Speed	Up to 33.6 Kbps (Up to 3 sec/page)	-
	Fax Resolution	Up to 400 x 400 dpi	-
	Compression Method	MH, MR, MMR, JBIG	-
	Memory Capacity ⁴	Up to 90 jobs	-
	Speed Dials	Up to 281 dials	-
	Group Dials / Destinations	Up to 299 dials	-
	Sequential Broadcast	310 destinations	-
	Receive Mode	Fax Only, Fax/tel Auto Switch, Answer Mode, Manual	-
	Memory Backup	Permanent Fax Memory Backup	-
SEND	Fax features	Fax Forwarding, Remote Reception, PC Fax (Transmit Only), DRPD, ECM, Auto Redial, Fax, Activity Reports, Fax Activity Result Reports, Fax Activity Management Reports	

* Print speed is measured based on internal testing using A4/11 paper printed with 100% print ratio to original on one-sided paper. Internal testing involved continuously printing the same one page of content on plain paper. Print speed may vary depending on paper type, paper size or paper loading direction.
² First print out time is measured based on internal test procedure and may vary. When the printer is in the ready state, this is the time from receiving the print instruction from the controller to printing one sheet and finishing paper ejection.
³ Scan resolution 300 x 300 dpi.
⁴ Excluding toner cartridge.

SPECIFICATIONS/ImageCLASS		MF756Cx II	MF752Cdw II
Printing Method		Print, Scan, Copy, Fax	
Input tray Capacity (Plain Paper, 80 g/m ²)	Standard	Cassette	250 sheets
	Optional	Multi Purpose Tray	50 sheets
		ADF	50 sheets Duplex, Single Pass
	Maximum	850 sheets (Cassette + 1 Paper Feeder)	
Output Tray Capacity (Plain Paper, 80 g/m ²)		150 sheets	
Media Size	Cassette	A4, A5, A6, Legal, Letter, Foolscap, Indian Legal, Envelope (COM10, Monarch, DL, C5) Custom (Min. 98.0 x 148.0 mm to Max. 216.0 x 356.0 mm)	
	Paper Feeder	A4, A5, A6, Legal, Letter, Foolscap, Indian Legal, Envelope (COM10, Monarch, DL, C5) Custom (Min. 100.0 x 148.0 mm to Max. 216.0 x 356.0 mm)	
	Multi Purpose Tray	A4, A5, A6, Legal, Letter, Foolscap, Indian Legal, Index Card, Envelope (COM10, Monarch, DL, C5) Custom (Min. 76.0 x 127.0 mm to Max. 216.0 x 356.0 mm)	
	ADF	A4, A5, A6, Letter, Legal (min. 148 x 105 mm to max. 216 x 356 mm) Business card: 48 x 85 mm	
	2-Sided Printing	A4, A5, Legal, letter, Foolscap, indian Legal, Custom (min. 148.0 x 148.0 mm to max. 216 x 356.0 mm)	
Media type		Plain Paper, Recycled paper, Colour Paper, Bond Paper	
Media Weight	Cassette/Paper Feeder	60-200 g/m ²	
	Multi Purpose Tray	60-200 g/m ²	
	ADF	50-105 g/m ² (Business Card: 80 to 209 g/m ²)	
Standard Interface	Wired	USB 2.0, 10Base-T/100Base-TX/1000Base-T	
	Wireless	Wi-Fi 802.11b/g/n (Infrastructure Mode, Access Point, WPS)	
Network Protocol	Print	LPD, RAW, IPP, IPFS, WSD-Print (IPV4, IPV6)	LPD, RAW, IPP, WSD-Print (IPV4, IPV6)
	Scan	Email, SMB, WSD-Scan (IPV4, IPV6), FTP, OAuth 2.0	
	Application	mDNS, DHCP, Auto IP (IPV4), DHCPv6 (IPV6)	
	Management	SNMPv3 (IPV4, IPV6), HTTP/HTTPS, SNMP	
Network Security	Wired	IP/Mac Address Filtering, HTTPS, SNMPv3, IEEE802.1X, IPsec, TLS 1.3	
	Wireless	Infrastructure Mode: WPA-PSK(AES), WPA2-PSK(AES), WPA3-SAE(AES), WPA-EAP(AES), WPA2-EAP(AES), WPA3-EAP(AES) Access Point Mode: WPA2-PSK(AES), WPA3-SAE(AES)	
Mobile Solution	Canon PRINT app, AirPrint®, Mopria® Print Service, Microsoft Universal Print		
Compatible operating Systems ⁵	Windows®, Windows Server®, macOS®, Linux, ChromeOS™		
Other features	Department ID, Secure Print, Skip Blank Page, Application Library		
Available Software	Printer Driver, Fax Driver, Scanner Driver, MF Scan Utility, Toner Status	Printer Driver, Scanner Driver, MF Scan Utility, Toner Status	
Device Memory	1GB		
Storage (eMMC)	2GB		
Display	5" LCD Touchscreen		
Power Requirements	AC 220 - 240 V, 50/60 Hz		
Power Consumption (Approx)	Operation	700 W (max. 1380 W)	
	Standby	24 W	
	Sleep	1 W	
Operating Environment	Temperature	10 - 30°C	
	Humidity	20 - 80% RH (no condensation)	
Monthly Duty Cycle ⁶	50,000 pages		
Dimensions (W x D x H)	425 x 461 x 430 mm		
Weight* (Approx.)	21.95 kg		21.71 kg
	Toner Cartridge**	Standard	Cartridge 069 BK: 2,100 pages (bundled: 2,100 pages) Cartridge 069 CMY: 1,900 pages (bundled: 1,900 pages)
High		Cartridge 069H BK: 7,600 pages Cartridge 069H CMY: 5,500 pages	
Paper Feeder	Paper Feeder PF-K1 (550 sheets)		
Barcode Printing	Barcode Printing Kit-EIE		

¹ Based on I1U-1 #1 Char1 (standard mode).
² The latest drivers for Windows, Windows Server, Mac OS and Linux can be downloaded from the <https://asia.canon.com/support> website when available.
³ Monthly Duty Cycle value provides a means of comparison for product robustness in relation to other Canon laser printer devices, and does not refer to actual maximum image output per month.
⁴ Excluding toner cartridge.
⁵ Toner cartridge yield is in accordance with ISO/IEC 19798.



**SOUTH AND SOUTHEAST ASIA REGIONAL HEADQUARTERS
 CANON SINGAPORE PTE. LTD.**
 1 Fusionopolis Place, #14-10 Galaxis, Singapore 138522
 Tel : 65-6799-8888 | Fax : 65-6799-8882 | <https://asia.canon>

DEALER'S STAMP

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weights and dimensions are approximate. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.