

Thermal Receipt

1 Year Warranty



Model	DLI-200P	DLI-581PW	DLI-801PN
Color	Black	Black	Black
Print Method	Direct thermal	Direct thermal	Direct thermal
Resolution	203 dpi/8 dots/mm	203 dpi/8 dots/mm	203 dpi/8 dots/mm
Print Speed	60mm/s	70mm/s	180mm/s
Print Width	48 mm	48 mm	72 mm/48 mm
Print Length	N/A	N/A	N/A
Print density	N/A	1-4 level (adjustable)	1-10 level (adjustable)
Sensor	N/A	Out of paper detection	Out of paper detection, cover-open detection, print head temperature detection, cutter detection"
Paper Type	Standard thermal paper	Standard thermal paper	Standard thermal paper
Paper Width	50 mm	58±0.5mm	80±0.5mm/58±0.5mm
Paper roll diameter	Max 70mm	Max 70mm	Max 80mm
Software	ESC	Instruction set : ESC/POS	Instruction set : ESC/POS
Dimensions (L x H x W)	112x81x56mm	188x130x115mm	197.9x142x129mm
Weight	0.25 kg	0.98 kg	0.96 kg
Interface	USB , Bluetooth	USB , cash drawer ,Bluetooth	network interface(RJ-45), cash drawer , USB (สายแปลง)
Certificate	CE	CE	CE
Inbox	Printer + USB Cable	Printer + USB Cable + Power cord + Paper roll	Printer + USB Cable + Power cord + Power adapter + Paper roll + Paper holder + Insallation CD + สายแปลง LAN to USB

Description	พิมพ์กระดาษใบเสร็จ กว้าง 2" สามารถต่อ Bluetooth ได้ เหมาะสำหรับเชื่อมต่อ เมื่อถือ Tablet	พิมพ์กระดาษใบเสร็จ กว้าง 2" สามารถต่อ Cash drawer ได้ สามารถต่อ Bluetooth ได้ เหมาะสำหรับงาน POS	พิมพ์กระดาษใบเสร็จ กว้าง 2" - 3" สามารถต่อ Cash drawer ได้ ไม่สามารถต่อ Bluetooth ได้ เหมาะสำหรับงาน POS
-------------	------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------

SRP(inc.VAT)	1,350	1,390	2,990
--------------	-------	-------	-------



Model	DLI-S301	DLI-S302
Color	Black	Black
Print Method	Direct thermal	Direct thermal
Resolution	203 dpi/8 dots/mm	203 dpi 8 dots/mm
Print Speed	300 mm/s	300 mm/s
Print Width	72 mm	72 mm
Print Length	3276 mm	3276 mm
Print density	Automatic paper cutting + manual paper tearing	Automatic paper cutting + manual paper tearing
Sensor	Paper detection;Cover opening and closing detection;Paper shortage detection;Black mark detection	Paper detection;Cover opening and closing detection;Paper shortage detection;Black mark detection;
Paper Type	Standard thermal paper	Standard thermal paper
Paper Width	79.5±0.5mm	79.5±0.5mm
Paper roll diameter	82mm	82mm
Software	ESC	ESC
Dimensions (L x H x W)	140mm×178mm×130 mm	140mm×178mm×130 mm
Weight		
Interface	USB+Serial+LAN +Cash Drawer	USB+BlueTooth 4.0
Certificate	ISO FC CUL	ISO FCC UL
Inbox	Test Paper 1 Roll USB Cable 1 PCS User Manual 1 PCS	Test Paper 1 Roll USB Cable 1 PCS User Manual 1 PCS

Description	พิมพ์กระดาษใบเสร็จ กว้าง 3" สามารถต่อ Cash drawer ได้ ไม่สามารถต่อ Bluetooth สามารถต่อ Lan ได้ เหมาะสำหรับงาน POS ติดกระดาษ Auto	พิมพ์กระดาษใบเสร็จ กว้าง 3" ไม่สามารถต่อ Cash drawer ได้ สามารถต่อ Bluetooth ไม่สามารถต่อ Lan ได้ เหมาะสำหรับงาน POS ติดกระดาษ Auto
-------------	----------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------

SRP(inc.VAT)	3,490	3,690
--------------	-------	-------

SCANNERS



Thermal Label

1 Year Warranty



2 นิ้ว



3 นิ้ว



3 นิ้ว

Model	DLI-886A	DLI-886BW	DLI-760DW
Color	Black	Black	White
Print Method	Direct thermal	Direct thermal	Direct thermal
Resolution	203 dpi 8 dots/mm	203 dpi 8 dots/mm	203 dpi 8 dots/mm
Print Speed	90mm/s	90mm/s	180mm/s
Print Width	56 mm	80 mm	80 mm
Print Length	15-250 mm	15-200 mm	25-300 mm
Print density	N/A	N/A	N/A
Sensor	Black mark detection, Out of paper detection, seam mark detection, Cover-open detection, Thermal head temperature detection	Black mark detection, Out of paper detection, seam mark detection, Cover-open detection, Thermal head temperature detection	
Paper Type	Standard thermal paper, Die cut or continuous roll Labels, Black Label	Standard thermal paper, Die cut or continuous roll Labels, Black Label	Folding paper, roll paper, black mark paper, label paper, continuous paper
Paper Width			
Paper roll diameter			
Software	Label Design -	Label Design -	Label Design -
Dimensions (L x H x W)	0.79"(20 mm)-2.36"(60 mm)	0.79"(20 mm)-3.35"(80 mm)	0.79"(20 mm)-3.35"(80 mm)
Weight	90 mm	105 mm	
Interface	Deli BarTender UltraLite 197.5x132x128mm	Deli BarTender UltraLite 230x154x140mm	Deli BarTender UltraLite 210x154x135mm
Certificate	0.85 Kg	1.160 Kg	
Inbox	USB2.0 TypeB, Cash drawer 12v CE Printer + USB Cable + Power cord	USB2.0 TypeB, Cash drawer 24v, BT CE Printer + USB Cable + Power cord	USB2.0 Type B, Bluetooth CE Printer + USB Cable + Power cord

Description	พิมพ์ Sticker กว้าง 2" สามารถต่อ Cash drawer ได้ ไม่สามารถต่อ Bluetooth มีโปรแกรม Label Design ให้อัด Download	พิมพ์ Sticker กว้าง 3" สามารถต่อ Cash drawer ได้ สามารถต่อ Bluetooth ได้ มีโปรแกรม Label Design ให้อัด Download	พิมพ์ Sticker กว้าง 2"-3" ไม่สามารถต่อ Cash drawer ได้ สามารถต่อ Bluetooth ได้
--------------------	----------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------

SRP(inc.VAT)	2,095	2,890	2,590
---------------------	--------------	--------------	--------------



4 นิ้ว



4 นิ้ว



4 นิ้ว

Model	DLI-740C	DLI-750W	DLI-S401
Color	White	White	Black
Print Method	Direct thermal	Direct thermal	Direct thermal
Resolution	203 dpi 8 dots/mm	203 dpi 8 dots/mm	203 dpi 8 dots/mm
Print Speed	150mm/s	150mm/s	200 mm/s
Print Width	108mm	108mm	104 mm
Print Length	15-300 mm	15-300 mm	2000 mm
Print density	N/A	N/A	Label detection
Sensor	Stationary out of paper detection, cover-open detection, seam mark detection, black mark detection	Stationary out of paper detection, cover-open detection, seam mark detection, black mark detection	Black mark detection Cover opening and closing detection; Paper shortage detection; "Continuous paper;
Paper Type	Fold or roll paper, black mark continuous roll labels	Fold or roll paper, black mark continuous roll labels	Gap paper; Folded paper; Black mark paper
Paper Width	0.79"(20 mm)-4.65"(118 mm)	0.79"(20 mm)-4.65"(118 mm)	0.79"(20 mm)-4.65"(118 mm)
Paper roll diameter	120 mm	120 mm	130 mm
Software	Label Design - Deli BarTender UltraLite	Label Design - Deli BarTender UltraLite	Bartender, Deli Label
Dimensions	231.7x180.1x154.7mm	231.7x180.1x154.7mm	245x186x178 mm
Weight	2 Kg	2 Kg	
Interface	USB2.0 Type B	USB2.0 Type B , Bluetooth	USB+BlueTooth 4.0
Certificate	CE	CE	ISO FCC UL
Inbox	Printer + USB Cable + Power cord	Printer + USB Cable + Power cord	Printer + USB Cable + Paper Clip

Description	พิมพ์ Sticker กว้าง 2"-4" ไม่สามารถต่อ Cash drawer ไม่สามารถต่อ Bluetooth มีโปรแกรม Label Design ให้อัด Download	พิมพ์ Sticker กว้าง 2"-4" ไม่สามารถต่อ Cash drawer สามารถต่อ Bluetooth มีโปรแกรม Label Design ให้อัด Download	พิมพ์ Sticker กว้าง 2"-4" ไม่สามารถต่อ Cash drawer สามารถต่อ Bluetooth มีโปรแกรม Label Design ให้อัด Download
--------------------	------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------

SRP(inc.VAT)	3,790	4,190	4,590
---------------------	--------------	--------------	--------------

SCANNERS

198

Thermal Transfer Label

1 Year Warranty



Model	DLI-S351	DLI-S352
Printing Method	Thermal printing/Thermal Transfer	Thermal printing/Thermal Transfer
Resolution	203dpi	203dpi
Printing Speed	152 mm/s	152 mm/s
Max Width	104 mm	104 mm
Maximum Print Length	2000 mm	2000 mm
RAM	16 MB	16 MB
Flash Memory	8 MB	8 MB
Consumables Width	Max 118 mm, Min 20mm	Max 118 mm, Min 20mm
Consumables Thickness	Max 0.254mm Min 0.06mm	Max 0.254mm Min 0.06mm
Paper Roll Max Diameter	5"(127 mm)	5"(127 mm)
Core Inner Diameter	25.4 mm	25.4 mm
Carbon Ribbon Width		
Carbon Ribbon Length	300 m	300 m
Carbon Ribbon Roll core Diameter	Bartender, Deli Label	Bartender, Deli Label
Design Software		
Drive	CODE128 EAN128 ITF CODE39 CODE93	CODE128 EAN128 ITF CODE39CODE93
Barcode	EAN13 EAN13+2EAN13+5EAN8EAN8+2EAN8 +5CODABAR POSTNET UPC-A UPC-A+2UPC-A+5 UPC-E UPC-E+2 UPC-E+5 CPOST MSI MSIC PLESSEY ITF14 EAN14 MaxiCodeQRCODE PDF417 DataMatrix Code	EAN13 EAN13+2 EAN13+5 EAN8 EAN8+2 EAN8+5 CODABAR POSTNET UPC-A UPC-A+2 UPC-A+5 UPC-E UPC-E+2 UPC-E+5 CPOST MSI MSIC PLESSEY ITF14 EAN14 MaxiCode
QR-code		QRCODE PDF417 DataMatrix Code
Interface	USB+LAN+Parallel+Serial	USB+Bluetooth
Weight	210x285x180 mm	210x285x180 mm
Product Size	ISO FCC UL	ISO FCC UL
Certificate	Paper Clip 1 Set	Paper Clip 1 Set
Inbox	Test Ribbon 1 Roll Test Paper 1 Roll USB Cable 1 PCS User Manual 1 PCS	Test Ribbon 1 Roll Test Paper 1 Roll USB Cable 1 PCS User Manual 1 PCS
SRP(inc.VAT)	6,790	6,990

SCANNERS

199

Thermal Paper



Article No.	Description	SRP (Inc Vat)
DLI-3141	กระดาษใบเสร็จ ขนาด 57x50 มม., ความยาว 18 ม., 1 แพค มี 4 ม้วน	64
DLI-3141-CTN	กระดาษใบเสร็จ ขนาด 57x50 มม., ความยาว 18 ม., 1 ลัง มี 25 แพค หรือ 100 ม้วน	1,605
DLI-3145	กระดาษใบเสร็จ ขนาด 57x30 มม., ความยาว 6.5 ม., 1 แพค มี 4 ม้วน	35
DLI-3145-CTN	กระดาษใบเสร็จ ขนาด 57x30 มม., ความยาว 6.5 ม., 1 ลัง มี 50 แพค หรือ 200 ม้วน	1,766
DLI-3203	กระดาษใบเสร็จ ขนาด 80x80 มม., ความยาว 59 ม., 1 แพค มี 2 ม้วน	130
DLI-3203-CTN	กระดาษใบเสร็จ ขนาด 80x80 มม., ความยาว 59 ม., 1 ลัง มี 20 แพค หรือ 40 ม้วน	2,589
DLI-11874	สติ๊กเกอร์ความร้อน ขนาด 50x30 มม., 1000 แผ่น	98
DLI-11874-CTN	สติ๊กเกอร์ความร้อน ขนาด 50x30 มม., 72 ม้วน (1 ม้วน มี 1000 แผ่น)	7,088
DLI-11871	สติ๊กเกอร์ความร้อน ขนาด 70x50 มม., 500 แผ่น	105
DLI-11871-CTN	สติ๊กเกอร์ความร้อน ขนาด 70x50 มม., 48 ม้วน (1 ม้วน มี 500 แผ่น)	5,033
DLI-11870	สติ๊กเกอร์ความร้อน ขนาด 100x100 มม., 500 แผ่น	243
DLI-11870-CTN	สติ๊กเกอร์ความร้อน ขนาด 100x100 มม., 24 ม้วน (1 ม้วน มี 500 แผ่น)	5,829
DLI-12102	สติ๊กเกอร์ความร้อน ขนาด 60x40 มม., 950 แผ่น	145
DLI-12102-CTN	สติ๊กเกอร์ความร้อน ขนาด 60x40 มม., 24 ม้วน (1 ม้วน มี 950 แผ่น)	3,492
DLI-12108	สติ๊กเกอร์ความร้อน ขนาด 100x150 มม., 325 แผ่น	165
DLI-12108-CTN	สติ๊กเกอร์ความร้อน ขนาด 100x150 มม., 12 ม้วน (1 ม้วน มี 325 แผ่น)	1,977
DLI-81505	ริบบ้อน (Enhanced Wax-Based Carbon Ribbon) ขนาด 110x70 มม. - สีดำ	95
DLI-81505-CTN	ริบบ้อน (Enhanced Wax-Based Carbon Ribbon) ขนาด 110x70 มม. - สีดำ, 6 ม้วน	571
DLI-81525	ริบบ้อน (Wax-Based Carbon Ribbon) ขนาด 110x70 มม. - สีดำ	80
DLI-81525-CTN	ริบบ้อน (Wax-Based Carbon Ribbon) ขนาด 110x70 มม. - สีดำ, 6 ม้วน	482

Barcode Scanner

1 Year Warranty



New



Model	DLI-15130	DLI-S201	DLI-S211	DLI-AA711
Scanning principle		CCD red light technology	Laser transmitte	CMOS Image
Decoding type		1D	1D	1D (22 types) & 2D (3 types)
Scanning media		Paper, Screen	Paper	Paper, Screen , DPM (ullan):
Connection mode		Wired 1.8m	Wired 1.8m	Wired 3m
Scanning depth of field		5 mm - 300 mm.	5 mm - 300 mm.	5mm - 250mm
Description	ขาตั้ง Scanner สำหรับรุ่น DLI-S201, DLI-S211, DLI-14952	CCD อ่าน 1D ได้ทั้งกระดาษ และจอมือถือ	Laser อ่าน 1D ได้ทั้งกระดาษ (อ่านได้เร็ว และรองรับ Barcode ยาวๆ)	CMOS อ่าน 1D-2D บนกระดาษ , หน้าจอมือถือ และอ่านบาร์โค้ดที่ฝังลงบนเนื้อวัตถุชิ้นส่วนใหญ่ จะใช้งานกลุ่มอุตสาหกรรมยานยนต์ อิเล็กทรอนิกส์ และเครื่องมือราคาสูง เช่น เครื่องมือแพทย์
SRP(inc.VAT)	459	990	990	6,790

1D / 2D



1D / 2D

Battery 2000 mAh



1D / 2D

Battery 2500 mAh



1D / 2D

Battery 2000 mAh



Model	DLI-14952	DLI-S221	DLI-14952WB	DLI-14970WB
Scanning principle	CMOS Image	CMOS Image	CMOS Image	CMOS Image res 300,000 px
Decoding type	1D (22 types) & 2D (3 types)	1D (22 types) & 2D (3 types)	1D (22 types) & 2D (3 types)	1D & 2D
Scanning media	Paper, Screen	Paper, Screen	Paper, Screen	Paper, Screen
Connection mode	Wired 1.8m	Wireless (ไร้สาย)	BT (ไร้สาย)	Wired 1.8m
Scanning depth of field	100 mm - 380 mm.	100 mm - 380 mm.	100 mm - 300 mm.	1D (50-200 mm.) / 2D (100-400 mm.)
Description	CMOS อ่าน 1D-2D ได้ทั้งกระดาษ และจอมือถือ	CMOS อ่าน 1D-2D ได้ทั้งกระดาษ และจอมือถือ	CMOS อ่าน 1D-2D บนกระดาษ และหน้าจอมือถือได้	CMOS อ่าน 1D-2D บนกระดาษ และหน้าจอมือถือได้, มีแท่นชาร์จในตัว, Drop 1.2M
SRP(inc.VAT)	1,590	2,290	2,390	3,990

1D / 2D

Battery 2000 mAh



1D / 2D



1D / 2D



1D / 2D



Model	DLI-S227WB	DLI-S231	DLI-14960S	DLI-AA510
Scanning principle	CMOS Image	CMOS Image	CMOS Image	CMOS Image
Decoding type	1D (22 types) & 2D (3 types)	1D (22 types) & 2D (3 types)	1D & 2D	1D & 2D
Scanning media	Paper, Screen	Paper, Screen	Paper, Screen	Paper, Screen
Connection mode	BT (ไร้สาย)	Wired 1.8m	Wired 1.8m	Wired 1.6m
Scanning depth of field	100 mm - 300 mm.	5 mm - 300 mm.	1D (10-200 mm.) / 2D (30-450 mm)	1D (50-200 mm.) / 2D (100-400 mm.)
Description	CMOS อ่าน 1D-2D บนกระดาษ และหน้าจอมือถือ	CMOS อ่าน 1D-2D ได้ทั้งกระดาษ และจอมือถือ	CMOS อ่าน 1D-2D บนกระดาษ และจอมือถือ	CMOS อ่าน 1D-2D บนกระดาษ และหน้าจอมือถือ
SRP(inc.VAT)	2,290	2,390	4,390	5,790

SCANNERS

200



Mobile & Tablet

Swift2 Pro		Swift2 Ultra			LARK1						
<p>มือถือพร้อมพิมพ์ในตัว ขนาด 58 มม ใส่ Sim 4G ได้</p> 		<p>มือถือพร้อมพิมพ์ในตัว ขนาด 58 มม ใส่ Sim 4G ได้ Support 1D Barcode / 2D QR Scanning (Option)</p> 			<p>Support 1D Barcode / 2D QR Scanning ใส่ Sim 4G ได้ IP68, Drop Test: 1.5m</p> 						
	IMI-6975189859517N (มี NFC)	IMI-6975189851511N(No Scanner) IMI-6975189851528N(Newland Scanner) IMI-6975189851535N(Zebra Scanner)			IMI-6975189855564N(Totinfo Scanner) IMI-697518985571N(Zebra Scanner) IMI-697518985588N(Zebra Scanner)						
OS	Android 13	Android 13	Android 13		Android 13						
CPU	Quad core Arm Cortex-A53 2.0GHz	Octa-core (Dual-core ARM Cortex-A76 2.2GHz, Hexa-core ARM Cortex-A55 2.0GHz)*	Octa-core (Dual-core ARM Cortex-A76 2.2GHz, Hexa-core ARM Cortex-A55 2.0GHz)*		Octa core Arm Cortex-A76 2.2GHz						
Display	6.5", 1600 x 720 Touch screen	6.5", 1600 x 720 Touch screen	6.5", 1600 x 720 Touch screen		6.5", 1600 x 720 Touch screen						
RAM	4GB	4GB	4GB		4GB / 8GB						
ROM	32GB	64GB	64GB		32GB / 64GB / 128GB						
External Memory Support	TF Card up to 64 GB	TF Card up to 64 GB	TF Card up to 64 GB		TF Card						
SIM	Nano SIM x 1, 2G/3G/4G LTE	Nano SIM x 1, 2G/3G/4G LTE	Nano SIM x 1, 2G/3G/4G LTE		Nano SIM x 1, 2G/3G/4G LTE						
Camera	5 MP Support 1D Barcode / 2D QR Scanning	5 MP	802.11 a/b/g/n/ac (2.4GHz/5GHz)		2.0 MP front camera, 13 MP rear camera						
Wi-Fi	802.11 a/b/g/n/ac (2.4GHz/5GHz)	802.11 a/b/g/n/ac (2.4GHz/5GHz)	802.11 a/b/g/n/ac (2.4GHz/5GHz)		802.11 a/b/g/n/ac (2.4GHz/5GHz)						
Bluetooth Version	Bluetooth v5.0	Bluetooth v5.2	Yes		Bluetooth v5.2						
NFC	Optional	Yes	Yes		มี NFC						
Interface	USB Type-C x 1	USB Type-C x 1	High Speed Printing, Up to 100mm/s, 58mm in Width & 50mm in Diameter		USB Type-C x 1 (Support OTG)						
Printer	High speed printing, up to 100mm/s, 58mm in width & 50mm in diameter	Support Receipt & Label Printing	Support Receipt & Label Printing		Support 1D Barcode / 2D QR Scanning						
Battery	Capacity: 7.7V / 3350mAh / 25.8Wh	Capacity: 7.7V / 3350mAh / 25.8Wh	Capacity: 7.7V / 3350mAh / 25.8Wh		Capacity: 3.87V / 5000mAh / 19.35Wh						
Power Adapter	Input: 100 ~ 240V; Output: 5V / 2A	Input: 100 ~ 240V; Output: 9V / 2.22A	Operating temperature: -10 ~ 50°C		Input: 100 ~ 240V; Output: 9V / 2.22A						
Environment	Operating temperature: -10 ~ 50°C	Storage temperature: -20 ~ 60°C	Operating temperature: -10 ~ 50°C		Operating temperature: -10 ~ 50°C						
Drop Test	1m	1m	1m		Storage temperature: -20 ~ 60°C						
Dimensions	84.3 X 240.6 X 59.6mm	84.3 X 240.6 X 63.5(17.0)mm	180.5 X 81.4 X 17.2mm		IP68, Drop Test: 1.5m						
Weight	450g	474g	280g		180.5 X 81.4 X 17.2mm						
Certification	Google GMS , FCC CE IMDA WEEE	Google GMS , FCC CE IMDA WEEE	Google GMS , FCC CE IMDA WEEE		Google GMS , FCC CE IMDA WEEE						
SRP (Inc vat)	10,486	11,770	15,515	18,083	13,803	16,799	20,651				
FALCON1		FALCON2			FALCON2 Max						
<p>มือถือพร้อมพิมพ์ในตัว ขนาด 58 มม ใส่ Sim 4G ได้ มี Port Lan , Port ลื่นชัก</p> 		<p>ใส่ Sim 4G ได้ (Option)</p> 			<p>ใส่ Sim 4G ได้ Support 1D Barcode / 2D QR Scanning (Option)</p> 						
	IMI-TF1-11-2-16 (ไม่มี NFC) IMI-TF1-11-2-16NFC (มี NFC) IMI-TF1-11-4-32NFC (มี NFC)	IMI-6975189855625N(4/64GB,WIFI, ไม้มี Fingerprint) IMI-697518985595N(8/128GB,WIFI, ไม้มี Fingerprint) IMI-6975189855816N(4/64GB,LTE, ไม้มี Fingerprint) IMI-6975189855823N(8/128GB,LTE, ไม้มี Fingerprint)			IMI-6975189856820N(4/64GB , No Scanner) IMI-6975189856837N(8/128GB , No Scanner) IMI-6975189851580N(4/64GB , Newland Scanner) IMI-6975189856851N(8/128GB , Newland Scanner)						
OS	Android 11	Android 13	Android 13		Android 13						
CPU	Octa-Core 2.0GHz, Dual*A75 and Hexa*A55*	Octa core (Dual-core Arm Cortex-A76 2.2GHz, Hexa-core Arm Cortex-A55 2.0GHz)	Octa core (Dual-core Arm Cortex-A76 2.2GHz, Hexa-core Arm Cortex-A55 2.0GHz)		Octa core (Dual-core Arm Cortex-A76 2.2GHz, Hexa-core Arm Cortex-A55 2.0GHz)						
Display	10.1", 800 x 1280 Touch screen and 2.4" LED Screen	10.95", 1920 x 1200 Touch screen	10.95", 1920 x 1200 Touch screen		12.6" IPS, 2560 x 1600 Touch screen						
RAM	2GB, 4GB	4GB, 8GB	4GB, 8GB		4GB, 8GB						
ROM	16GB, 32GB	64GB, 128GB	64GB, 128GB		64GB, 128GB						
External Memory Support	TF Card up to 64 GB	TF Card up to 64 GB	TF Card up to 64 GB		TF Card up to 64 GB						
SIM	Nano SIM x 1, 2G,3G,4G LTE	Nano SIM x 1, 2G,3G,4G LTE	Nano SIM x 1, 2G,3G,4G LTE		Nano SIM x 1, 2G,3G,4G LTE						
Camera	0.3 MP Support 1D / 2D QR Scanning	2 MP front camera, 13 MP rear camera	2 MP front camera, 13 MP rear camera		2 MP front camera, 13 MP rear camera						
Wi-Fi	802.11 a/b/g/n/ac (2.4GHz/5GHz)	802.11 a/b/g/n/ac (2.4GHz/5GHz)	802.11 a/b/g/n/ac (2.4GHz/5GHz)		802.11 a/b/g/n/ac (2.4GHz/5GHz)						
Bluetooth Version	Bluetooth v5.0	Bluetooth v5.2	Bluetooth v5.2		Bluetooth v5.2						
NFC	Optional	Yes	Yes		Yes						
Interface	USB Type-C x 1 ,USB Type-Ax2 ,RJ11x1, RJ12 x 1, RJ45 x 1	USB Type-C x 1	Optional		USB Type-C x 1						
Printer	High speed printing, up to 250mm/s , Automatic cutter,80mm(width)(diameter)	Optional	Optional		Optional						
Battery	No	Capacity: 3.8V / 8000mAh / 19.35Wh	Capacity: 3.8V / 8000mAh / 19.35Wh		Capacity: 3.89V / 10,000mAh / 38Wh						
Power Adapter	Input: 100 ~ 240V; Output: 24V / 2.5A	Input: 100 ~ 240V; Output: 9V / 2.22A	Input: 100 ~ 240V; Output: 9V / 2.22A		Input: 100 ~ 240V; Output: 9V / 2.22A						
Environment	Operating temperature: 0 ~ 40°C	Operating temperature: -10 ~ 50°C	Operating temperature: -10 ~ 50°C		Operating temperature: -10 ~ 50°C						
Drop Test	No	No	No		Storage temperature: -20 ~ 60°C						
Dimensions	248 x 199 x 140mm	257.2 x 168.8 x 9mm	257.2 x 168.8 x 9mm		No						
Weight	1.785Kg	0.56 Kg	0.56 Kg		292.80 x 191.55 x 9.50mm						
Certification	FCC CE IMDA WEEE	Google GMS FCC CE IMDA WEEE	Google GMS FCC CE IMDA WEEE		0.56 Kg						
SRP (Inc vat)	12,840	14,338	15,990	11,342	16,906	16,050	19,581	21,400	24,931	24,931	28,355

SCANNERS

Desktop



Swan1 Pro

Swan2

Swan2 - Printer 58mm



	IMI-6975189859005 (4/64GB) IMI-6975189859036 (8/128GB)	IMI-6975189855762 (1 Display 15.6", 4/64GB) IMI-6975189856134 (2 Display 15.6"+10.1", 4/64GB)	IMI-6975189856370 (1 Display 15.6", 4/64GB) IMI-6975189856325 (2 Display 15.6"+10.1", 4/64GB) IMI-6975189856332 (2 Display 15.6"+15.6", 4/64GB)
OS CPU Display	Android 11 series iMin UI Octa-Core, Dual*A78 and Hexa*A55, 2.2GHz 15.6" 1920x1080 Touch screen	Android 13 Octa-core A55 2.0GHz 15.6" 1920x1080 FHD 250Nit Touch screen 15.6" 1920x1080 FHD 250Nit Touch screen +10.1" 800x1280 280Nit"	Android 13 Octa-core A55 2.0GHz 15.6"1920x1080 FHD 250Nit Touch screen 15.6"1920x1080 FHD 250Nit Touch screen+10.1"800x1280 280Nit 15.6"1920x1080 FHD 250Nit Touch screen+15.6"1920x1080 FHD250Nit
RAM ROM External Memory Support Wi-Fi Bluetooth Version NFC Interface	4GB , 8GB 64GB , 128GB TF Card up to 128 GB 802.11 a/b/g/n/ac (2.4GHz/5GHz) No Bluetooth v4.2 No USB Type-A x 3 , RJ11 x 1, RJ12 x 1, RJ45(1000M) x 1 , TF Card x 1, DC Jack x 1	4GB 64GB N/A 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) Bluetooth v5.4 No USB-A x 5, USB-C x 1, 3.5mm Headphone Jack x 1, DC Jack x 1, HDMI x 1, RJ11 x 1, RJ12 x 1, RJ45 x 1, Pogo pin (12 pin) TF Card (up to 1TB) x 1 No	4GB 64GB N/A 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) Bluetooth v5.4 No USB-A x 5, USB-C x 1, 3.5mm Headphone Jack x 1, DC Jack x 1, HDMI x 1, RJ11 x 1, RJ12 x 1, RJ45 x 1, Pogo pin (12 pin)TF Card (up to 1TB) x 1 58mm in width & 50mm in diameter, up to 100mm/s printing speed
Printer	No	No	58mm in width & 50mm in diameter, up to 100mm/s printing speed
Power Adapter	Input: 100 ~ 240V; Output: 24V / 1.5A	Input: 100 ~ 240V; Output: 24V / 1.5A	Input: 100 ~ 240V; Output: 24V / 1.5A
Environment	Operating temperature: 0 ~ 40°C Storage temperature: -10 ~ 50°C	Operating temperature: -10 ~ 50°C Storage temperature: -20 ~ 60°C	Operating temperature: -10 ~ 50°C Storage temperature: -20 ~ 60°C
Dimensions Weight Certification	363 x 185 x 300mm 3.3Kg FCC CE IMDA WEEE	365 x 190 x 306 mm 3.96Kg Google GMS FCC CE IMDA WEEE	365 x 190 x 306 mm 3.96Kg Google GMS FCC CE IMDA WEEE
SRP (Inc vat)	24,931 30,067	14,231 17,762	16,906 20,437 23,968

Swan2 - Printer 80mm

Swan2 Pro

Swan2 Pro Printer 80mm



- 15.6" Full HD Main Display
- 15.6" Full HD Main Display + 10.1" HD Customer Facing Display
- 15.6" Full HD Main Display + 15.6" Full HD Customer Facing Display

80mm Printer Series

- 15.6" Full HD Main Display + 80mm Thermal Printer
- 15.6" Full HD Main Display + 10.1" HD Customer Facing Display + 80mm Thermal Printer

	IMI-6975189856349 (1 Display 15.6", 4/64GB) IMI-6975189856356 (2 Display 15.6"+10.1", 4/64GB)	IMI-6975189851313 (1 Display 15.6", 4/64GB) IMI-6975189851320 (1 Display 15.6", 8/128GB) IMI-6975189851337 (2 Display 15.6"+10.1", 4/64GB) IMI-6975189851344 (2 Display 15.6"+10.1", 8/128GB) IMI-6975189851351 (2 Display 15.6"+15.6", 4/64GB) IMI-6975189851368 (2 Display 15.6"+15.6", 8/128GB)	IMI-6975189851436 (1 Display 15.6", 4/64GB) IMI-6975189851443 (1 Display 15.6", 8/128GB) IMI-6975189851450 (2 Display 15.6"+10.1", 4/64GB) IMI-6975189851467 (2 Display 15.6"+10.1", 8/128GB)
OS CPU Display	Android 13 Octa-core A55 2.0GHz 15.6" 1920x1080 FHD 250Nit Touch screen 15.6" 1920x1080 FHD 250Nit Touch screen +10.1" 800x1280 280Nit	Android 15 Octa-Core (Dual-Core Arm Cortex-A76 Hexa-Core Arm Cortex-A55 2.0GHz) 15.6" (Full HD), 1920 x 1080 15.6"(Full HD), 1920 x 1080+10.1" (HD), 280 x 800 15.6"(Full HD), 1920 x 1080+15.6"(Full HD),1920x1080	Android 15 Octa-Core (Dual-Core Arm Cortex-A76 Hexa-Core Arm Cortex-A55 2.0GHz) 15.6" (Full HD), 1920 x 1080 15.6" (Full HD), 1920 x 1080 + 10.1"(HD),1280 x 800
RAM ROM External Memory Support Wi-Fi Bluetooth Version NFC Interface	4GB , 8GB 64GB , 128GB N/A 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) Bluetooth v5.4 No USB-A x 5, USB-C x 1, 3.5mm Headphone Jack x 1, DC Jack x 1, HDMI x 1, RJ11 x 1, RJ12 x 1, RJ45 x 1, Pogo pin (12 pin)TF Card (up to 1TB) x 1 80mm (with automatic cutter) in width & 80mm in diameter, up to 250mm/s	4GB , 8GB 64GB , 128GB N/A 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) Bluetooth v5.4 No USB-A x 5, USB-C x 1, 3.5mm Headphone Jack x 1, DC Jack x 1, HDMI x 1, RJ11 x 1, RJ12 x 1, RJ45 x 1, Pogo pin (12 pin)TF Card (up to 1TB) x 1 No	4GB , 8GB 64GB , 128GB N/A 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) Bluetooth v5.4 No USB-A x 5, USB-C x 1, 3.5mm Headphone Jack x 1, DC Jack x 1, HDMI x 1, RJ11 x 1, RJ12 x 1, RJ45 x 1, Pogo pin (12 pin) TF Card (up to 1TB) x 1 80mm (with automatic cutter) in width & 80mm in diameter, up to 250mm/s printing speed
Printer	80mm (with automatic cutter) in width & 80mm in diameter, up to 250mm/s	No	80mm (with automatic cutter) in width & 80mm in diameter, up to 250mm/s printing speed
Power Adapter	Input: 100 ~ 240V; Output: 24V / 1.5A	Input: 100 ~ 240V; Output: 24V / 1.5A	Input: 100 ~ 240V; Output: 24V / 1.5A
Environment	Operating temperature: -10 ~ 50°C Storage temperature: -20 ~ 60°C	Operating temperature: -10 ~ 50°C Storage temperature: -20 ~ 60°C	Operating temperature: -10 ~ 50°C Storage temperature: -20 ~ 60°C
Dimensions Weight Certification	365 x 190 x 306 mm 3.96Kg Google GMS FCC CE IMDA WEEE	365 x 189 x 303 mm N/A Google GMS FCC CE IMDA WEEE	365 x 189 x 389 mm N/A Google GMS FCC CE IMDA WEEE
SRP (Inc vat)	19,581 23,112	19,260 24,610 23,005	26,750 32,100
SRP (Inc vat)	19,581 23,112	28,355 26,750 32,100	30,495 35,845


SCANNERS

Kiosk

By order 45-60 Day




Crane1		Article No.	Description/Spec	Type	SRP Inc Vat
OS	Android 13	IMI-6975189859166	IDS Crane1 16" 4/64GB	Touch NFC	28,569
CPU	Octa-Core (Dual-Core Arm Cortex-A78 2.2GHz, Hexa-Core Arm Cortex-A55 2.0GHz)	IMI-6975189859128	IDS Crane1 16" 8/128GB	Touch NFC	33,919
Display	32" Display: 746.5 x 441 x 56.5mm 27" Display: 645.5 x 384 x 47.5mm 21.5" Display: 525 x 316.7 x 46.5mm 16" Display: 375 x 246 x 36.5mm	IMI-6975189859630	IDS Crane1 21.5" 4/64GB	Touch NFC	35,631
RAM	4GB, 8GB	IMI-6975189859579	IDS Crane1 21.5" 8/128GB	Touch NFC	40,981
ROM	64GB, 128GB	IMI-6975189859135	IDS Crane1 27" 4/64GB	Touch NFC	42,800
External Memory Support	TF Card up to 64 GB	IMI-6975189859142	IDS Crane1 27" 8/128GB	Touch NFC	48,150
SIM	Nano SIM x 1, 2G/3G/4G LTE	IMI-6975189859586	IDS Crane1 32" 4/64GB	Touch NFC	49,969
Rear Camera	5 MP Support 1D Barcode / 2D QR Scanning	IMI-6975189859593	IDS Crane1 32" 8/128GB	Touch NFC	55,319
Wi-Fi	802.11 a/b/g/n/ac (2.4GHz/5GHz)				
Bluetooth Version	Bluetooth v5.3				
NFC	No				
Interface	USB Type_A 2.0 x 6, USB Type_C x 1, RJ12 x 1, RJ11 x 1, RJ45 x 1, DC Jack x 1, 3.5mm Audio Jack x 1				
Printer	16" Display: USB Pogo Pin x 2, USB+I2C Pogo Pin x 1 21.5" / 27" / 32" Display: USB Pogo Pin x 3, USB+I2C Pogo Pin x 1				
Battery	High speed printing, up to 100mm/s, 58mm in width & 50mm in diameter				
Power Adapter	Capacity: 7.7V / 3350mAh / 25.8Wh				
Environment	Input: 100 ~ 240V; Output: 24V / 2.5A				
Storage temperature:	Operating temperature: -10 ~ 50°C				
Weight	-20 ~ 60°C				
Certification	32" Display: 9.3kg 27" Display: 7.3kg 21.5" Display: 4.8kg 16" Display: 1.6kg FCC CE IMDA WEEE				
	Crane1 Stand 1 Support 16" , 21.5" , 27"	IDS Crane1 Table Stand		Stand	13,482
	Crane1 Stand 2 Support 21.5" , 27" , 32"	IMI-6975189859807 IDS Crane1 Floor Stand		Stand	22,363
	Crane1 Accessory 1 Support 16" , 21.5" , 27" , 32"	IDS Crane1 Scanner		Accessory	3,638
	Crane1 Accessory 2 Support 16" , 21.5" , 27" , 32"	IMI-6975189859616 IDS Crane1 MSR		Accessory	2,782
	Crane1 Accessory 3 Support 16" , 21.5" , 27" , 32"	IMI-6975189859623 IDS Crane1 Status Light		Accessory	1,819
	Crane1 Accessory 4 Support 16" , 21.5" , 27" , 32"	IMI-6975189859814 IDS Crane1 NFC		Accessory	1,819
	Crane1 Accessory 5 Support 16" , 21.5" , 27" , 32"	IMI-SC1-Printer IDS Crane1 Printer		Accessory	7,169



1920 x 1080



1920 x 1080



1920 x 1080



1920 x 1200