



# TIS RCU MODULE

Room Control Unit with 8 Channels

Data Sheet Rev 3.2

Model: RCU-8OUT-8IN



## OVERVIEW

This product is a smart controller with eight channels ideal for the automation of lights, sensors, FCU, curtains and motorized devices for maximum efficiency and user comfort.

### KEY BENEFITS

- + Compatibility with other TIS solutions
- + Improving management efficiency
- + Saving energy & costs
- + Applicable in all types of projects

### KEY FEATURES

- ★ Din rail & wall mounting
- ★ 8 input/output channels
- ★ User-friendly programming
- ★ Controllable via TIS App



BARCODE (UPC-12)



# TIS RCU MODULE

Room Control Unit with 8 Channels

Model: RCU-8OUT-8IN



## PRODUCT SPECIFICATIONS

↑ <b>Output Switching Voltage</b>	Number of channels	8
	Nominal voltage	0 – 230 V AC 50/60 Hz
	Max. switching Voltage	440VAC / 125VDC
	Analog Output	Ch8 include 0-10V output for dimming
↑ <b>Output switching current</b>	Nominal current per channel	Ch1 20A, Ch 2-8 10 A
	Maximum total channels load	90 A
	Max switching current	16A Resistive 8A Florescent
	Max Continues current	10A VAC
↑ <b>Output service life</b>	Mechanical service life	> 10,000,000 Times
↑ <b>Output switching times</b>	Operating time	15mS (at nomi. Volt)
	Releasing time	8 mS (at nomi. Volt)
	Max. operating frequency	20 cycle/min
↓ <b>Input</b>	Number of channels	8
	Input Type	Digital input. Open / Close
	Length of connected wire	< 350 meter
TISBUS <b>TIS Bus</b>	Number of devices on 1 line	Max. 64
	Bus voltage	12-32 V DC
	Current consumption (Normal)	<30 mA / 24 V DC
	Current consumption (Peak)	<50 mA / 24 V DC
	Protection	Reverse polarity protection
🕒 <b>Reaction time</b>		approx. 20ms
🔧 <b>Operation</b>	Programming button/LED	For assignment of the physical address
	2 buttons	Manually ON/OFF and programming
	By TIS bus	TIS protocol messages and commands
	Programming	Manual & via software
🔧 <b>Mounting</b>	Din rail	Standard 35 mm din rail
	Wall mount	screw holder on the back of the module
🔌 <b>Connection terminal</b>	Load and Power	Screw terminal 0,25...4mm <sup>2</sup>
	Data / bus	Male/female connectors Link + screw Terminal



Copyright © 2022 TIS, All Rights Reserved

TIS Logo is registered trademark of TIS CONTROL .  
All of the specification are subject to change without notice.

TIS CONTROL PTY LIMITED  
SA , AUSTRALIA

TIS CONTROL LIMITED  
Wanchai, Hong Kong

# TIS RCU MODULE



Room Control Unit with 8 Channels

Model: RCU-8OUT-8IN



## PRODUCT SPECIFICATIONS

<b>Functions</b>	Lighting control ON/OFF Dimming	8 separately controllable channels
	Curtain control	Can set 4 group of curtains open/close
	Fan speed control	Can set 2 group of fan speed options (low, med, high)
	Dimming	Ch 8 used with 0-10V output for dimming
	Scenes	8 different scenarios
	8 Digital inputs	Programmable inputs to connect to normal wall switches and sensors
<b>Weight</b>	Without packaging	400g
<b>Dimensions</b>	Width × Length × Height	144mm × 76mm × 90mm
<b>Housing</b>	Materials	Fireproof ABS
	Casing color	Black Gray
	Button color	Silver
	IP rating	IP 20
<b>Temperature range</b>	Operation	0...60°C
	Storage	-20...50°C
	Transport	-25...75°C
<b>Air humidity</b>		<85% non-condensing



Copyright © 2022 TIS, All Rights Reserved

TIS Logo is registered trademark of TIS CONTROL .  
All of the specification are subject to change without notice.

TIS CONTROL PTY LIMITED  
SA , AUSTRALIA

TIS CONTROL LIMITED  
Wanchai, Hong Kong