

## **TIS AIR BUS CONVERTOR**

With Power Supply

Data Sheet Rev 3.2

Model: TIS-AIR-BUS-3W







### **OVERVIEW**

This product is an AIR-BUS converter designed to create an instant connection between TIS wireless and wired network solutions to provide maximum harmony across home automation systems. It is installed next to or behind a wired module and is programmable via TIS App.

#### **KEY BENEFITS**

- Programming and communication port
- Bidirectional convertor: AIR-BUS/BUS-AIR
- TIS cloud server connection
- Internal timer and logic

#### **KEY FEATURES**

- Supplies power for TIS wired wall panels
- Compatibility with all types of back boxes
- Standard 35mm din rail mounted
- Controllable through TIS App.











# TIS AIR BUS CONVERTOR With Power Supply

Model: TIS-AIR-BUS-3W





PRODUCT SPECIFICATIONS			
•	Power supply	Input voltage	80-240 VAC 50/60 Hz
		Output power	3W / 12V
		Protection	Internal protection fuse
		Current consumption	10-30 mA / 12 V DC
	Protection	Bus connection	Reverse polarity protection
TISÂÎR	TIS AIR	WIFI signal	2.4 GHz
		Protocol standard	802.11 b/g/n
*	Manualina	Behind the panel	Attachable to the back of TIS panel, fits in all standard back box
To	Mounting	Din rail	Standard back box Standard size din rail mount
		Load and power	Screw terminal 0,252mm2
<del></del>	Connection terminal	Data / Bus	Connectors link
		Panel link	2 female connectors for TIS panel connection
		· and mix	
å	Weight	Without packaging	20g
+	Dimensions	Length × Width × Height	50mm × 24mm × 50mm
		Materials	Fireproof PC
	Housing	Casing color	White
		IP rating	IP 20
		Operation	-3060°C
	Temperature range	Storage	-2060°C
-		Transport	-3075°C
•	A in boomiditor		(DEB) pap condensing
8	Air humidity		<85% non-condensing







