

# **HD Entry Level Phone Xorcom UC902S**

**UC902SP** delivers superior HD audio quality, rich and leading-edge telephony features, all the functions of software are the same as other models. It is a perfect choice for small to medium businesses looking for a high quality, feature rich IP Phone at an affordable cost.











## Key Features and Benefits

#### 1. Friendly User-experience

**UC902S** supports many practical features, such as XML Browser, SCA, BLF List, call forward, call transfer, 5-way conferencing, etc., allowing users to enjoy a smoother and more efficient office experience at all times.

#### 2. HD Audio

**UC902S** not only upgrades its hardware such as handset, hands-free components and headset, but also supports Opus and other sound codecs, creating a clearer voice, and achieving HD sound quality under different network bandwidths, making remote communication close at hand and helping your team to more smoothly.

## 3. High Security and Wide Compatibility

**UC902S** supports SRTP and TLS which is the latest network security technology. Furthermore, UC902S is equipped with a dual firmware images function, which can prevent system crashes caused by upgrade failures and provide you with carrier-class system protection.

#### 4. Efficient Installation and Provisioning

Efficient installation using Xorcom's Endpoint Manager (EPM) allowing for a smooth and effortless provisioning of the phone on any CompletePBX system.

- · 132x48 pixel graphical LCD with backlight
- · 2 SIP accounts, 6 feature keys, 2 line keys
- · Local phonebook up to 1000 entries
- · Support Opus Codec
- · HD Voice: HD Codec, HD Speaker, HD Handset
- · Dual-port 10/100M Ethernet
- · PoE support
- · 5-way conferencing
- · Stand with one angle at 40°
- · Wall mountable
- · Support HDMS



# **Specifications**

#### **Phone Features**

- 2 SIP accounts
- · Call hold, mute, DND
- · One-touch speed dial, hotline
- Call forward, call waiting, call transfer
- · Redial, call return, auto answer, direct IP call
- 5-way conferencing
- · Group listening, SMS, emergency call
- · Ring tone selection/provisioning
- · Set date time automatically or manually
- · Dial plan for each account
- RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)
- · Action URL/URI

#### **Audio Features**

- HD Voice: HD Speaker, HD Handset, HD codec
- Codecs: iLBC, G.722, G.711(A/μ), Opus, G.723.1, G.729AB, G.726-32
- DTMF: In-band, RFC 2833, SIP INFO
- Full-duplex hands-free speakerphone with AEC
- · AEC, VAD, AGC, CNG, PLC, AJB

#### Directory

- Local phonebook up to 1000 entries
- XML/LDAP remote phonebook
- · Intelligent search method
- · Phonebook search/import/export
- · Call history: dialed/received/missed/forwarded
- Black list

#### **IP-PBX Features**

- Busy Lamp Field (BLF)
- Bridged Line Appearance (BLA)
- · Anonymous call, anonymous call rejection
- Voice mail
- · Intercom, paging
- · Call park, call pickup
- · Music on hold
- · Hot-desking
- Flexible seating
- · Call recording

#### Display and Indicator

- 132x48-pixel graphical LCD with backlight
- · LED for call and message waiting indication
- National language selection
- · Caller ID with name, number

#### Feature keys

- 2 line keys with LED
- · 6 feature keys: mute, headset, message transfer, redial, speaker
- · 4 context-sensitive soft keys
- 5 Navigation keys and volume control keys

#### Interface

- Dual-port 10/100M Ethernet
- Power over Ethernet (IEEE 802.3af), class 2
- 1xRJ9 (4P4C) handset port
- 1xRJ9 (4P4C) headset port

#### Physical Features

- Stand with one angle at 40°
- Wall mountable
- · External universal AC adapter : AC 100~240V input and DC 5V/1.2A output
- Power consumption (PSU): 1.6~2.6W
- Power consumption (PoE): 2.0~3.2W
- Operating humidity: 10~95%
- Operating temperature: -10~50°C

#### Management

- Configuration: browser/LCD-Menu/auto provision
- Auto provision via HTTP/HTTPS/FTP/TFTP
- · Auto-provision with PnP
- · Reset to factory, reboot
- · Local tracing log export, system log
- · Phone lock for personal privacy protection

### Network and Security

- SIP v1 (RFC2543), v2 (RFC3261)
- · SIP server/proxy redundancy
- NAT Traversal: STUN mode
- IP assignment: static/DHCP
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- DNS-NAPTR/DNS-SRV(RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS
- Transport Layer Security(TLS1.2), SRTP, ZRTP
- · HTTPS certificate manager
- · AES encryption for configuration file
- · Digest authentication using MD5/MD5-sess
- IEEE802.1X/OpenVPN
- IPv4/IPv6, LLDP/CDP/DHCP VLAN

### Package Features

- · Package content:
- Phone Device\*1pcs
- Footstand\*1pcs
- Handset\*1pcs
- Handset Cord\*1pcs
- Ethernet Cable\*1pcs
- Quick Reference Manual
- Power Adapter (Optional)
- · Qty/CTN:15pcs
- N.W/CTN:12.54kg
- G.W/CTN:13.59kg
- Phonebox Size:187mm(L)\*198mm(W)\*90mm(H)
- Carton Meas:585mm(L)\*475mm(W)\*220mm(H)

### Compliance







