



HA-614B202

4IN1SYSTEM

AHD TVI CVI ANALOG SUPPORT



AHD 6000SERIES

2M PIXEL **HD**
AHD Camera Series



HA-614B202

4in1 SYSTEM

AHD/TVI/CVI/ANALOG



Key Feature

- 1/2.9" CMOS progressive scan
- Image Resolution 1080P, 720P (H.264)
- 4-in-1(AHD/TVI/CVI/CVBS)
- Focal Length 3.2mm./F2.0
- IR SMD 18PCS / IR Distance 20-30M.
- Support IR Smart
- Support DAY&NIGHT
- Support OSD Menu, COC Control
- Lighting Protection 6KV
- Ingress Protection IP66

Specification

Model	HA-614B202
Image Sensor	1/2.9" CMOS Progressive Scan
Pixels	1080P/720P
Video System Output	4-in-1(AHD/TVI/CVI/CVBS)
Video Mode	AHD: 1080P/720P@25/30fps / CVI: 1080P/720P@25/30fps TVI: AHD 1080P/720P@25/30fps / CVBS: PAL/NTSC
Min. Illumination	0.1lux full color
Shutter Speed	1/25s-1/100,000s
Automatic Gain Control	Auto
Day&Night	EXT, AUTO, COLOR, B/W (default color)
Digital Wide Dynamic Range	Support DWDR
Exposure Mode	Groble, center, BLC, FLC
White Balance	Support ATW, MWB, Gray World
Digital Noise Reduction	Support 3DNR
Image Adjustment	Support brightness, contrast, sharpness, saturation
S/N Ratio	>58dB.
Signal System	PAL/NTSC
Lens	
Mount Type	M12
Auto Iris	Auto Electric Iris
Focal Length	3.2mm./F2.0
Focus Mode	Manual
Angle of View	82°
Infrared	
IR LED	IR SMD x 18 Pcs / IR Distance 20-30M.
IR Intensive	Support IR Smart
IR CUT	Support DAY&NIGHT
User Interface	
OSD Menu	Support (NO OSD Cable)
OSD Language	Support English/ Chinese / Japanese / Etc.
Control Over Coax (COC)	Support COC/UTC
Electrical	
Power	DC Jack 12V.±10%
Power Consumption	IR off 1-1.2W. / IR On 8-11W.
Environmental	
Operating Temperature	-30°C~+60°C
Storage Temperature	-30°C~+50°C
Working Humidity	10%~90% RH
Lighting Protection	6KV
Ingress Protection	IP66
Hardware Interface	
Video Output	BNC x1 (Female 1.0Vp-p at 75Ω)
Power Input	DC Jack x1 (DC12V)
Mechanical	
Case Material	Metal bullet
Dimension	188x75x102mm / Weight 510g