



H.265
Compression Code

2M Megapixel
Analog Camera Series



MIC

- 2MP**
Ultra HD
- Microphone Built-in
Support
- IP66
Waterproof Dustproof
- WDR
Digital
- DAY & Night
Support
- LED
Smart IR
- BLC
Support

FULL HD CAMERA SERIES
2Megapixel Analog Camera


MIC

H.265

 Compression Code


Feature

- 1/3" Progressive CMOS
- 2MP 1920(H)*1080(V)
- Min. Illumination Color 0.05lux@F1.2(AGC ON)
0Lux with IR ON
- Max, Framerate AHD/TVI/CVI: P/@25fps N/@30fps
CVBS: 960H
- Focal Length (Zoom Ratio) 3.6MM
- Min. Object Distance 2m
- Lens Type Fixed lens
- Audio Built-in Microphone
- Audio Range 7M
- IR Distance 20M
- Ingress Protection IP66
- Input Voltage/Current 12V DC

Specification

Model	HA-754B20M
Imaging Device	SC2332 1/3" Progressive CMOS
Scanning System	Progressive
Min. Illumination	0.05lux@F1.2(AGC ON), 0Lux with IR ON
Video Output	BNC
Resolution	2MP 1920 (H) * 1080 (V)
Max. Framerate	AHD / TVI / CVI: P / @25fps N / @30fps CVBS: 960H
Focal Length (Zoom Ratio)	3.6MM
Max. Aperture Ratio	F1.6
Angular Field of View	H:78.14 / V:40.24 / D:93.05
Min. Object Distance	2m
Lens Type	Fixed lens
Operational	
Audio	Built-in Microphone
Audio Range	7M
IR Distance	20M
On Screen Display	English
Day & Night	Ext / Color / B/W
Backlight Compensation	Off / User BLC
Wide Dynamic Range	D-WDR (Off/On)
Digital Noise Reduction	2D DNR
Gain Control	Auto
White Balance	ATW
Electronic Shutter Speed	Auto
Reverse	Mirror
Remote control interface	ACP (AHD Coax Protocol)
Video Transmission Distance	MAX 300M (Cable : 5C 2V)
Environmental	
Operating Temperature / Humidity	-30C ~ 50C / 90%
Ingress Protection	IP66
Electrical	
Input Voltage / Current	12V DC
Power Consumption	IR ON : 3.5W, IR OFF : 0.5W
Mechanical	
Color / Material	White / Plastic
Dimension (WxHxD)	TBD
Weight	250g

FULL HD CAMERA SERIES

2Megapixel Analog Camera