



# 2M Megapixel

Network Camera Series



**H.265**  
Compression Code

- 2M Pixel
- H.265 / H.264 Compression
- ONVIF Support
- PoE Support
- DAY & Night Support
- LED Smart IR
- BLC Support
- WDR Digital
- Audio Cable

## CAMERA 7800 SERIES

### 2Megapixel Network Camera



  
**AUDIO CABLE**

**H.265**  
Compression Code



## Feature

- 1/2.7" progressive scan CMOS
- 2.0 Megapixel 1920(H) x 1080(V)
- Dual Stream H.265, H.264
- Focal Length 3.6 mm
- IR Array 2 pcs
- Audio Support
- IR Distance Up to 50M.
- ONVIF 2.6
- Protection Level IP67
- Power supply 12VDC / POE

**CAMERA 7800 SERIES**  
2Megapixel Network Camera

## Specification

Model	HP-78A202PE
Resolution	2MP 1920(H) x 1080(V)
Image Sensor	1/2.7" Progressive CMOS
Min. Illumination	Color 0.1lux @ F1.2(AGC ON) B/W 0 lux @ IR ON
Shutter	1/5 ~ 1/20000s
Slow shutter	Support
Lens	3.6 mm H.FOV: 87
Day & Night	IR cut filter with auto switch (Day / Night / Auto / Schedule)
Digital noise reduction	3D DNR
WDR	Digital WDR
Video Compression	H.265 / H.264
Video bit rate	256Kbps ~ 8Mbps
Stream	Dual
Frame Rate	Main stream (1 ~ 25 fps) 1080P (1920x1080) 960P (1280x960), 720P (1280x720) Sub stream VGA (640x480), QVGA (320x240)
Image Settings	Flip mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable
BLC	Support
Privacy Mask	Support
Video Analytics	N/A
Protocols	TCP / IP, HTTP, DHCP, DNS, DDNS, RTP / RTSP, PPPoE SMTP, NTP, UPnP, SNMP, HTTPS, FTP
System Compatibility	ONVIF (Ver 2.6, Profile S, Profile G)
Interface	RJ45 10M / 100M Ethernet interface x1
Led	2pcs Array
IR Range	Up to 50m
SD storage	no
Alarm Trigger	no
Audio	Support
Video Output	no
Reset Button	no
PoE	yes
Water Proof	IP 67
Power Supply	DC 12V / POE
Consumption	≤ 7W
Dimension	∅ 81 X 243mm
Weight	appr. 350g
Storage Temperature	-30 ~ +60C
Operating Temperature	-30 ~ +55C