





NVR Wi-Fi 8ch H.265 Full HD 1080P

- Support Max. Wi-Fi range 300M. (Open area)
- Support Automatic connection with IP camera
- Support Automatically connection between NVR and IPC
- Support Mobile viewing iOS/Android (IP Pro)
- Support Wi-Fi repeater mode for IP Camera
- Support Auto bitrate
- Support PC online remote, EseeCloud (CMS)
- Support Build-in Wi-Fi module with high-performance
- Support Wi-Fi channel adjustable
- Support Web online www.e-seenet.com
- Support Video preview/recording/ playback/backup
- Support Free DDNS hiview.org
- Support System log search
- Support User management
- Support Upgrade system
- Support Auto Maintenance
- Support Bitrate Information
- Support Import/Export system config



Application
IP PRO3, Hiviewwifi

Specification

Model	HW-3308P
System	
Main CPU	Hisilicon Hi3536D
OS	Linuxed system
Menu GUI language	Thai, English, Chinese and more
Network Bandwidth	100MB/s
Hardware Interfaces	
HDMI	x1 (Max. 1920x1080P)
VGA	x1
SATA	x1 (Max. 6Tb.)
USB 2.0	x2
Wi-Fi Antena	x2
RJ45	x1 (100Mbps)
Video	
Video Compression	Standard H.265/H.264
Video Input	8Ch
Resolution	1080P
Video System	PAL/NTSC
Auto Add	Support auto add ipc
Live View	
Split Screen	x1,x4,x6,x8,x9 layout
HDMI resolution output	1080P@60Hz, 1080P@50Hz, 1440x900 1366x768, 1280x1024, 1024x768
OSD Alpha	Support
Auto Switch	Support (x1, x4 View)
E-Zoom	Support live view/playback mode
Color Adjust	Support
Recording	
Over Write	Support (Auto/Custom)
Record Plan	Time, Motion, Alarm, Manual
Main Stream	1920x1080@15fps, Bitrate 3Mbps.
Sub Stream	640x360@15fps, Bitrate 256 Kbps.
Video Compression	H.265/H.264
Bitrate Control	VBR/CBR
Image Quality Control	Adjustable
Back Up	U-Disk (AVI format)
Playback	
Local Playback layout	x1, x4 layout
Search Mode	Time, Motion, Manual, Alarm
Network	
Network Protocol	TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, 3G, FTP, Email
DDNS Provider	Hiview, Dyndns, 3322, Changeip, NO-IP, Oray, NVR163
Wireless Standard	Wi-Fi 802.11b/g/n
Application	iOS/Android (Ip pro)
User Interface	Browsers (IE), CMS, App
Onvif	Onvif 2.4
Alarm	
Alarm Type	Motion, Video loss
System Alarm	HDD error, Insufficient disk space Network Idisconnect, IP conflict, Record error
Alarm Triggering	Buzzer, Email Notice (Max. 2 receiver), App notice
Electrical	
Power Supply	DC12V/3A.
Power Consumption	3.6W (With out HDD)
Power Consumption	9.0W (With HDD)
Environmental	
Operating Temperature	-10 °C~+55 °C
Operating Humidity	10%-90%RH
Mechanic	
Case Material	Metal case
Dimension	258x210x42mm.

