



Wireless pan-tilt **IP CAMERA 3 MPIXEL**























- * Compact body, engineering plastic material, stylish, beautiful and refined
- * High-definition lens, automatic switching between day and night
- * Horizontal rotation of 340 degrees, vertical rotation of 90 degrees, APP controllable
- * Built-in high-sensitivity MIC and speaker, support two-way audio
- * Intelligent motion tracking, automatically tracking when people break into the area
- * Support cloud storage and local TF card video storage to ensure the safe storage of video data
- * Wifi connection, scan the QR code to easily connect the camera and the network, and the operation is simple and convenient
- * Area motion detection, push alarm information

| Model | HW-33ROBOT30W |
|----------------------------------|--|
| Pixel | змР |
| Image Sensor | 1/3" CMOS Sensor |
| Lens | 4mm |
| IR | 6pcs. |
| Pan and tilt angle | Pan 0 - 350 Tilt 58 |
| | Horizontal speed 20 / S |
| | Vertical speed 10 / S |
| Video stream | Main stream: 2304*1296; |
| | Sub-stream: 640*360 |
| Frame rate | 15fps |
| Image compression | H.264 / H.265 |
| Audio format | AAC / G711A |
| Human trucking | Support |
| Storage Interface | Support SD card (maximum 128G) |
| Audio function | Two-way audio built-in speaker, |
| | microphone |
| WIFI | Support, 2.4Ghz |
| Support protocols | TCP/IP, HTTP, DHCP, DNS, RTSP, NTP, UDP |
| Minimum illumination | Color: 0.01Lux,black and white: 0.001 Lux |
| Alarm function | Motion detection alarm,and push alarm info |
| Cloud storage | Support (Optional) |
| Working temperature and humidity | -20C~50C, Humidity is less than 95% |
| | (non-condensing) |
| Network protocol | Private protocol,support match to the |
| | wireless nvr kit |
| Infrared distance | 0-10 meters |
| Power supply | DC5V/1A (standard) |
| Power consumption | ≤3W |
| | |



Hiviewwifi







Wi-fi Camera