

## DS-K4H258D Two-Door Magnetic Lock



The DS-K4H258D Two-Door magnetic lock is designed for wooden door, glass door, and steel door with the opening angle of 90°. The maximum thrust of the lock is 280 kg (617 Lbs) × 2. It can be used for controlling door opening/closing, and the indicator shows the door status.

- Magnetic lock supports static linear thrust of 280 kg (617 Lbs) × 2
- Power supply can be 12VDC or 24VDC, (default voltage is 12VDC)
- Suitable for wooden door, glass door, metal door and fireproof door
- LED indicator displays door lock status
- Abrasion-proof materials

## ▪ Specification

General	
Indicator	Green: Working Status
Power supply	12 VDC, 340 mA × 2
Working temperature	-10 °C to 55 °C (14 °F to 131 °F)
Working humidity	0 to 95 % (relative humidity)
Dimensions	Lock Body: 500 mm × 45 mm × 25 mm (19.7" × 1.8" × 1.0") Armature Plate: 182 mm × 38 mm × 12.5 mm (7.2" × 1.5" × 0.5")
Weight	4.2 kg (9.3 lb)
Material	Shell: hard Anodizing Electroplating Operated Lock Body: eco-friendly Nickel Electroplating Operated Armature Plate: eco-friendly Zinc Electroplating Operated
Thrust	280 kg (617 lb) × 2 linear thrust
Door type	Single leaf, double leaf, wooden door, glass door, metal door, fireproof door
Magnetic Lock	
Unlock method	Current Interruption
Surface temperature	≤ Ambient Temperature 20 °C (68 °F)

## ▪ Available Model

DS-K4H258D

## ▪ Accessory

### ▪ Optional

DS-K4H258-LZ Value Series Magnetic Lock Bracket	DS-KAS261 Fingerprint Terminal Kit
	

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
www.hikvision.com



Follow us on social media to get the latest product and solution information.

