



TIS IO THERMOSTAT PANEL

Thermostatic Switch with 4 Buttons

Data Sheet Rev 3.2

Model: IO-AC-4G



OVERVIEW

This product is a BUS-operated wall switch with a rotating knob and push buttons for smart control over indoor climate, lights and motorized curtains. This switch is available in black and white and features customizable LED beklit for more applicability.

KEY BENEFITS

- + Integratable with other TIS solutions
- + Offering manual & automatic controls
- + Smooth & easy temperature adjustment
- + Customisable backlit for better interior designs

KEY FEATURES

- ★ Compatible with TIS couplers for added functionality
- ★ Climate data display on OLED 2.3"
- ★ Programmable for scenes & presets
- ★ Controllable via TIS App
















TIS IO THERMOSTAT PANEL



Thermostatic Switch with 4 Buttons

Model: IO-AC-4G



PRODUCT SPECIFICATIONS

 Input	Temp /Humidity Sensor Using Panel Addition	0-100C / 0-99% RH 2-3 Digital Inputs
 Output	Using Panel Addition 3R Using Panel Addition 3DL-12V Using Panel Addition 2DL-IRE	3 Relay Output 3A/5A 12V DC 50mA Output IR Emitter
 TIS Bus	Number of devices on 1 line Bus voltage Current consumption	Max. 64 12-32 V DC <50 mA / 24 V DC
 Protection		Reverse Polarity Protection ESD Protection
 Reaction time		approx. 20ms
 Connection terminal	Data	2 male pins connectors to fit in panel addition
 Operation	Display	2.3-inch OLED Screen
	Rotating Knob push buttons TIS bus	1× Rotating and pushing knob 4 push buttons with White/Orange LED TIS Protocol messages and commands
 Functions	Rotating / Press (knob) 1 Press (push button) Long Press (push button) Double click (push button)	Change Temperature / AC ON-OFF ON/OFF/Scene Dim or ramp the lights Extra Scene
 Weight	Without packaging	150 g
 Dimensions	Width × Length × Height	94mm × 23mm(including knob) × 129mm
 Housing	Materials	PC fire proof / acrylic in front
	Casing color	Silver plating frame, acrylic white or black
	Internal Parts color	Black & White
	IP rating	IP 50
 Temperature range	Operation	-10...60°C
	Storage	-20...50°C
	Transport	-25...75°C
 Air humidity		<80% non-condensing



Copyright © 2022 TIS, All Rights Reserved

TIS Logo is registered trademark of TIS CONTROL .
All of the specification are subject to change without notice.

TIS CONTROL PTY LIMITED
SA , AUSTRALIA

TIS CONTROL LIMITED
Wanchai, Hong Kong