




TIS IO OUTDOOR BELL PANEL

Outdoor Panel with Card Readability

Data Sheet Rev 3.2

Model: IO-OUT-HOTEL-RF



OVERVIEW


This product features a bell panel with RF readability and touch buttons for room services designed for maximum convenience and efficiency in hospitality facilities.

KEY BENEFITS

- + RF card reader & access control
- + Room number display
- + Hotel service indicator
- + Programmable RGB backlite
- + Push bell button with built-in relay switch

KEY FEATURES


- ★ Wall-mount panel
- ★ Works with TIS-BUS protocol
- ★ 4 Digital inputs for service button connection
- ★ Fits in all standard back boxes (US, UK, EU)



TIS IO OUTDOOR BELL PANEL

Outdoor Panel with Card Readability

Model: IO-OUT-HOTEL-RF



PRODUCT SPECIFICATIONS

	Input	RF card reader Dry Inputs	Temic RF Type 4 Digital Inputs
	Output	Low current relay	1 Relay Output 2A/12V
	TIS Bus	Number of devices on 1 line Bus voltage Current consumption	Max. 64 12-32 V DC <25 mA / 24 V DC
	Protection		Reverse Polarity Protection ESD Protection
	Reaction time		approx. 20ms
	Mounting	Wall mount	by 2 screws on the back box (UK, EU, US)
	Connection terminal	Data	2 male pins connectors to fit in panel addition
	Operation	Push buttons Backlight TIS bus Upgrading	1 Push button with red / white indicator 2 RGB indicators + Room number white LEDs TIS Protocol messages and commands By Rs485 upgrading kit
	Functions	Bell Press	Push button
	Weight	Without packaging	120g
	Dimensions	Width x Length x Height	94mm x 13mm x 129mm
	Housing	Materials Casing color Internal Parts color IP rating	PC fire proof / acrylic in front Silver plating frame. Glass black Black & White IP 50
	Temperature range	Operation Storage Transport	-10...60°C -20...50°C -25...75°C
	Air humidity		<80% non-condensing

