



NWA55AXE

802.11ax (WiFi 6) Dual-Radio Outdoor PoE Access Point

Thinking of upgrading to the 11ax (WiFi 6) technology for your outdoor wireless network? Zyxel NWA55AXE is your answer! Designed for harsh outdoor environments, the IP55-rated, weatherproof NWA55AXE is the best WiFi 6 outdoor access point to extend your wireless network outside.

The embedded Zyxel Smart Mesh Technology not only forms dynamic wireless links between APs for extended range, but can also bridge the wireless connectivity from one building to another. It is no doubt that NWA55AXE is an ideal choice for a simple expansion of your outdoor wireless network or forming an interconnected wireless network through outdoor inter-building links.

The downward pointing antenna position of NWA55AXE provides better protection against rain and moisture, whereas the traditional, upward pointing antenna design is prone to water leaks, having a potential of damaging the access point's internals. The external, detachable antenna design allows users to attach other antennas to better suit different demands.

Perfect for small business owners or SOHO users, the NWA55AXE supports both local GUI management and Nebula Cloud networking management. The simple setup allows you to quickly configure the AP with only a few clicks, making it super easy to set up guest and employee network on your own and start enjoying the ultra-fast WiFi 6 speeds in no time.



Dual-radio (2x2) 802.11ax AP provides maximum data rate of 1775 Mbps



Smart Mesh automatically forms dynamic wireless links to bridge networks for inter-building settings and mitigates complex, inconvenient cabling WiFi deployments



Excellent performance with WiFi 6 technology of high-speed transmission and low latency ensures a long-range of coverage for outdoor deployments



External, detachable antenna design allows users to attach other antennas that better suit different demands



Easy configuration setup with Zyxel's intuitive Nebula Cloud to get the network up and running in no time



Designed for harsh outdoor environment with up to IP55 weatherproof rating



Zyxel **one** network
Redefining network integration

Benefits

Effortless deployments and lower initial investment

Deployment of outdoor access points is a complex task that involves cabling, installation and maintenance. The NWA55AXE simplifies the process with its Smart Mesh Technology and external, detachable antennas that save your effort to install and adjust signal patterns. This makes NWA55AXE an ideal solution to extend reliable wireless connectivity to outdoor environments at an affordable price.

Bringing next generation WiFi within reach

WiFi 6 made tremendous improvement by introducing new technologies, such as orthogonal frequency-division multiple access (OFDMA), and spatial re-use, which is also referred to as Basic Service Set (BSS) coloring. It aims to simultaneously satisfy all requirements from rapidly growing mobile users. Zyxel's NWA55AXE is a true WiFi 6 access point which support essential 11ax functions that delivers faster performance and massive increased capacity, making the user experience even better.


Apart from running at 25% faster speed, NWA55AXE can also maximize WiFi efficiency by allowing simultaneous data transmission for multiple clients; thus, the airtime contention is no longer an issue here.

NebulaFlex – simply manage it your way!

The NebulaFlex provides extended flexibility, allowing users to easily switch between standalone and our intuitive cloud-managed NCC (Nebula Control Center) mode any time according to your needs without additional cost while protecting wireless technology investments.

The Nebula cloud management platform provides centralized control and visibility over all Nebula networking devices. You simply need to register the device on NCC, and it will automatically join, auto provision and begin to give real-time information. The intuitive platform allows you to group your access points together, control centrally, gain access to diagnostics tools and additional features like captive portal all under a single platform.

Specifications

Model	NWA55AXE	
Product name	802.11ax (WiFi 6) Dual-Radio Outdoor PoE Access Point	
		
Wireless		
Standard	IEEE 802.11 ax/ac/n/g/b/a	
MIMO	MU-MIMO	
Wireless speed	2.4 GHz	575 Mbps
	5 GHz	1200 Mbps
Frequency band	2.4 GHz	<ul style="list-style-type: none"> • USA (FCC): 2.412 to 2.462 GHz • Europe (ETSI): 2.412 to 2.472 GHz
	5 GHz	<ul style="list-style-type: none"> • USA (FCC): 5.15 to 5.35 GHz; 5.470 to 5.850 GHz • European (ETSI): 5.15 to 5.35 GHz; 5.470 to 5.725 GHz
Bandwidth	20-, 40-, 80-MHz	
Conducted typical transmit output power	US (2.4 GHz/5 GHz)	23/26 dBm
	EU (2.4 GHz/5 GHz)	20/25 dBm
RF Design		
Antenna type	2x2 external antenna	
Antenna gain	2.4 GHz	4 dBi
	5 GHz	5 dBi
Minimum receive sensitivity	Min. Rx sensitivity up to -99 dBm	
WLAN Feature		
Band steering	Yes	
WDS/Mesh	Yes	
Fast roaming	Yes	
DCS	Yes	
Load balancing	No	
Security		
Encryption	<ul style="list-style-type: none"> • WPA Personal • WPA2 Personal • WPA3 Personal 	
Authentication	No	
Access management	MAC filtering/Rogue AP detection	
Networking		
IPv6	Yes	
VLANs	Yes	
WMM	Yes	
U-APSD	Yes	

Model	NWA55AXE	
Management		
Operating mode	Cloud managed/standalone	
ZON Utility	<ul style="list-style-type: none"> • Discovery of Zyxel switches, APs and gateways • Centralized and batch configurations <ul style="list-style-type: none"> ▪ IP configuration ▪ IP renew ▪ Device reboot ▪ Device locating ▪ Web GUI access ▪ Firmware upgrade ▪ Password configuration 	
Zyxel Wireless Optimizer	WiFi AP planning	
Web UI/CLI	Yes	
SNMP	No	
Physical Specifications		
Item	Dimensions (WxDxH)(mm/in.)	308 x 136.4 x 49.6/12.13 x 5.37 x 1.95
	Weight (g/lb.)	580/1.28
Packing	Dimensions (WxDxH)(mm/in.)	221 x 188 x 59/8.70 x 7.40 x 2.32
	Weight (g/lb.)	887/1.96
Included accessories	<ul style="list-style-type: none"> • PoE injector • Mounting screws 	
MTBF (hr)	1,091,186	
Physical Interfaces		
Ethernet port	1 x 10/100/1000M LAN	
Power	PoE (802.3at): power draw 16 W	
Environmental Specifications		
Operating	Temperature	-20°C to 60°C/-4°F to 140°F
	Humidity	10% to 90% (non-condensing)
Storage	Temperature	-40°C to 70°C/-40°F to 158°F
	Humidity	10% to 90% (non-condensing)
Certifications		
Radio	CC Part 15C, FCC Part 15E; ETSI EN 300 328, EN 301 893; LP0002, EN 60601-1-2	
EMC	FCC Part 15B, EN 301 489-1; EN 301 489-17, EN55022, EN55024, EN61000-3-2/-3, BSMI CNS13438	
Safety	EN 60950-1, IEC 60950-1; BSMI CNS14336-1	

For more product information, visit us on the web at www.zyxel.com

Copyright © 2021 Zyxel and/or its affiliates. All rights reserved.
All specifications are subject to change without notice.

