

## Technical Specifications

### Mechanical

<b>Dimensions</b>	442.4 x 325 x 43.7 mm (17.4 x 12.8 x 1.7")
<b>Weight</b>	Without mounting brackets: 4.8 kg (10.6 lb) With mounting brackets: 4.9 kg (10.8 lb)
<b>Enclosure material</b>	SGCC steel

### Hardware

<b>Management interface</b>	Ethernet In-Band
<b>Networking interface</b>	(32) GbE RJ45 ports (16) 1/2.5 GbE RJ45 ports (4) 10G SFP+ ports
<b>Total non-blocking throughput</b>	112 Gbps
<b>Switching capacity</b>	224 Gbps
<b>Power method</b>	Universal input, 100—240V AC, 50/60 Hz USP RPS DC input
<b>Power supply</b>	AC/DC, internal, 100W
<b>Supported voltage range</b>	100—240V AC
<b>Max. power consumption</b>	100W
<b>LCM display</b>	(1) 1.3" touchscreen
<b>Button</b>	Factory reset
<b>Operating temperature</b>	-5 to 40° C (23 to 104° F)
<b>Operating humidity</b>	10 to 90% noncondensing
<b>Certifications</b>	CE, FCC, IC

### Etherlighting™

<b>Ethernet</b>	Locating Speed/link Native VLAN/network
<b>SFP+</b>	Locating Speed/link Native VLAN/network

### LEDs

<b>System</b>	Status
<b>RPS</b>	Status

### Application Requirements

<b>UniFi Network</b>	Version 8.0.24 and later
----------------------	--------------------------