



Newland AIDC
Scanning Made Simple



NLS-HR2000-BT

WIRELESS 2D BARCODE SCANNER

FEATURES

○ Outstanding Performance

Equipped with an outstanding CPU, this wireless handheld scanner can effortlessly capture high-density, high-volume and distorted barcodes printed on paper or displayed on screen.

○ Replaceable Battery

With 2600mAh battery, it will run a comfortable 16 hours of continuous use. Replaceable battery ensures continuous functionality and minimizes downtime.

○ Reliable Wireless Communication

Adopting the latest Bluetooth 5.0 technology, the NLS-HR2000-BT is able to maintain a reliable wireless connection to transmit data. The communication distances up to 100m.

○ Durable Construction

The NLS-HR2000-BT, built into an IP52-sealed and drop resistant (1.5m) housing with no moving parts, fortifies itself inside and out.



CMOS



1D Barcode



2D Barcode



IP Sealing



Drop



USB



2600mAh

NLS-HR2000-BT

Performance

Image Sensor	640×480 CMOS
Illumination	White LED
Aiming	Red LED
	ID: Code 11, Code 128, Code39, GSI-128(UCC/ENA-128), AIM 128, ISBT 128,Codabar, Code 93, UPC-A, UPC-E, Coupon, GSI Composite, EAN-13, EAN-8, ISSN, ISBN, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5, ITF-6, ITF-14, Standard 2 of 5,China Post 25, MSI-Plessey, Plessey, GSIDatabar(RSS).
	2D: PDF417, QR Code, Aztec, Data Matrix, Micro PDF417, Micro QR, Hanxin Code
Resolution*	≥3mil
Typical Depth of Field*	EAN-13: 50mm-260mm (13mil) Code 39: 50mm-120mm (5mil) PDF 417: 40mm-120mm (6.7mil) Data Matrix: 30mm-125mm (10mil)
Scan Angle**	Pitch: ±60°, Roll: 360°, Skew: ±60°
Field of View	Horizontal 45°, Vertical 34°
Min Symbol Contrast*	20%

Wireless

Communication Mode	Synchronous mode, asynchronous mode and batch mode
Radio Technology	Bluetooth 5.0
Communication Distance	100m (direct line of sight in open air)
Memory Capacity	16384 pieces
Battery	2600 mAh lithium-ion battery
Expected Charge Time	6 hours
Expected Battery Life	16 hours of continuous operation (scan once per 6 seconds)

Physical

Interface	USB Type-A (Support USB-KBW, USB-CDC, HID-POS)
Operating Voltage	5VDC±5%
Dimensions (L×W×H)	Scanner: 117.5×67.5×144mm; Cradle: 140×90×144.5mm
Weight	Scanner: 209g; Cradle:340.5g
Notification	Beep, LED, vibration

Environmental

Operating Temperature	-10°C to 50°C (14°F to 122°F)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)
Battery Charge Temperature	0°C to 45°C (32°F to 113°F)
Humidity	5%-95% (non-condensing)
ESD	±15 KV (air discharge); ±8 KV (direct discharge)
Drop	Scanner: 1.5m; Cradle: 1.2m
Sealing	IP52

Certificates

Certificates & Protection	CE Red, FCC ID, RoHS 2.0, IEC62471
---------------------------	------------------------------------

*Test conditions: T=23°C; Illumination=300lux using incandescent lamp; sample printed barcodes made by Newland.

**Test conditions: Scan Distance= (min. DOF + max. DOF)/2; T=23°C; Illumination=300lux using incandescent lamp;

2D: QR code (15mil); 10 Bytes.

Specifications are subject to change without notice.

Version: V1.1

Newland AIDC

Add: No.1 Rujiang West Rd.,
Mawei, Fuzhou, Fujian 350001, China
Tel: +86-591-83979500
Fax: +86-591-83979216
Email: info@newlandaidc.com
Web: www.newlandaidc.com

Asia Pacific

Add: 6 Raffles Quay #14-06
Singapore 048582
Email: info@newlandaidc.com

Europe & Middle East

Add: Rolweg 25, 4104 AV Culemborg,
The Netherlands
Tel: +31 (0) 345 87 00 33
Email: sales@newland-id.com
Tech Support: tech-support@newland-id.com

North America & Latin America

Add: 46559 Fremont Blvd.,
Fremont, CA 94538, USA
Tel: +1 510 490 3888
Fax: +1 510 490 3887
Email: info@newlandaidc.com