

LIMIT SWITCH BOX

SPECIFICATION

- Enclosure : Weatherprof IP67/NEMA4&4X (Standard) IP68 (Option)
- Solid and compact design
- Bolts on visual position indicator (Re-adjustment available upon required direction)
- Dual cable entries : 2 x 1/2 NPT (Standard)
- Terminal Strips : 8 points (0.08 - 2.5mm²)
- Captive cover bolts
- Easy mounting bracket NAMUR standard stainless steel shaft and bracket



FEATURES

- Solid and flexible design
Aluminium die-casting housing and powder coating.
- Bolts on visual position indicator
- Quick-set" cam
Spring loaded splined cam.
No need to adjust again after initial setting.
Easy setting without tool
- Dual cable entries
- Captive cover bolts
No worry to loose bolts while cover open.
Spring loaded cover bolts (APL-5N)
- Easy mounting bracket
NAMUR standard stainless steel shaft and bracket.
- Mechanical switch (2SPDT)
Standard switch : SS5GL (Omron)
Optional switch : SS10GL (Omron)

MATERIALS

Part	Materials
Housing cover & body	Aluminium die casting
Shaft	Stainless steel
Indicator cover	Polycarbonate
Cam	Polycarbonate
Spring	Stainless steel
Housing cover bolt	Stainless steel
O-Ring	NBR
Bushing	Bronze
E-Ring (shaft)	Stainless steel
Earth Lug	Stainless steel
Indicator	ABS/Polycarbonate
Bracket	Stainless steel

STRUCTURE



BRACKET

NAMUR STANDARD



Size : 30 x 80(130) H : 30(50)

