











Built for **Business**


High-Performance Wireless Ink Tank Printer for Small Businesses

The MAXIFY GX4070 makes your business look its best. Offering remarkable productivity for small work teams, this 4-in-1 inkjet printer provides ultra-affordable colour printing and a wide range of connectivity options.

 UP TO 21,000* COLOUR PAGES	 UP TO 9,000* MONO PAGES <small>*Economy Mode</small>	
 100/250 PLAIN PAPER CAPACITY	 35 35-SHEET ADF	 3-WAY PAPER FEEDING
 2.7" TOUCH	 FAX	 CONNECTIVITY

HIGHLIGHTER & WATER RESISTANT PRINTS

The quick-drying pigment ink ensures high-quality document printouts that resist fading or moisture and accidental exposure to water.



EASY MAINTENANCE

The easy-to-replace maintenance cartridge makes maintenance fuss-free and extends printer lifespan even when printing in high volumes.



FULL NETWORK COMPATIBILITY

Wireless and Wired LAN connectivity enhances installation flexibility. Print wirelessly and connect to smart devices directly.



COMPACT, SPACE SAVING FOOTPRINT

The printer's compact footprint allows it to fit into tight spaces with ease.



SPECIFICATIONS / MAXIFY GX4070

PRINT		Maximum Printing Resolution		600 (horizontal) x 1,200 (vertical) dpi		
PRINT	Print Speed ^{*1} (Mono/Colour)	ESAT/Simplex	18 / 13 ipm			
		ESAT/Duplex	10 / 8 ipm			
		FPOT Ready/Simplex	8 / 9 sec			
Auto 2-Sided Printing (not applicable for Rear Flat Tray)		Yes				
SCAN ^{*2}	Scanner Type		Flatbed (ADF / Platen)			
	Scanning Method		Contact Image Sensor (CIS)			
	Optical Resolution ^{*3}		1,200 x 2,400 dpi			
	Maximum Document Size	Flatbed	A4, LTR (216 x 297 mm)			
ADF		A4, LTR, LGL				
COPY	Copy Speed ^{*4}	Colour	sFCOT/Simplex	17 sec		
			sESAT/Simplex	11.1 ipm		
		ADF (Mono/Colour)	ESAT/Simplex	15.2 / 7.4 ipm		
	Maximum Copies		99 pages			
Maximum Document Size		A4, LTR				
FAX	Transmission Speed ^{*5}	Mono/Colour	3 sec / 1 min			
	Transmission/Reception Memory ^{*6}		250 pages			
	PC Fax		Windows: Available, Mac: Available			
	Automatic Dialing	Coded Speed Dialing (max.)		100 locations		
Group Dialing (max.)		99 locations				
PAPER HANDLING	Maximum Input Capacity	Rear Tray	Plain Paper (64 g/m ²)	Up to 100 sheets		
		Cassette	Plain Paper (64 g/m ²)	Up to 250 sheets		
		Rear Flat Tray	Paperboard	1 sheet		
		ADF	Plain Paper (64 g/m ²)	A4, LTR: 35 sheets, LGL: 5 sheets		
Media Size	Rear Tray	A4, A5, A6, B5, LTR, LGL, Foolscap, FS, Envelope (COM10, DL, C5, Monarch), Card Size (91 x 55 mm), 4 x 6", 5 x 7", 7 x 10", 8 x 10", Square (127 x 127 mm), Custom (width: 89 – 216 mm, length: 127 – 1,200 mm)				
	Cassette	A4, A5, B5, LTR, Executive, Custom (width: 148 – 215.9 mm, length: 210 – 297 mm)				
	Rear Flat Tray	A4, B5, LTR, Custom (width: 89 – 215.9 mm, length: 127 – 1,200 mm)				
	Auto 2-sided Printing		A4, LTR			
Media Type	Rear Tray	Plain Paper (64 – 105 g/m ²) High Resolution Paper (HR-101N) Photo Paper Plus Glossy II (PP-201/PP-208) Photo Paper Pro Luster (LU-101) Matte Photo Paper (MP-101) Double-Sided Matte Paper (MP-101D) Photo Stickers (PS-208/PS-808) Envelope				
	Cassette	Plain Paper (64 – 105 g/m ²)				
	Rear Flat Tray	Paperboard (thickness: 0.1 – 0.7 mm)				
NETWORK SYSTEM REQUIREMENTS & GENERAL SPECIFICATIONS	Operating System Compatibility	Please visit https://asia.canon.to to confirm OS compatibility and to download the latest drivers.		Windows 11 / 10 / 8.1 / 7 SP1 ^{*7} macOS 10.14.16 – 12 or later Chrome OS		
	Connectivity	Network		Wireless LAN IEEE802.11b/g/n/a ^{*8} /ac ^{*9} Wired LAN 100 Base-TX/10 Base-T		
		Interface		USB 2.0		
	Canon Printing Apps	Mobile		Canon PRINT, Easy-PhotoPrint Editor, Creative Park		
		Others		Easy Layout Editor, PosterArtist Lite, PosterArtist (Web), Canon Inkjet Smart Connect		
	Mobile/Cloud Printing Solutions		AirPrint, Mopria, Canon Print Service (Android), Direct Wireless, Cloud Service			
	Power		AC 100 – 240 V, 50/60 Hz			
	Power Consumption ^{*9}		20 W (Standby: 0.9 W)			
	Duty Cycle		Up to 33,000 pages/month			
	Recommended Monthly Print Volume		300 – 2,500 pages			
Operation Panel	Display		2.7" / 6.7 cm LCD (Touch Screen, Colour)			
Dimensions (WxDxH)	Factory Configuration		399 x 417 x 251 mm			
	Output/ADF Trays Extended		399 x 719 x 304 mm			
Weight		9.5 kg				
CONSUMABLES	Ink Bottles	Type/Colours		All Pigment Inks / Black, Cyan, Magenta, Yellow		
		Page Yield ^{*10} (Plain Paper)		A4 Colour Documents ^{*11} : GI-76 PGBK: 6,000 (Economy Mode ^{*12} : 9,000) GI-76 C, M, Y: 14,000 (Economy Mode ^{*12} : 21,000)		
	User Replaceable Maintenance Cartridge		MC-G03			

Specifications are subject to change without notice.

- Document print speeds are the averages of ESAT (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734. Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.
- TWAIN driver (ScanGear) is based on the TWAIN specification V1.9 and requires the Data Source Manager comes with the operating system.
- Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard. Optical resolution scan is available, only when you use TWAIN Driver.
- Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183. Copy speeds (ADF) are ESAT of copy in sequence, ISO/IEC24735. Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warm up time.
- Black & white document fax transmission speed is based on default setting using ITU-T No. 1 chart. Colour document fax transmission speed is based on default setting using Canon Colour Fax Test Sheet. Actual transmission speed may vary depending on document complexity, fax settings at receiving end, and line conditions etc.
- Page count is based on ITU-T No. 1 chart or Canon FAX Standard Chart No. 1.
- Operation can only be guaranteed on a PC with a pre-installed Windows 7 or later.
- Wireless LAN IEEE802.11a/ac are available for Taiwan models only.
- When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings.
- Page yields may vary depending on content coverage, print settings, temperature, humidity, and frequency of printing.
- Declared yield value is the estimated value based on Canon individual test method using the ISO/IEC 24712 colour chart and continuous printing simulation with the replacement ink bottles after initial setup. The colour yield is based on 1 set of composite colour bottles.
- The Economy mode reduces the ink consumption by lowering the density. More pages can be printed using this mode.



Delighting You Always

© Canon Singapore Pte Ltd 2022. All rights reserved.

CDG | Computer Peripheral and Supplies Ltd.

Computer Peripheral and Supplies Ltd.

244 Soi Pattanakarn 53, Pattanakarn, Suanluang, Bangkok 10250 Thailand

Contact Us

Tel : (66) 0-2322-9535, 0-2722-4040

Fax : (66) 0-2322-7990

E-Mail : sales.dept@cps.co.th

Web site : www.cps.co.th, www.facebook.com/cps.co.th

More Details

Scan Here

LINE ID

Need more

Information

