

Button	1 physical button	/	1 physical button	/
Installation	Surface mounting	Surface mounting	Surface mounting	Surface mounting
Indicator	2	/	2	/
Weight	Net weight: 0.190 kg Gross weight: 0.414 kg	Net weight: 350 g Gross weight: 675 g	Net weight: 0.190 kg Gross weight: 0.414 kg	Net weight: 355 g (0.8 lb) Gross weight: 683 g (1.5 lb)
Protective Level	IP65	/	IP65	/
Working Temperature	-40 °C to 55 °C(-40 °F to 131 °F)	-10 °C to 55 °C (14 °F to 131 °F)	-40 °C to 55 °C(-40 °F to 131 °F)	-10 °C to 55 °C (14 °F to 131 °F)
Working Humidity	10% to 95% (no-condensing)	10% to 90% (no-condensing)	10% to 95% (no-condensing)	10% to 90% (no-condensing)
Dimension (W × H × D)	138 mm × 65 mm × 27 mm (5.4" × 2.6" × 1.1")	200 mm × 140 mm × 15.1 mm (7.9" × 5.5" × 0.6")	138 mm × 65 mm × 27 mm (5.4" × 2.6" × 1.1")	200 mm × 140 mm × 15.1 mm (7.9" × 5.5" × 0.6")
Battery	/	/	/	/
Application Environment	Outdoor	Indoor	Outdoor	Indoor
Power Consumption	< 10 W	≤ 5 W	< 10 W	≤ 5 W
Language	English, French, Portuguese (Brazil), Spanish, Russian, German, Italian, Polish, Arabic, Turkish, Vietnamese, Hungarian, Dutch, Romanian, Czech, Bulgarian, Ukrainian, Croatian, Serbian, Portuguese, Slovak	English, Russian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese (Brazil), Spanish, Hebrew, Romanian, Turkish, Estonian, Danish, Swedish, Norwegian, Finnish, Vietnamese, Croatian, Slovenian, Serbian, Arabic, Portuguese (Portugal), Lithuanian, Uzbek, Kazakh, Mongolian, Ukrainian	English, French, Portuguese (Brazil), Spanish, Russian, German, Italian, Polish, Arabic, Turkish, Vietnamese, Hungarian, Dutch, Romanian, Czech, Bulgarian, Ukrainian, Croatian, Serbian, Portuguese, Slovak	English, Russian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese (Brazil), Spanish, Hebrew, Romanian, Turkish, Estonian, Danish, Swedish, Norwegian, Finnish, Vietnamese, Croatian, Slovenian, Serbian, Arabic, Portuguese (Portugal), Lithuanian, Uzbek, Kazakh, Mongolian, Ukrainian
Network Protocol	TCP/IP, RSTP	TCP/IP, SIP, RTSP	TCP/IP, RTSP	TCP/IP, SIP, RTSP
Wi-Fi	/	/	IEEE802.11b, IEEE802.11g, IEEE802.11n	2.4 GHz, IEEE802.11b, IEEE802.11g, IEEE802.11n
Bluetooth	/	/	Not supported.	/
3G/4G	/	/	/	/
Operation System	Linux	Linux	Linux	Linux
ROM	32 MB	32 MB	32 MB	32 MB
RAM	256 MB	128 MB	256 MB	128 MB
Processor	Embedded high performance processor	Embedded high performance processor	Embedded high performance processor	Embedded high performance processor
Lens	1	/	1	/
Resolution	/	1024 × 600	/	1024 × 600
FOV	Horizontal: 131° Vertical: 78°	Not supported.	Horizontal: 131° Vertical: 78°	/
Wide Dynamic Range (WDR)	Support 120 dB	/	Support 120 dB	/
Supplement Light	IR light, up to 3 m	N.A.	IR light, up to 3 m	N.A.
Video Compression Standard	H.264	/	H.264	/