



# iData P1 mini Thin & Rugged Android Industrial Tablet

Designed to enhance efficiency by building outstanding productivity

iData P1 mini is a new generation of thin and rugged Android industrial tablets. It adopts an 8-inch screen, with a thin and light main body, making it convenient for on-site operations. Its powerful configuration can meet the operation needs of enterprises in the next 3 to 5 years. Equipped with iData's latest scanning engine, it can improve operating efficiency significantly; Besides, it has a sturdy and durable housing design, making it genuinely competent in store management, warehouse management, production management, equipment inspection, etc.

## Excellent ergonomic design, convenient for on-site operations

Adopts an 8-inch screen, weighs only 580g, 13.3mm in thickness. This ultra-thin main body, together with first-of-its-kind side-edge dual scan buttons, makes it more convenient for users to work on-site. The whole device is extremely compact and small in size but has rich functional interfaces. It supports various interfaces, including type-C, USB, bottom pin port, and DC power port, making it convenient to access various terminals on-site.

## Outstanding performance to meet long-term use requirements

Regardless of core configurations such as processors and memory, as well as functional features such as front and rear cameras, large speakers, and accessories, all of them can satisfy the company's operational needs in the next 3 to 5 years; In particular, equipped with iData's latest generation self-developed scanning engine, it's able to reach longer scanning distance and wider reading range, making on-site operations more efficient.

## Sturdy and rugged, suitable for complex scenarios

The sturdy housing design makes the device more competent to work in complex environments. No matter if it falls to the ground accidentally or is even washed by water, the device can still operate normally; It is ultra-thin but has a long battery life. The large 7000mAh battery can survive an entire long shift, making it more reliable for long-term usage.



Store management



Inventory management



Sign for parcels and delivery



Production management

# P1 mini Technical Specifications

## System Configuration

Processor	Octa-core 2.0GHz high-performance processor
Operating System	Android 13.0
Memory (ROM+RAM)	64GB + 4GB (standard)
SIM	Two out of three SIM card slots, support dual SIM and dual standby. *Two out of three SIM card slots: two cards can be inserted at the same time, Nano SIM card + Nano SIM card /Nano SIM card +TF card
Expansion Slot	Micro SD card (up to 512 GB)
Display Screen	8-inch, resolution: 1280*800 pixels
Touch Screen	Industrial capacitive screen, support wet-hand operation/glove mode/multi-touch operation
Camera	13 megapixels rear camera, support PDAF/ auto-focus; 8 megapixels front camera
Flashlight	1A flashlight
Keypad	5 keypads in total: front scan key *2, power key on top *1, volume key on top *2
Battery	3.85V lithium battery, with 7000mAh, embedded
Audio	Microphone
Charging Method	Type-C charging, DC power interface and pin-port charging, support 18W fast charging
Reminder	Vibration reminder/LED reminder/high power speaker/audio reminder
Vibrating Motor	Built-in vibrating motor
Sensors	G-sensor/Proximity sensor/Light sensor/Geomagnetic sensor/Gyroscope
Intercom Function (Optional)	Support one-button PTT calls

## Structure Parameter

Dimension (L*W*D)	217mm*145mm*13.3mm
Weight	580g (battery included)

## Environmental Parameter

Working Temperature	-10°C - 50°C *Do not charge under low-temperature conditions for safety concerns
Storage Temperature	-30°C - 70°C (without battery)
Humidity	10%- 95% (no moisture condensation)
Drop Specification	Multiple drops resistance from the height of 1.2m
Roller Drop Specification	1000 times of roller drops from a height of 0.5 meter
Ingress Protection	IP65
ESD Protection	±15KV (air discharge), ±8KV (contact discharge)

## Scanning Engine

Barcode Type	It can scan one-dimensional / two-dimensional barcodes
Scanning Accuracy	≥3.33mil
Scanning Angle	Pitch: ±60°; Skew: ±45°; Tilt: 360°
View Angle	Horizontal: 44.3°, Vertical: 28.4°, Diagonal: 51°
Motion Error Tolerance	8m/s

## Communication Transmission

WWAN (Network Frequency)	2G: B2/B3/B5/B8 3G: WCDMA: B1/B2/B5/B8 4G: B1/B2/B3/B4/B5/B7/B8/B12/B17/B19/B20/B28A/B28B/B34/B38/B39/B40/B41
WWAN (Data Service)	GSM/GPRS/EDGE/UMTS/HSPA/HSPA+/WCDMA/TDD-LTE/FDD-LTE
WLAN Function	Wi-Fi 802.11a/b/g/n/ac (2.4G + 5G dual-band Wi-Fi), support fast roaming
Bluetooth	Bluetooth 5.0 BLE
GPS	GPS/AGPS/BDS/Galileo/GLONASS

## NFC (Optional)

Working Frequency	13.56 MHz
Reading Distance	Within 40 mm
Communication Protocol	ISO14443A/14443B/15693

## Development Support

Programming Language	Java
Development API	iScan API (Scanning Development Kits), Device API (Device Management/Configuration Development Kits), Android Standard Interface
Development Tool	Eclipse/Android Studio

## Communication Interface

USB Interface	Type-C 3.0 (with headset function) *1, Type-A USB 2.0*1, Micro HDMI interface *1
Power Interface	DC power interface*1
OTG Interface	Support

## Accessories (More details in accessories guide)

Standard Accessories	USB cable*1, device-back strap *1, power adapter*1
Optional Accessories	Power adapter (fast-charging), charging dock, extension dock, protective film, multifunctional cradle



Each product comes with a pack of practical and cost-effective accessories

## USB Cable

Type-C to USB cable, 1m in length, support charging and data transmission



CHA-USBC-GNR

## Device-back Strap

Attach on the device back to help you hold the device easily and firmly, avoid accidental drops



MNT-BS-P1 mini

## Power Adapter

Input voltage 100-240V, output 5V2A. Support plug types of China/Europe/UK/US/Australia, match with CHA-USBC-GNR  
ps: choose one that fits your local standard



CHA-PWAD-GNR-5V2A-EU

# P1 mini Optional Accessories for Charging

Improve management efficiency of devices and operational level of enterprises

## Power Adapter (fast-charging)

Input voltage 100-240V, output 9V2A. Support plug types of China/Europe/UK/US/Australia, match with CHA-USBC-GNR  
ps: choose one that fits your local standard



CHA-PWAD-P1-9V2A-EU

## Extension Dock

Support charging for 1 main unit. Support 3 Type-A interfaces, 1 Type-B interface, 1 RS232 interface, 1 RJ45(1000Mbps)interface.  
It can be used to expand other accessories.  
ps: you may have one of the power adapters



CHA-EXTD-P1

Improve management efficiency of devices and operational level of enterprises

## Charging Dock

Support charging for 1 main unit. The device starts charging when matching with CHA-USBC-GNR and CHA-PWAD-P1-9V2A-CN accessories.



CHA-CHAD-P1

Enhance user experience and improve working efficiency

## Multifunctional Cradle

The multifunction cradle is composed of four parts: the host cradle, the extension cradle, the round-port cradle, and the square-port cradle. It has four connection ways (host+round-port cradle, host+extension+round-port cradle, host+square-port cradle, host+extension+square-port cradle) The joint can be rotated flexibly to enable the tablet to be installed in the workbench, work control desk, etc., improving worker's efficiency.

PS: you can choose the connection ways and cradles based on your installment

MNT-MC-P1



Host cradle



Extension cradle



Round-port cradle



Square-port cradle



## Lower risks of malfunction during usage, extend the lifespan of devices

### Protective Film

Protective film for touchscreen. It can protect the screen from cracking or being scratched in case there's any accidental drops or impact during usage



PRT-PTF-P1 mini

