

360° Omnidirectional audio pickup, guarantees everyone to be heard

Engineered to fill up large conference room with clear sound, MAXHUB SPEAKERPHONE supports 360-degree omnidirectional audio pickup.

6 Array |

360° Omnidirectional 5 Meters⁴
Sound pick up





Get crystal clear calls with MAXHUB SPEAKERPHONE

PZM structure design High Performance

Acoustic Echo Cancellation | **Noise Reduction**

Set up in seconds, that's it

Seamless Connection

Plug and Play

Multiple Devices Connection

Supports 8-hour of talk-time on a single charge

Supports wireless charging.

8 hours | Wireless Charging

To support 360° omnidirectional audio pickup, MAXHUB SPEAKERPHONE needs to be unobstructed, Wireless charging is optional, and an extra dual-mode wireless charger is required for this function, Based on tests results from MAXHUB Lab, the actual usage time depends on the environment and batter onsumption,

4.Based on tests results from MAXHUB Lab, test environment is within a meeting room with reverberation time less than Is, voice being recognizable identified as effective audio pick up, 5.To achieve ideal results, MAXHUB recommends using MAXHUB USB cable and MAXHUB audio cable, which

Product Specification Audio Pick-up Pickup Distance 5 meters radius Microphone 6 array microphones 100 Hz**-**15kHz Frequency Sensitivity -38dBV Signal to Noise Ratio 65dB Amplification 90dB SPL@0.5m, 1kHz Touch Technology Writing Tools ≦1% @1W/1kHz Writing Accuracy ≥75dB Supported Electromagnetic Pen 150Hz~15kHz **Operating System** USB Type C (audio in/out + charge 5V/2A) Port AUX 3.5MM (audio in/out) Bluetooth BT4.2+EDR Mode Music mode/call mode (under Bluetooth mode) Buttons 6 (power, answer/hang up, mute, Bluetooth, volume+, volume-) Indicator Light Power & Volume Indication **Physical Specification** Dimension (Diameter*Height) 120mm*35mm Net Weight 380g Color Dark Gray Battery **Battery Capacity** 7.4V/2200mAh Wire 5V/2A Charging Requirement Wireless 5W/dual mode (optional) Lifetime on a single charge Up to 8 hours **Operating Environment** 0°C ~40°C Operating Temperature Operating Humidity 10% ~ 90% Storage Temperature -20℃ ~ 60℃ Storage Humidity 10% ~ 90% Operating Altitude 5000 meters and below



: www.cps.co.th

Follow Us











^{*} All data from MAXHUB lab.